



# CONTRACTOR/ INDUSTRIAL



Coleman Cable Inc.

A tradition of excellence...

## Exceptional Performance.

**Coleman Cable Inc.** is a worldwide leader in the development, design, manufacture, marketing & distribution of wire and cable products. A Broad Range of Products, Innovative Solutions, Recognized Brands, and a Solid Service Platform are the foundation that Coleman Cable's Dedicated, Professional People build upon to create Customer Value. These characteristics, combined with strategic acquisitions, such as Copperfield and Woods, establish and strengthen Coleman Cable's leadership position as a premier US-based manufacturer of electrical, electronic and assembled wire and cable products.

**Coleman Cable** is one of the most trusted names in the industry for reliability, innovation and quality performance. Our product offering includes products from market leading brands such as Polar/Solar®, Yellow Jacket®, X-Treme Box™, Luma-Site®, Seoprene®, Royal®/Excelene® and many others. Coleman Cable's technical expertise and commitment to innovation ensure the most advanced and highest quality products on the market.

Polar/Solar® cords, made with Coleman's exclusive T\*Prene® insulation, stay flexible even under the most extreme temperatures. They weigh less and are 2-1/2 times more abrasion resistant than ordinary cords. Available in 16, 14, 12 and 10 gauge and in 25, 50 and 100 ft. lengths. Meets OSHA hard usage requirements.

Coleman Cable's X-Treme Box™ provides work-site power distribution that's economical, rugged, and most of all safe! Now available in two versions to meet contractor demands. The new roll cage designs are constructed with a tubular steel frame for added durability and are vertically stackable for easy transportation. The X-Treme Box™ provides you with a portable, reliable distribution center that withstands the harshest jobsite conditions.



# TABLE OF CONTENTS

<b>Outdoor Cords, Power Products, GFCI</b> . . . . .	<b>.4-15</b>
<b>Lighting Products</b> . . . . .	<b>.16-21</b>
<b>Bulk Wire</b> . . . . .	<b>.22-33</b>
<b>Consumer Products</b> . . . . .	<b>.34-41</b>
<b>Index</b> . . . . .	<b>.42-45</b>
<b>Common Abbreviations &amp; Wire Terms</b> . . . . .	<b>.45</b>

## ***OUTDOOR CORDS, POWER PRODUCTS, GFCI***

<b>Polar/Solar® Extension Cords</b> . . . . .	<b>.4-5</b>
<b>Yellow Jacket® Outdoor Extension Cords</b> . . . . .	<b>.6</b>
<b>Vinyl Extension Cords</b> . . . . .	<b>.6-7</b>
<b>Cord Runner™ Multi-Outlet Extension Cords</b> . . . . .	<b>.7</b>
<b>Cool Colors™ and Stripes™ Extension Cords</b> . . . . .	<b>.8</b>
<b>Red, White &amp; Blue Extension Cords</b> . . . . .	<b>.9</b>
<b>Locking Extension Cords</b> . . . . .	<b>.9</b>
<b>Cold Flex Extension Cords</b> . . . . .	<b>.9</b>
<b>Custom Extension Cords</b> . . . . .	<b>.10</b>
<b>Replacement Plugs and Connectors</b> . . . . .	<b>.11</b>
<b>X-Treme Box™ Temp Power Boxes</b> . . . . .	<b>.12</b>
Temp Power Extensions Cords . . . . .	.12
Replacement Ends/Adapters . . . . .	.12
<b>Disaster Recovery &amp; Restoration Cords</b> . . . . .	<b>.13</b>
<b>Generator Power Cords</b> . . . . .	<b>.13</b>
<b>Twist-To-Lock Extension Cords</b> . . . . .	<b>.13</b>
<b>“Y” and “W” Adapters</b> . . . . .	<b>.13</b>
<b>Generator Power Cords and Adapters</b> . . . . .	<b>.14</b>
<b>Twist-To-Lock Adapters</b> . . . . .	<b>.14</b>
<b>Adapters</b> . . . . .	<b>.14</b>
<b>GFCI– Ground Fault Circuit Interrupters</b> . . . . .	<b>.15</b>





## Polar/Solar®

America's premier extension cord, Polar/Solar® is lightweight and stays flexible to -67°F. Its rugged T\*Prene® insulation provides superior resistance to abrasion, ozone, oil, grease, and chemicals. Plus, the outer jacket is flame retardant and water resistant. Polar/Solar® Extension Cords feature a power indicator light in the female receptacle to show that the power is on.



### Polar/Solar®

*T\*Prene® Insulated Cord with Power Indicator Light*



CAT NO	WIRE GA/COND	WIRE TYPE	COLOR	LENGTH IN FT	PACKAGE TYPE	125V RATING	MASTER PACK	MASTER WT	MASTER PACK CUBE
01287	16/3	SJEOW	Yellow	25	Sleeve	13A	12	19	.64
01288	16/3	SJEOW	Yellow	50	Sleeve	13A	12	38	1.41
01289	16/3	SJEOW	Yellow	100	Sleeve	10A	6	35	1.57
01487	14/3	SJEOW	Yellow	25	Sleeve	15A	12	27	1.14
01488	14/3	SJEOW	Yellow	50	Sleeve	15A	6	26	1.14
01489	14/3	SJEOW	Yellow	100	Sleeve	13A	6	49	1.14
01687	12/3	SJEOW	Yellow	25	Sleeve	15A	12	39	1.57
01688	12/3	SJEOW	Yellow	50	Sleeve	15A	6	38	1.41
01689	12/3	SJEOW	Yellow	100	Box	15A	4	48	2.02
01788*	10/3	SJEOW	Yellow	50	Box	15A*	4	42	2.02
01789*	10/3	SJEOW	Yellow	100	Box	15A*	3	63	1.25

\* Not CSA Listed



01769

### Polar/Solar® Extra-Hard Service

*T\*Prene® Insulation and Power Indicator Light - 600 Volt Rated*



CAT NO	WIRE GA/COND	WIRE TYPE	COLOR	LENGTH IN FT	PACKAGE TYPE	125V RATING	MASTER PACK	MASTER WT	MASTER PACK CUBE
01567	14/3	SEOW	Yellow	25	Sleeve	15A	6	24	1.41
01568	14/3	SEOW	Yellow	50	Box	15A	4	32	2.02
01569	14/3	SEOW	Yellow	100	Box	13A	3	46	1.25
01767	12/3	SEOW	Yellow	25	Sleeve	15A	6	31	1.41
01768	12/3	SEOW	Yellow	50	Box	15A	4	39	1.87
01769	12/3	SEOW	Yellow	100	Box	15A	3	57	1.25

### Polar/Solar® Tri-Source® Three-Way Power Blocks

*Power Block with T\*Prene® Insulation and Power Indicator Light*



03488

CAT NO	WIRE GA/COND	WIRE TYPE	COLOR	LENGTH IN FT	PACKAGE TYPE	125V RATING	MASTER PACK	MASTER WT	MASTER PACK CUBE
03482	12/3	SEOW	Yellow	2	Sleeve	15A	12	10	.64
03487	12/3	SJEOW	Yellow	25	Sleeve	15A	12	42	1.41
03488	12/3	SJEOW	Yellow	50	Sleeve	15A	6	39	1.41
03489	12/3	SJEOW	Yellow	100	Box	15A	4	49	2.02
03588***	10/3	SJEOW	Yellow	50	Box	15A*	4	43	2.02
03589***	10/3	SJEOW	Yellow	100	Box	15A*	3	62	1.25

\* Cap and Connector rated 15A

\*\*\* Not UL, CSA Listed



## Polar/Solar® Quadnector® Four-Way Power Blocks

### T\*Prene® Insulation and Lighted End

Designed with a handy eyelet for easy hanging and storage. Rated for indoor use only.

Made to meet  
OSHA  
Specifications

MADE IN  
THE USA



CAT NO	WIRE GA/COND	WIRE TYPE	COLOR	LENGTH IN FT	PACKAGE TYPE	125V RATING	MASTER PACK	MASTER WT	MASTER PACK CUBE
<b>Polar/Solar Plus™</b>									
04422	12/3	SJEOW	Yellow	6	Sleeve	15A	6	9	.64
04427	12/3	SJEOW	Yellow	25	Sleeve	15A	6	24	1.14
04428	12/3	SJEOW	Yellow	50	Box	15A	4	30	2.02
04429	12/3	SJEOW	Yellow	100	Box	15A	4	53	2.02
<b>Polar/Solar Plus™ – 600 Volt Rated</b>									
04522	12/3	SEOW	Yellow	6	Sleeve	15A	6	11	.64



## Polar/Solar® Coiled Extension Cords

### Tangle-Free Self-Coiling Cord Never Needs Winding

COILEX® extension cords offer coiled cord flexibility with Polar/Solar® cord toughness. Molded right angle plug helps prevent accidental disconnection.

MADE IN  
THE USA



CAT NO	WIRE GA/COND	WIRE TYPE	COLOR	LENGTH IN FT	PACKAGE TYPE	125V RATING	MASTER PACK	MASTER WT	MASTER PACK CUBE
01220*	16/3	SJEOW	Black	1-5	Sleeve	13A	6	5	.59
01226	16/3	SJEOW	Black	4-20	Sleeve	13A	12	29	1.14

\* Includes belt-clip attachment.



## Polar/Solar® Coiled Retractable Cords

Conveniently coiled to extend or retract with ease. The cords listed below do not include molded ends.

Contact factory for minimum quantities on variations in size, length and plug configurations.

MADE IN  
THE USA



CAT NO	WIRE GA/COND	WIRE TYPE	COLOR	LENGTH IN FT	PACKAGE TYPE	125V RATING	MASTER PACK	MASTER WT	MASTER PACK CUBE
09809	18/2	SJEOW	Black	4-20	Box	–	10	14	1.14
09810	18/3	SJEOW	Black	4-20	Box	–	12	21	1.41
09811	18/4	SJEOW	Black	4-20	Box	–	10	19	1.14
09812	16/2	SJEOW	Black	4-20	Box	–	10	17	1.14
09813	16/3	SJEOW	Black	4-20	Box	–	10	21	1.14
09814	16/4	SJEOW	Black	4-20	Box	–	10	25	1.41
<b>Polar/Solar Plus™ – 600 Volt Rated</b>									
09815	14/3	SEOW	Black	4-20	Box	–	5	29	1.41
09816	12/3	SEOW	Black	4-20	Box	–	5	37	1.41





## Yellow Jacket® Outdoor Extension Cords

Exclusive Yellow Jacket compound is more flexible and abrasion resistant at any temperature than standard vinyl compounds. Yellow Jacket extension cords feature a power indicator light in the female receptacle to show that the power is on.



2886

CAT NO	WIRE GA/COND	WIRE TYPE	COLOR	LENGTH IN FT	PACKAGE TYPE	125V RATING	MASTER PACK	MASTER WT	MASTER PACK CUBE
2886	14/3	SJTW	Yellow	25	Sleeve	15A	12	29	0.82
2887	14/3	SJTW	Yellow	50	Sleeve	15A	6	29	0.93
2888	14/3	SJTW	Yellow	100	Sleeve	15A	3	26	0.79
2883	12/3	SJTW	Yellow	25	Sleeve	15A	6	23	0.64
2884	12/3	SJTW	Yellow	50	Sleeve	15A	4	31	0.75
2885	12/3	SJTW	Yellow	100	Box	15A	2	27	0.79
2805	10/3	SJTW	Yellow	50	Box	15A*	2	21	1.02
2806	10/3	SJTW	Yellow	100	Box	15A*	2	42	2.35
<b>Yellow Jacket Power Blocks</b>									
2882	12/3	STW	Yellow	2	Sleeve	15A	10	11	0.48
2827	12/3	SJTW	Yellow	50	Box	15A	4	27	0.79
2820	12/3	SJTW	Yellow	100	Box	15A	2	26	1.02

\* Cap & connector rated 15A

## Vinyl Outdoor Extension Cords



Molded, water resistant connectors with reinforced blades make these cords suitable for outdoor use.



02307



02408



02589

CAT NO	WIRE GA/COND	WIRE TYPE	COLOR	LENGTH IN FT	PACKAGE TYPE	125V RATING	PACK QTY	MASTER WT	MASTER PACK CUBE
<b>Three Conductor</b>									
02304	16/3	SJTW	Orange	10	Sleeve	13A	24	18	.75
02211	16/3	SJOW	Black	10	Sleeve	13A	24	19	.79
02305	16/3	SJTW	Orange	15	Sleeve	13A	18	24	.76
02306	16/3	SJTW	Black	15	Sleeve	13A	18	24	.75
02307	16/3	SJTW	Orange	25	Sleeve	13A	12	25	.76
02308	16/3	SJTW	Orange	50	Sleeve	13A	12	46	1.16
02309	16/3	SJTW	Orange	100	Sleeve	10A	6	45	1.19
02407	14/3	SJTW	Red	25	Sleeve	15A	12	35	.90
02408	14/3	SJTW	Red	50	Sleeve	15A	6	29	.82
02409	14/3	SJTW	Red	100	Sleeve	13A	6	60	1.41
<b>Three Conductor - Lighted End</b>									
02587	12/3	SJTW	Yellow	25	Sleeve	15A	12	40	1.21
02588~	12/3	SJTW	Yellow	50	Sleeve	15A	6	40	1.41
02589~	12/3	SJTW	Yellow	100	Sleeve	15A	4	52	1.41
02687	10/3	SJTW	Yellow	25	Sleeve	15A**	6	36	1.14
02688	10/3	SJTW	Yellow	50	Box	15A**	4	48	1.00
02689	10/3	SJTW	Yellow	100	Box	15A**	3	70	1.25
<b>Three Conductor Large Cap and Conductor - 600 Volt Rated</b>									
02457~	14/3	STW	Orange	25	Sleeve	15A	6	26	1.41
02458~	14/3	STW	Orange	50	Box	15A	4	34	2.02
02459~	14/3	STW	Orange	100	Box	13A	3	50	1.25
02557~	12/3	STW	Orange	25	Sleeve	15A	6	34	2.38
02558~	12/3	STW	Orange	50	Box	15A	4	45	2.02
02559~	12/3	STW	Orange	100	Box	15A	3	65	1.25

\*\* Plug and receptacle rated 15A

~ Made in U.S.A.

# Multi-Outlet Vinyl Extension Cords



## Three- and Four-Way Power Blocks

Innovative block provides additional outlets for power distribution. Vinyl jacket resists moisture, abrasion, and prolonged exposure to sunlight. Reinforced blades help prevent accidental bending or breaking and a heavy-duty strain relief protects electrical connections resulting in longer cord life.



04112



04187

CAT NO	WIRE GA/COND	WIRE TYPE	COLOR	LENGTH IN FT	PACKAGE TYPE	125V RATING	MASTER PACK	MASTER WT	MASTER PACK CUBE
<b>Tri-Source® Three-Way Power Block</b>									
04004	14/3	SJTW	Orange	6	Sleeve	15A	18	19	.77
04217	14/3	SJTW	Red	25	Sleeve	15A	12	33	.94
04218	14/3	SJTW	Red	50	Sleeve	15A	6	30	.85
04219	14/3	SJTW	Red	100	Sleeve	13A	6	55	1.43
04112	12/3	STW	Yellow	2	Sleeve	15A	12	11	.40
<b>Tri-Source® Three-Way Power Block with Lighted End</b>									
04187	12/3	SJTW	Yellow	25	Sleeve	15A	12	45	1.34
04188	12/3	SJTW	Yellow	50	Sleeve	15A	6	42	1.14
04189	12/3	SJTW	Yellow	100	Sleeve	15A	4	53	1.28
04388	10/3	SJTW	Yellow	50	Box	15A	4	48	1.98
04389	10/3	SJTW	Yellow	100	Box	15A	3	72	1.98
<b>Quadnector® Four-Way Power Block</b>									
04102*~	12/3	SJTW	Orange	6	Sleeve	15A	6	9	.64
04107*~	12/3	SJTW	Orange	25	Sleeve	15A	6	25	1.14
04108*~	12/3	SJTW	Orange	50	Box	15A	4	32	2.02
04109*~	12/3	SJTW	Orange	100	Box	15A	4	56	2.02
<b>Quadnector® Four-Way Power Block - 600 volt Rated</b>									
04207*~	12/3	STW	Orange	25	Sleeve	15A	6	36	2.36
04208*~	12/3	STW	Orange	50	Box	15A	4	47	2.02
04209*~	12/3	STW	Orange	100	Box	15A	3	67	1.25

\* Rated for Indoor Use Only

~ Made in U.S.A.



## Cord Runner™ Multi-Outlet Outdoor Extension Cords

These heavy-duty multi-outlet extension cords have 3 lighted outlets spaced evenly along the length of the cord, making them perfect for landscaping, workshop and holiday decorating applications. The heavy-duty STW cord jacket is super flexible and durable, and outlet covers help keep water and dust out.



09001-02

CAT NO	WIRE GA/COND	WIRE TYPE	COLOR	LENGTH IN FT	PACKAGE TYPE	125V RATING	MASTER PACK	MASTER WT	MASTER PACK CUBE
09001-02	14/3	STW	Yellow	25	Sleeve	15A	4	20	.78
09001-05	14/3	STW	Green	25	Sleeve	15A	4	20	.78
09002-02	14/3	STW	Yellow	6	Sleeve	15A	6	8	.65
09003-02	12/3	STW	Yellow	50	Box	15A	4	45	2.37





## Cool Colors™ Outdoor Extension Cords

Made to meet  
OSHA  
Specifications

Contractor Grade SJTW cord features a jacket in a variety of colors for added safety and theft deterrence on the jobsite. Features clear molded plugs with power indicator light in the female receptacle. Added features include heavy duty strain relief and reinforced blades and ground pin.

CAT NO	WIRE GA/COND	WIRE TYPE	NEON COLOR	LENGTH IN FT	PACKAGE TYPE	125V RATING	MASTER PACK	MASTER WT	MASTER PACK CUBE
02577-00-XX	12/3	SJTW	See Colors Below*	25	Sleeve	15A	12	40	1.41
02578-00-XX	12/3	SJTW		50	Sleeve	15A	8	53	1.41
02579-00-XX	12/3	SJTW		100	Sleeve	13A	4	52	1.41

\*Color (XX): 0A= Pink; 0H=Blue; 0X=Green



## Stripes™ Outdoor Extension Cords

Made to meet  
OSHA  
Specifications

Increase safety awareness and help to prevent jobsite loss or theft with STRIPES™ outdoor extension cords. Each extension cord features a dominant color and an extruded colored stripe that runs the length of the cord. All STRIPES™ extension cords have a power indicator light in the receptacle to show that the power is on.

CAT NO	WIRE GA/COND	WIRE TYPE	NEON COLOR	LENGTH IN FT	PACKAGE TYPE	125V RATING	MASTER PACK	MASTER WT	MASTER PACK CUBE
02548-00-XX	12/3	SJTW	See Color Combinations Below**	50	Sleeve	15A	8	53	1.41
02549-00-XX	12/3	SJTW		100	Sleeve	15A	4	52	1.41
02648-00-XX	10/3	SJTW		50	Disk	15A	4	46	1.41
02649-00-XX	10/3	SJTW		100	Disk	15A	3	68	1.41

12/3: \*\*Color (XX): 54=Lime Green/Red; 22=Yellow Purple; 52=Dark Green/Yellow; 64=Blue/Red; 41=Red/White; 77=Pink/Lime Green; 3V=Orange/Blue  
10/3: 54=Lime Green/Red; 64=Blue/Red





02549-USA1

## Red, White & Blue Extension Cords



Display America's colors on the jobsite with the rugged Red, White and Blue contractor grade extension cord, dedicated to the American Contractor. Highly visible red cord, with two extruded white stripes and blue stenciled stripe the length of cord with "MADE IN THE USA by CCI\*\*\*\*PROUD TO BE AMERICAN". Pro-Power contractor grade extension cords all have molded water resistant connectors with reinforced blades that make them suitable for all weather outdoor use. The lighted female ends let you know that there is power ready and available.

CAT NO	WIRE GA/COND	WIRE TYPE	COLOR	LENGTH IN FT	PACKAGE TYPE	125V RATING	MASTER PACK	MASTER WT	MASTER PACK CUBE
02548-USA1	12/3	SJTW	Red, White & Blue	50	Sleeve	15A	8	53	1.41
02549-USA1	12/3	SJTW	Red, White & Blue	100	Sleeve	15A	4	52	1.41



02438

## Locking Extension Cords



New Locking Extension Cords keep tools locked into power, eliminating the frustration and hassle of tools coming unplugged - these cords provide a positive lock and can be disengaged only by choice.

CAT NO	WIRE GA/COND	WIRE TYPE	COLOR	LENGTH IN FT	PACKAGE TYPE	125V RATING	PACK QTY	MASTER WT	MASTER PACK CUBE
02438	14/3	SJTW	Yellow with Blue Stripe	50	Sleeve	15 A	4	23	0.54
02439	14/3	SJTW	Yellow with Blue Stripe	100	Sleeve	13 A	3	32	0.84
02538	12/3	SJTW	Yellow with Black Stripe	50	Sleeve	15 A	4	31	0.69
02539	12/3	SJTW	Yellow with Black Stripe	100	Sleeve	15 A	3	45	0.98



2628

## Cold Flex Extension Cords



Bright blue cords with jackets that resist deterioration from moisture, abrasion and extended exposure to sunlight. Cold Flex extension cords are designed for use in cold environments as stay flexible to -50° C.

CAT NO	WIRE GA/COND	WIRE TYPE	COLOR	LENGTH IN FT	PACKAGE TYPE	125V RATING	PACK QTY	MASTER WT	MASTER PACK CUBE
2627	14/3	SJTW	Blue	25	Sleeve	15A	6	23	0.53
2628	14/3	SJTW	Blue	50	Sleeve	15A	6	40	0.93
2629	14/3	SJTW	Blue	100	Sleeve	13A	3	29	1.3
2437	12/3	SJTW	Blue	25	Sleeve	15A	12	39	1.49
2438	12/3	SJTW	Blue	50	Sleeve	15A	6	42	1.45
2439	12/3	SJTW	Blue	100	Sleeve	13A	3	39	0.89



# Custom Extension Cords

Made to meet  
OSHA  
Specifications



## Features

- **Heavy-Duty Strain Relief** • **Molded Connectors** • **Reinforced Blades & Pins**

## Benefits

- **Best Delivery in the Industry**  
*CCI manufactures all custom cords in Illinois, USA. Domestic Production means faster turnaround.*
- **Safety**  
*Create your own highly visible colors to help prevent the cord from being accidentally severed and to reduce tripping hazards.*
- **Loss (Theft) Prevention**  
*Custom Cords help prevent inadvertent (or intentional) removal of cords from the job-site.*
- **Advertising Tool**  
*Make your cords an advertising tool with the use of custom colors and legends.*

## Options

- **Polar/Solar® Jacket Materials (SJEOW/SEOW)**  
*CCI's Polar/Solar extension cords are lightweight, extremely abrasion resistant and very flexible at all temperatures down to -67° F.*
- **Vinyl Jacket Materials (SJTW/STW)**
- **14-10 Gauge Cord and 6/3 & 8/1 Temp Power Cords**  
*10,000' minimum run quantity per gauge.*
- **Custom Colors**  
*Choose from one of Coleman Cable's custom colors or we can customize a color to meet your needs.*
- **Custom Extruded Striping**  
*Pick a unique cord color and stripe color combination. The stripe will not wear off over time like a painted stripe. Numerous stock colors mean that you can choose from hundreds of different STRIPES™ cord combinations. Additional charges apply.*
- **Multiple Outlet Options**  
*NEMA 5-15, NEMA L5-20, Tri-Source™, California-Style 50A, etc.*
- **Custom Legend**  
*Your custom legend can be ink printed on the jacket in black or white ink, or it can be indented into the jacket (no color). The legend repeats every 12"-18" down the entire length of the cords.*
- **UL & CSA approval (excluding 6/3 & 8/1 cords)**

**Call Coleman Cable customer service at 1-800-323-9355 to design your custom cords.**

## Cord Set Types

<input type="checkbox"/> NEMA 5-15				Most Applications
<input type="checkbox"/> NEMA 5-15				10/3 or 600V
<input type="checkbox"/> NEMA L5-20				20A Twist Lock
<input type="checkbox"/> NEMA 5-15				Tri-Source®
<input type="checkbox"/> CAL-STYLE 50A				6/3 & 8/1 only



*Custom Cord*  
**Program**

# Replacement Plugs & Connectors

All jobsites require rugged, safe replacement wiring devices when the need arises. Safety issues lead to a heavier-duty design able to withstand harsh job-site conditions. **Construction-Grade** devices have tough, vinyl or nylon housing with many built-in features for speed, safety and assembly convenience. 15A, 20A, 30A and 50A models address a wide range of customer needs, including locking 20A-50A applications. **Industrial-Grade** 15A devices have high visibility yellow housings designed for extended life for harsh, abusive IP20 and IP55 applications. **Watertight-Grade** 15A devices all have high visibility yellow housings designed for IP20 and IP55 applications where water is prevalent.

CAT NO	DESCRIPTION	DUTY	MASTER PACK	MASTER WT
<b>NEMA 5-15 15A 125v Straight Blade</b>				
05984	15A/125v NEMA 5-15 Yellow Vinyl Male Plug	Construction	20	1
05985	15A/125v NEMA 5-15 Yellow Vinyl Female Connector	Construction	20	1
05990	15A/125v NEMA 5-15 Yellow Rubber 1447 Male Plug	Industrial	10	1.5
05991	15A/125v NEMA 5-15 Yellow Rubber 1547 Female Connector	Industrial	10	2
05992	15A/125v NEMA 5-15 Yellow Watertight 14W47 Male Plug	Watertight	10	2
05993	15A/125v NEMA 5-15 Yellow Watertight 15W47 Female Connector	Watertight	10	3.5
<b>NEMA L5-20 20A 125v Locking</b>				
05986	20A/125v NEMA L5-20P Locking Nylon Male Plug	Construction	10	2.5
05987	20A/125v NEMA L5-20C Locking Nylon Female Connector	Construction	10	3
<b>NEMA L5-30 30A 125v Locking</b>				
05962	30A/250v NEMA L5-30 Locking Nylon Male Plug	Construction	10	2.5
05963	30A/250v NEMA L5-30 Locking Nylon Female Connector	Construction	10	3
<b>NEMA L6-30 30A 250v Locking</b>				
05964	30A/250v NEMA L6-30 Locking Nylon Male Plug	Construction	10	2.5
05965	30A/250v NEMA L6-30 Locking Nylon Female Connector	Construction	10	2.5
<b>50A 125/250v Locking</b>				
05974	50A/125/250v Locking Male Plug	Construction	4	5
05975	50A/125/250v Locking Female Connector	Construction	4	4.2
05958	50A/125/250v Hubbell Locking Male Plug	Construction	4	5
05959	50A/125/250v Hubbell Locking Female Connector	Construction	4	4.2





## X-Treme Box™



The X-Treme Box™ is a portable, flexible, rugged and reliable power distribution center for all jobsite conditions. It is an economical solution for electrical hook up on any worksite. For expandability, run up to four boxes at 400ft. in series before significant voltage drop occurs. A heavy-gauge carbon-steel case with corrosion resistant finish and a steel-reinforced sled base offer excellent durability. All boxes feature seven overload protected outlets, with GFCI, open neutral and over-voltage protection on all 20A outlets. All are Rainproof NEMA 3R enclosures. New roll cage versions allow for easy stackability.

**Applications:** Commercial – for Indoor/outdoor construction residential, renovation and demolition. Entertainment – for stage, concerts, broadcasting and cinema. Institution – for sports, special events and convention centers.

**Compliance:** ETL Listed US and Canada.



01960/01970



01962/01972

CAT NO	PORTABLE POWER DISTRIBUTION CENTER	50A POWER INLET	50A POWER OUTLETS	30A POWER OUTLET	20A POWER OUTLETS	OVERLOAD, OVER-VOLTAGE & OPEN-NEUTRAL PROTECTION	MASTER PACK	MASTER WT	MASTER PACK CUBE
01960	Rainproof NEMA 3R	125/250v Twist-To-Lock w/Cover	125/250v Twist-To-Lock w/Cover	250v L6-30R Twist-To-Lock w/Cover	(6) 20A 125v L5-20R Twist-To-Locks w/Cover	50A-None 30A Circuit Breaker Protected 20A GFCI & Circuit Breaker Protected	1	34	2.54
01962	<i>Roll Cage Model (Electrical specs are identical to part no. 01960)</i>								
01970	Rainproof NEMA 3R	125/250v Twist-To-Lock w/Cover	125/250v Twist-To-Lock w/Cover	250v L6-30R Twist-To-Lock w/Cover	(6) 20A 125v 5-20R Straight Blades w/Cover	50A - None 30A Circuit Breaker Protected 20A GFCI & Circuit Breaker Protected	1	34	2.54
01972	<i>Roll Cage Model (Electrical specs are identical to part no. 01970)</i>								



01980

## Mini X-Treme Box™



The Mini X-Treme Box provides more compact and less costly work-site power distribution than our full size models. Used with our restoration adapters, these units are ideal for disaster restoration work where the only available power is from range & dryer outlets or portable generators. Features 8 GFCI, Overload, & Circuit Breaker protected 20 amp straight blade outlets. **Compliance:** ETL Listed

CAT NO	PORTABLE POWER DISTRIBUTION CENTER	30A POWER INLET	20A POWER OUTLETS	MASTER PACK	MASTER WT	MASTER PACK CUBE
01980	NEMA Type 1	NEMA L14-30	8 x NEMA 5-20R (4 duplex outlets)	1	11.3	.98

## Power Distribution Extension Cords



Rugged temporary power cords for use with the X-Treme Box™ to handle 50A 3-Pole/4-Wire 125/250v AC.



01918

CAT NO	50A 6/3 & 8/1 125/250V CORD SETS	MASTER PACK	MASTER WT	MASTER PACK CUBE
01918	50ft SEOW w/ California-Style Twist-Lock Ends	1	27	.75
01919	100ft SEOW w/ California-Style Twist-Lock Ends	1	54	1.3
01938	50ft SEOW w/ Hubbell California-Style Twist-Lock Ends	1	27	.75
01939	100ft SEOW w/ Hubbell California-Style Twist-Lock Ends	1	54	1.3

## Replacement Ends/Adapters



Replacement ends constructed with impact & chemical resistant nylon, designed to keep out moisture and dust.



05959

05958



05974

05975

CAT NO	50A 3-POLE/4-WIRE 125/250V PLUGS/CONNECTORS/ADAPTERS	MASTER PACK	MASTER WT	MASTER PACK CUBE
05974*	50A/125/250V Locking Male Plug	4	2	.26
05975*	50A/125/250V Locking Female Connector	4	2	.26
05958*	50A/125/250V Locking Hubbell Male Plug	4	2	.26
05959*	50A/125/250V Locking Hubbell Female Connector	4	2	.26
01920	6/4 SEOW 50A "Y" Adapter	1	4	2.25

\* UL and CSA Listed

# Disaster Recovery & Restoration Cords

Made to meet  
OSHA  
Specifications

For use in disaster recovery, restoration, renovation or maintenance projects requiring temporary, portable power.



CAT NO	LENGTH	DESCRIPTION	STD PACK	WT	MALE END	FEMALE END	POWER FROM
01854~	10 ft.	10/4 SE00W 14-30P L1430R UL/CSA	4	3.99	14-30P	L14-30R	Dryer Outlet
01824~	10 ft.	10/4 SE00W 14-30P CA50A UL/CSA	4	4.28	14-30P	CA 50A Twist	
01864~	10 ft.	10/4 SE00W 14-50P L14-30R UL/CSA	4	3.99	14-50P	L14-30R	Range Outlet 50A generator w/straight blade output
01834~	10 ft.	6/3 & 8/1 SE0W 14-50P CA50A	4	6.38	14-50P	CA 50A Twist	
1493*	25 ft.	10/4 STW Yellow Jacket L14-30P L14-30R	2	8.24	L14-30P	L14-30R	30A Generator
01844~	10 ft.	10/4 SE00W L14-30P CA50A UL/CSA	4	4.11	L14-30P	CA 50A Twist	

\* Part number 1493 is UL / cUL

~Assembled in the U.S.A.

# Generator Power Cords

Made to meet  
OSHA  
Specifications



01910

CAT NO	WIRE GA/COND	WIRE TYPE	COLOR	LENGTH IN FT	PACKAGE TYPE	125V RATING	MASTER PACK	MASTER WT	MASTER PACK CUBE
<i>Temporary power cord with three 15 amp receptacles and one male 5-15P plug engineered to work exclusively with generators or other equipment rated to or less than 15 amps.</i>									
01910*	12/3	SJTW	Yellow	25	Card	15A	12	44.5	2.20
<i>Temporary power cord with three 15 amp receptacles and one male 5-20P plug engineered to work exclusively with generators or other equipment rated to or less than 15 amps.</i>									
01911	10/3	SJTW	Yellow	25	Card	15A	6	36.5	1.41
<i>Temporary power cord with three 15 amp receptacles and one male L5-30P plug engineered to work exclusively with generators or other equipment rated to or less than 15 amps.</i>									
01912	10/3	SJTW	Yellow	25	Card	15A	6	35.6	1.41

\* UL Listed



09058/09059



NEMA L5-20R  
20A 125V

# Twist-To-Lock Extension Cords


Made to meet  
OSHA  
Specifications



CAT NO	WIRE GA/COND	WIRE TYPE	COLOR	LENGTH IN FT	PACKAGE TYPE	125V RATING	MASTER PACK	MASTER WT	MASTER PACK CUBE
<b>SJTW Extension Cords (NEMA L5-20P to NEMA L5-20R)</b>									
09208	12/3	SJTW	Yellow	50	Box	20A	6	41	1.94
09209	12/3	SJTW	Yellow	100	Box	15A	4	52	1.77
09058	10/3	SJTOW	Yellow	50	Disc	20A	2	22	1.66
09059	10/3	SJTOW	Yellow	100	Disc	20A	2	45	2.33
<b>STW Extension Cords, (NEMA L5-20P to NEMA L5-20R) - 600 Volt Rated</b>									
09028	12/3	STW	Yellow	50	Box	20A	4	40	1.93
09029	12/3	STW	Yellow	100	Box	15A	3	60	2.6

# Vinyl "Y" and "W" Adapters

Made to meet  
OSHA  
Specifications



09019

09018

CAT NO	WIRE GA/COND	WIRE TYPE	COLOR	LENGTH IN FT	PACKAGE TYPE	125V RATING	MASTER PACK	MASTER WT	MASTER PACK CUBE
<b>15A "Y" Adapter</b>									
09018	12/3	STW	Yellow	2	Sleeve	15A	12	20	1.96
<b>15A "W" Adapter</b>									
09019	12/3	STW	Yellow	2	Sleeve	15A	12	25	1.09



# Generator Power Cords and Adapters

Made to meet  
OSHA  
Specifications



CAT NO	DESCRIPTION	LENGTH IN FT	PACKAGE TYPE	STD PACK	MASTER WT	MASTER PACK CUBE	NEMA PLUG	NEMA CONNECTOR
01915	10/3 STOW "Y" L5-30P to (2) Lighted 5-20R	3	Box	4	11	0.777	L5-30P	(2) 5-20R
01924	12/4 STOW "Y" L14-20P to 12/3 (2) Lighted 5-20R	3	Box	4	12	0.777	L14-20P	(2) 5-20R
01934	10/4 STOW "Y" L14-30P to 10/3 (2) Lighted 5-20R	3	Box	4	11	0.777	L14-30P	(2) 5-20R
02618	10/3 SJTOW 5-20P to Lighted 5-20R	50	Disk	2	22	0.848	5-20P	5-20R
02619	10/3 SJTOW 5-20P to Lighted 5-20R	100	Disk	2	45	1.2	5-20P	5-20R



## Twist-To-Lock Adapters

Made to meet  
OSHA  
Specifications



CAT NO	WIRE GA/COND	WIRE TYPE	COLOR	LENGTH IN FT	PACKAGE TYPE	125V RATING	MASTER PACK	MASTER WT	MASTER PACK CUBE
<b>Adapters</b>									
<i>Standard 15A U-Ground plug (NEMA 5-15P), Twist-To-Lock 20A receptacle (NEMA L5-20R)</i>									
09020	12/3	STW	Yellow	9 inches	Sleeve	-	10	5	.29
<i>Twist-To-Lock 20A plug (NEMA L5-20P), Standard 15A U-Ground receptacle (NEMA 5-15R)</i>									
09021	12/3	STW	Yellow	9 inches	Sleeve	-	10	6	.24
<b>"Y" Adapter</b>									
<i>Twist-To-Lock 20A plug (NEMA L5-20P), two Twist-To-Lock 20A receptacle (NEMA L5-20R)</i>									
09022	12/3	STW	Yellow	20 inches	Sleeve	20A	10	14	1.07
<b>"W" Adapter</b>									
<i>Twist-To-Lock 20A plug (NEMA L5-20P), three Twist-To-Lock 20A receptacle (NEMA L5-20R)</i>									
09023	12/3	STW	Yellow	20 inches	Sleeve	20A	10	16	1.04
<b>Tri-Source® Adapter</b>									
<i>Twist-To-Lock 20A plug (NEMA L5-20P), Standard 15A U-Ground Tri-Source® receptacle (NEMA 5-15R)</i>									
09084	12/3	STW	Yellow	24 inches	Sleeve	20A	6	15	.54



## Adapters



CAT NO	COLOR	PACKAGE TYPE	MASTER PACK	MASTER WT	MASTER PACK CUBE
<b>3 to 1 Adapter</b>					
09901	Gray	Bulk	100	8	.15
<b>3-Way Adapter - Solid Molded PVC</b>					
09902	Beige	Blister	18	7	.42
09905	Green	Blister	18	7	.42
09906	Orange	Bulk/Blister	24/18	9/7	.21/.42
<b>5-Way Adapter</b>					
997362	Yellow	Bulk	5	3.5	.23

# GFCI – Ground Fault Circuit Interrupters

Provide personal protection from ground faults and open neutral conditions anywhere electrical equipment is used. All GFCIs are compact, weatherproof/rainproof and engineered to handle rugged conditions of any jobsite. All models feature molded connectors, 12 or 14 gauge OSHA safety yellow cords, heavy-duty strain relief, reinforced blades and pins, manual “Test/Reset” buttons, and industrial grade relays.



## Right Angle

Right Angle models offer a variety of receptacles and cord lengths that are perfect where space is at a premium.



02832



03392

CAT NO	LENGTH IN FT	DESCRIPTION	AMP/VOLT/WATT/RATING	RELAY CAPACITY	MASTER PACK	MASTER WT	MASTER PK CUBE
02832	2	12/3 SJTW Tri-Source®	15A 120V/1800W UL/CSA Listed	15A	6	9	.40
02837	25	12/3 SJE0W Tri-Source®	15A 120V/1800W UL/CSA Listed	15A	6	25	1.13
02838	50	12/3 SJE0W Tri-Source®	15A 120V/1800W UL/CSA Listed	15A	6	43	1.41
02839	100	12/3 SJE0W Tri-Source®	15A 120V/1800W UL/CSA Listed	15A	4	52	1.41
03392	2	12/3 SJTW Lighted Tri-Source®	15A 120V/1800W UL/CSA Listed	15A	4	6	.40
02834	2	12/3 SJTW Single Outlet	15A 120V/1800W UL/CSA Listed	15A	6	7	.10

## In-Line

In-Line models offer a variety of receptacles with 20A and 30A relay units.



02841

CAT NO	LENGTH IN FT	DESCRIPTION	AMP/VOLT/WATT/RATING	RELAY CAPACITY	MASTER PACK	MASTER WT	MASTER PK CUBE
02841	2.5	12/3 SJTW Tri-Source®	15A 120V/1800W UL/CSA Listed	20A	6	6	.63
02851	2.5	12/3 SE0W Tri-Source® Extra Heavy-Duty	15A 120V/1800W UL Listed	30A	6	8	.63

## Duplex Boxes

High impact resin with a slant-roof design to prevent water entry. Receptacles can accommodate large plugs.



02822

CAT NO	LENGTH IN FT	DESCRIPTION	AMP/VOLT/WATT/RATING	RELAY CAPACITY	MASTER PACK	MASTER WT	MASTER PK CUBE
02822	6	12/3 SJTW GFCI w test/reset buttons	15A 120V/1800W UL Listed	25A	6	15	.93
02827	25	14/3 SJE0W GFCI w test/reset buttons	15A 120V/1800W UL Listed	25A	1	3	.26
02828	50	14/3 SJE0W GFCI w test/reset buttons	15A 120V/1800W UL Listed	25A	1	5	.36

## Quad Boxes

High impact resin with a slant-roof design to prevent water entry. Receptacles can accommodate large plugs.



02821

CAT NO	LENGTH IN FT	DESCRIPTION	AMP/VOLT/WATT/RATING	RELAY CAPACITY	MASTER PACK	MASTER WT	MASTER PK CUBE
02816	6	12/3 SJTW GFCI w handle, test/reset buttons	15A 120V/1800W UL Listed	25A	2	6	.36
02821	6	12/3 SJTW GFCI w handle, test/reset buttons	20A 120V/1800W UL Listed	25A	2	6	.36

## User Attachable

Convert your extension cords, tools, and equipment to add GFCI protection.



02831

CAT NO	LENGTH IN FT	DESCRIPTION	AMP/VOLT/WATT/RATING	RELAY CAPACITY	MASTER PACK	MASTER WT	MASTER PK CUBE
02831	-	15A User-Attachable GFCI	15A 120V/1800W UL/CSA Listed	15A	10	7	1.0

## Plug-In with Surge Protection

Converts any standard receptacle into a GFCI surge protected outlet.



02800

CAT NO	LENGTH IN FT	DESCRIPTION	AMP/VOLT/WATT/RATING	RELAY CAPACITY	MASTER PACK	MASTER WT	MASTER PK CUBE
02800	-	15A GFCI Converter for Standard Receptacles	15A 120V/1800W UL Listed	15A	12	8	.34



# LIGHTING CONTENTS

<b>Temporary Lighting</b> .....	<b>17-18</b>
Luma-Site® Halogen Work Lights .....	17
Metal Halide Temporary Lights .....	17
Cord-O-Lite™ .....	18
Economy Cord-O-Lite™ .....	18
Replacement Guards .....	18
<b>Work Lights</b> .....	<b>19-21</b>
Polar/Solar® Work Lights .....	19
Yellow Jacket Work Lights .....	19
Luma-Site® Work Lights .....	19
Luma-Site® Fluorescent Lights .....	20
LED Work Lights .....	20
Luma-Site® Cord Reels .....	20
Luma-Site® Rough Service & Fluorescent Replacement Bulbs & Parts ..	21
Luma-Site® Heavy Duty Reflector Lights .....	21
Luma-Site® Brooder and Heat Lamps .....	21





07775

## Luma-Site® Halogen Work Lights

When the job must go on, rely on Coleman's Luma-Site® to light the way. For the times when the weather does not cooperate or the job goes on into the night, be prepared . . . make our Luma-Site® part of your everyday tool list. When the job is done, Coleman's halogen lights are easily transported from site-to-site and collapse for easy storage.

### Floodlight Series

Coleman Cable's Floodlight Series are reliable for basic needs.



CAT NO	DESCRIPTION	CORD LENGTH	MASTER PACK	MASTER WT	MASTER PACK CUBE
07775	500W halogen light, adjustable pivot handle, handle held, yellow. w/on-off switch *No tripod or telescoping post.	3'	6	36	1.99
07776	Two 500 watt pivoting heads, separate on/off power switches for each fixture, yellow. Tripod base.	7'	2	36	2.61
07777	500W halogen light, yellow, hand held base and tripod included.	7'	3	28	2.41



07776

### Premium Series

Coleman Cable's Premium Series halogen lights feature large heads for better lighting and heavy gauge steel guards to resist damage.



CAT NO	DESCRIPTION	CORD LENGTH	MASTER PACK	MASTER WT	MASTER PACK CUBE
07765	500W halogen light, hand-held, padded handle, sled base, on/off switch, red.	6'	6	38	.42
07766	500W/1000W pivoting head, halogen light, tripod base, on/off switch, red, bulb storage compartment and 500W halogen bulb included.	12'	2	41	3.49



07766

### Halogen Replacement Parts



CAT NO	DESCRIPTION	MASTER PACK	MASTER WT	MASTER PACK CUBE
07818	Glass for part numbers 07775, 07776, and 07777	1	1	.04
07880	500W Halogen bulb	50	3	.1

### Metal Halide Temporary Light - Pulse Start



CAT NO	WATTS	GUARD TYPE	BULB TYPE	CORD LENGTH IN FT	MASTER PACK	MASTER WT	MASTER PACK CUBE
07605*	400	10" Wire Guard	Type "O"	6	1	26	1.74

\* NEC 2005



07605

### Metal Halide Replacement Bulb



CAT NO	WATTS	DESCRIPTION	CORD LENGTH IN FT	MASTER PACK	MASTER WT	MASTER PACK CUBE
07625*	400	Type "O" Replacement Pulse Start Bulb	-	4	4.41	0.4

\* NEC 2005



# Temporary Lighting

Durable, indoor/outdoor lighting systems are available in 50ft. and 100ft. lengths, 12/3 or 14/2 cord, and metal or easy open/snap-on plastic guards to meet contractor demands. All feature lamp sockets every 10ft. and accommodate A-23 bulbs up to 150 watts.

## CORD-O-LITE™



Our most rugged lighting system. Heavy duty 12/3 SJTW (yellow) cord with molded light sockets. Accommodates A-23 type bulbs up to 150 watts. Available with coated-metal lamp guards, or easy-open snap-on plastic guards. Standard 15 amp molded or 20 amp locking ends.

CAT NO	LENGTH IN FT	DESCRIPTION	GUARD	NEMA PLUG	NEMA RECEPTACLE	COMPLIANCE	MASTER PACK	MASTER WT	MASTER PCK CUBE
<b>15 Amp</b>									
07538	50	12/3 SJTW 300v	*Coated METAL	5-15P	5-15R	UL; NEC; OSHA	1	11	1.2
07539	100	12/3 SJTW 300v	*Coated METAL	5-15P	5-15R	UL; NEC; OSHA	1	27	1.97
07548	50	12/3 SJTW 300v	Plastic	5-15P	5-15R	UL; NEC; OSHA	1	9	1.20
07549	100	12/3 SJTW 300v	Plastic	5-15P	5-15R	UL; NEC; OSHA	1	25	1.97
07598**	50	12/3 <b>STW</b> 600v	*Coated METAL	5-15P	5-15R	UL/CSA; NEC; OSHA	1	16	1.20
07599**	100	12/3 <b>STW</b> 600v	*Coated METAL	5-15P	5-15R	UL/CSA; NEC; OSHA	1	30	1.97
<b>20 Amp</b>									
07558	50	12/3 SJTW 300v	Coated METAL	L5-20P	L5-20R	UL; NEC; OSHA	1	12	1.20
07559	100	12/3 SJTW 300v	Coated METAL	L5-20P	L5-20R	UL; NEC; OSHA	1	27	1.97
07569	100	12/3 SJTW 300v	Plastic	L5-20P	L5-20R	UL; NEC; OSHA	1	25	1.97

\* Guards are pre-assembled onto lamp sockets

\*\* CSA

## Economy CORD-O-LITE™



Guards are pre-assembled onto lamp sockets to save labor and installation time.

CAT NO	LENGTH IN FT	DESCRIPTION	GUARD	NEMA PLUG	NEMA RECEPTACLE	COMPLIANCE	MASTER PACK	MASTER WT	MASTER PCK CUBE
<b>15 Amp</b>									
07145	100	14/2 SJTW 300v	Plastic	1-15P	—	UL; NEC; OSHA	1	14	2.15



07200



07300

## Replacement Guards

CAT NO	DESCRIPTION	MASTER PACK	MASTER WT	MASTER PACK CUBE
07200	Coated METAL for Cord-O-Lite™	20	6	1.13
07300	Plastic for Economy Cord-O-Lite™	20	2	1.05
07500	Plastic for Cord-O-Lite™	20	3	1.05



**POLAR/SOLAR®**  
C O R D



## Work Lights

### Polar/Solar®

Made to meet  
OSHA  
Specifications



Heavy-duty work lights featuring Coleman's exclusive T\*Prene® insulated Polar/Solar® cord. Stays flexible under all temperature extremes to -67°F. Exclusive one-piece injection molded handle. Grounded, vinyl coated metal guard with switch and side outlet. 75 Watt maximum bulb. Oil and chemical resistant.

CAT NO	DESCRIPTION	WIRE GA/COND	WIRE TYPE	COLOR	LENGTH IN FT	PACKAGE TYPE	125V RATING	MASTER PACK	MASTER WT	MASTER PACK CUBE
05657	Metal Guard w/outlet	14/3	SJEO	Yellow	25	Sleeve	15A	6	6	2.06
05658	Metal Guard w/outlet	14/3	SJEO	Yellow	50	Sleeve	15A	6	30	2.06
05857	Metal Guard w/outlet	16/3	SJEO	Yellow	25	Sleeve	13A	6	13	1.43
05858	Metal Guard w/outlet	16/3	SJEO	Yellow	50	Sleeve	13A	6	23	1.91
<b>Industrial Work Lights</b>										
05337*	Metal Guard	18/3	SJEO	Yellow	25	Sleeve	10A	12	26	3.01
05338*	Metal Guard	18/3	SJEO	Yellow	50	Sleeve	10A	6	21	1.78

\* Note: These products do not have a switch or outlet, UL listed only.



### Yellow Jacket® Work Lights

Made to meet  
OSHA  
Specifications



Yellow Jacket® Work Lights feature flexible wire, high heat resistant bulb collar, grounded metal guard, 13 amp grounded receptacle in handle and dual hooks. Hex-shaped cage helps direct light where it's needed. Coated wire cage keeps hot reflector from skin or upholstery. 75 Watt bulb rating.

CAT NO	DESCRIPTION	WIRE GA/COND	WIRE TYPE	COLOR	LENGTH IN FT	PACKAGE TYPE	125V RATING	MASTER PACK	MASTER WT	MASTER PACK CUBE
2893	Metal Guard w/outlet	16/3	SJT	Yellow	25	Sleeve	13A	12	30	3.01
2948	Metal Guard w/outlet	16/3	SJT	Yellow	50	Sleeve	13A	4	16	1.39

### LUMA-SITE®

### Luma-Site® Work Lights

Made to meet  
OSHA  
Specifications



Luma-Site® Work Lights represent both durability and practicality. Lightweight construction makes handling them effortless, but don't let the lack of weight fool you! Constructed from tough PVC, these lights can stand the rigors of almost any work environment. All Luma-Site® Work Lights come standard with power switches and bulb cages for fast light bulb changes. 75 Watt bulb maximum.



CAT NO	DESCRIPTION	WIRE GA/COND	WIRE TYPE	COLOR	LENGTH IN FT	PACKAGE TYPE	125V RATING	MASTER PACK	MASTER WT	MASTER PACK CUBE
<b>Two Conductor, Polypropylene Guard with Switch</b>										
05006	Plastic Guard	18/2	SJT	Orange	15	Sleeve	75W	12	14	1.98
05007	Plastic Guard	18/2	SJT	Orange	25	Sleeve	75W	12	19	2.04
<b>Three Conductor, Polypropylene Guard with Outlet and Switch</b>										
05307	Plastic Guard w/outlet	18/3	SJT	Orange	25	Sleeve	10A	12	22	2.22
05407	Plastic Guard w/outlet	16/3	SJT	Orange	25	Sleeve	13A	6	13	1.49
05408	Plastic Guard w/outlet	16/3	SJT	Orange	50	Sleeve	13A	6	24	1.97
<b>Three Conductor, Grounded Metal Guard with Side Outlet and Switch</b>										
05327	Metal Guard w/outlet	18/3	SJT	Orange	25	Sleeve	10A	12	23	1.91
05328	Metal Guard w/outlet	16/3	SJT	Orange	50	Sleeve	10A	6	20	1.36
05427	Metal Guard w/outlet	16/3	SJT	Orange	25	Sleeve	13A	12	28	2.02
05428	Metal Guard w/outlet	16/3	SJT	Orange	50	Sleeve	13A	6	24	1.49





05364



05999



05930

## Luma-Site® Fluorescent Lights



Engineered to provide maximum light, Luma-Site® Fluorescent Lights were created specifically for the professional. A compact casing ensures the light can be placed in the tightest of spots and a convenient on/off switch guarantees you will have glare-free light only when you are ready. The ergonomic design means the light will sit comfortably in your hand even after an extended period of time. Should you need to work using both hands, a collapsible swivel hook allows you to hang the light in virtually any direction.

CAT NO	WIRE GA/COND	WIRE TYPE	HANDLE COLOR	LENGTH IN FT	PACKAGE TYPE	125V RATING	MASTER PACK	MASTER WT	MASTER PACK CUBE
<b>26 Watt with Outlet &amp; Detachable Magnet - 2 Switches/2 Bulbs/2 Hooks</b>									
05364	16/3	SJT	Black	25	Sleeve	13A	4	16	1.04
<b>26 Watt with Outlet</b>									
05926	16/3	SJT	Black	10	Sleeve	13A	4	8	.64
<b>13 Watt with Outlet</b>									
05929	16/3	SJT	Red	15	Sleeve	13A	6	13	.67
05998	16/3	SJT	Red	2	Sleeve	13A	6	19	.43
<b>13 Watt with Outlet, Wall Bracket and Detachable Magnet</b>									
05999	16/3	SJT	Red	15	Sleeve	13A	6	21	1.60
<b>13 Watt</b>									
05930	18/2	SJT	Yellow	15	Sleeve	-	6	13	.69
05931	18/2	SJT	Yellow	25	Sleeve	-	6	18	.82



05952

## LED Work Lights

Coleman Cable's long-life LED Work Lights bring durability, practicality and functionality to the work site. The TwistBrite™ is an LED work light with a flexible neck which allows light to be positioned in multiple ways. The TwistBrite also includes a PVC-coated magnet on the base of the unit for quick attachment to many metal surfaces. Product ships in a merchandising blister pack that includes batteries.

CAT NO	DESCRIPTION	PACKAGE TYPE	MASTER PACK	MASTER WT	MASTER PACK CUBE
05952	TwistBrite™ – Ultra Bright LED with Flexible Neck	Clamshell	4	6	0.84

## Luma-Site® Rough Service & Fluorescent Replacement Bulbs & Parts



CAT NO	VOLT RATING	WATT RATING	DESCRIPTION	MASTER PACK	MASTER WT	MASTER PACK CUBE
<b>Replacement Bulbs</b>						
05902	130	75	Rough Service Incandescent Bulbs – 4 Pack	120	14	1.72
05903	130	100	Rough Service Incandescent Bulbs – 4 Pack	120	14	1.72
05933	120	13	13 watt U-shaped fluorescent bulb	6	1	.04
<b>Replacement Work Light Guard</b>						
05906	NA	NA	Metal Swing-open	12	5	1.14

## LUMA-SITE® Luma-Site® Cord Reels



Tired of tripping over extension cords? Luma-Site® Retractable Reels solve that problem and keep your work area organized. Luma-Site® Retractable Reels are available with an incandescent light or Trinector® three-outlet power block. Reel cases are constructed with extra-tough ABS plastic or heavy-duty steel and mount easily for use in workshop, basement, or garage. Mounting hardware included.



CAT NO	WIRE GA/COND	WIRE TYPE	COLOR	LENGTH IN FT	PACKAGE TYPE	125V RATING	MASTER PACK	MASTER WT	MASTER PACK CUBE
<b>Cord Reel with Trinector®</b>									
04633	16/3	SJT	Black	30	Box	10A	4	36	1.95
<b>Heavy Duty Cord Reel w/Lighted Tri-Source®</b>									
04820	12/3	SJTW	Yellow	50	Box	13A	1	18	.94
<b>Trouble Light with Metal Guard and Plastic Reel w/Outlet</b>									
05360	18/3	SVT	Black	20	Box	7A	4	15	1.14
<b>Trouble Light with Metal Guard w/Outlet</b>									
05570	16/3	SJT	Black	30	Box	10A	4	36	1.94

## Luma-Site® Heavy Duty Reflector Lights



Versatile multi-use utility lamps with polished and vented aluminum reflectors. Each unit features a double ball universal joint, non-marring grips, and a clamp-on bracket, on/off push-through switch and rugged molded-on plug.



CAT NO	WIRE GA/COND	WIRE TYPE	COLOR	LENGTH IN FT	PACKAGE TYPE	125V RATING	REFL. DIA. IN INCHES	MASTER PACK	MASTER WT	MASTER PACK CUBE
05922	18/2	SPT	Brown	6	Sleeve	60W	5.5	12	6	.67
05932	18/2	SPT	Brown	6	Sleeve	150W	8.5	12	11	.84
05939	18/2	SPT	Brown	6	Sleeve	150W	10.5	12	12	1.18
05946	18/2	SJT	Black	15	Sleeve	60W	5.5	12	17	.97
05956	18/2	SJT	Black	15	Sleeve	150W	8.5	12	17	1.09

## Luma-Site® Brooder and Heat Lamps

An ideal temporary heat source for pig and chicken brooders. Insulated two-piece porcelain sockets with heavy-gauge aluminum reflectors, hang-up hooks and optional clamp.



CAT NO	WIRE GA/COND	WIRE TYPE	COLOR	LENGTH IN FT	PACKAGE TYPE	125V RATING	REFL. DIA. IN INCHES	MASTER PACK	MASTER WT	MASTER PACK CUBE
05968	18/2	SJT	Black	8	Sleeve	250W	10.5	6	12	1.64
05961*	18/2	SJT	Black	8	Sleeve	250W	10.5	6	20	1.62

\* Clamp included



# BULK WIRE CONTENTS

<b>Industrial</b> .....	<b>.23-33</b>
Royal/Excelene Welding Cable .....	.23
Welding Cable Assemblies .....	.23
Welder Extension Cords .....	.23
Seoprene® SEOW Portable Cord .....	.24
Royal® SOOW Rubber Portable Cord .....	.25
Seoprene® Control Cable .....	.26
Lamp Cord .....	.27
MTW .....	.27
TFFN/TFN .....	.27
THHN .....	.27
Bare Copper .....	.28
XHHW-2 .....	.28
<b>Low Voltage Wire</b> .....	<b>.29-33</b>
Thermostat Wire .....	.29
Single-Conductor Underground Feeder (UF) .....	.29
Multi-Conductor Underground Feeder (UF) – B .....	.29
Multi-Conductor Sprinkler Cable .....	.30
Pump and Irrigation Cable .....	.30
<b>Fire Alarm Cable</b> .....	<b>.31-33</b>
Fire Alarm Multi-Conductor Cable – Unshielded Type FPLR .....	.31
Fire Alarm Multi-Conductor Cable – Overall Shielded Type FPLR .....	.31
Fire Alarm Multi-Conductor Cable – Unshielded Plenum Type FPLP .....	.31
2 & 4 Conductor Cable – Unshielded Type CM/CL2 – CMX Outdoor .....	.31
Multi-Conductor Cable – Unshielded Type CMR/CL3R .....	.32
Multi-Conductor Cable – Overall Shielded Type CMR/CL3R .....	.32
Area Network Cable .....	.32
Coaxial Cable .....	.33

# Royal/Excelene® Welding Cable



- Ethylene-Propylene Rubber (EPR)
- -50°C to 105°C
- Resistant to oil, chemicals, water, ozone, & solvents
- Sequential foot-marked
- Red jacket available
- RoHS Compliant
- Made in the USA



CAT NO	SIZE	STRANDING	NOM. JACKET THICKNESS	NOM. OD	WT/M'
10411	6	266	0.065	0.305	116
10412	4	392	0.064	0.340	159
10413	2	644	0.065	0.420	254
10414	1	784	0.084	0.490	323
10415	1/0	1026	0.082	0.525	395
10416	2/0	1254	0.085	0.570	473
10417	3/0	1615	0.084	0.635	598
10418	4/0	2052	0.084	0.695	749
F25001*	250 MCM	2451	0.148	0.875	1060
F35003*	350 MCM	3458	0.125	0.960	1393
F50001*	500 MCM	4921	0.160	1.150	1890

Other sizes available upon request  
\* Minimums & lead times may apply

## Welding Cable Assemblies

- Royal/Excelene Welding Cable
- Professionally assembled & tested
- Other lengths, sizes, and connectors available upon request
- Call for minimums & lead times
- Assembled in the USA

CAT NO	SIZE	DESCRIPTION	STD PK QTY	WT/EA.
10416-S9-08	2/0	50ft Coil, w/Tweco Connectors	1	27.11
10416-S9-08	2/0	100ft Coil, w/Tweco Connectors	1	51.36

TWECO® is a registered trademark of Thermadyne® and is not affiliated in any way with Coleman Cable Inc.



## Welder Extension Cords

- Heavy-duty STW jacket
- Lighted receptacle end indicates when power is on
- Molded ends offer safety and convenience on the jobsite
- 40 Amp, 250 Volts & 10,000 Watts

CAT NO	DESCRIPTION	LENGTH	MALE END	FEMALE END	STD PK QTY	WT/EA.
01940-88-08	8/3 STW Black	1.5 ft.	14-50P	Lighted 6-50R	12	2
01941-88-08	8/3 STW Black	10 ft.	14-50P	Lighted 6-50R	4	6
01917-88-06	8/3 STW Blue	25 ft.	6-50P	Lighted 6-50R	2	11
01922-88-06	8/3 STW Blue	50 ft.	6-50P	Lighted 6-50R	1	22



## Recommended Minimum Welding Cable Sizing Chart

Welding Current	Length in Feet For Total Circuit for Secondary Voltages Only (DO NOT Use This Table For 600 Volt In-Line Applications)						
	50	100	150	200	250	300	350
100	4	4	4	2	2	1	1/0
150	4	4	2	1	1/0	2/0	3/0
200	2	2	1	1/0	2/0	3/0	4/0
250	2	2	1/0	2/0	3/0	4/0	
300	1	1	2/0	3/0	4/0		
350	1/0	1/0	3/0	4/0			
400	2/0	2/0	3/0				
500	3/0	4/0	4/0				
600	4/0	4/0					

- Ampacities are based on 105°C conductor temperature, 40°C ambient air / 50% duty cycle and approximate voltage drop of 4V @ 25°C conductor temperature or 5VB @ 105°C conductor temperature.
- Dimensions and weights are subject to normal manufacturing tolerances. All data herein is subject to change without notice.

Custom Colors & Legends Available  
Minimums & Lead Times Apply



# Seoprene® Seoprene® 105°C Black Portable Cord



Flexible and tough jacket. Offers a wide useable temperature range of -50°C to 105°C. Seoprene provides excellent abrasion, ozone, sunlight, chemical, oil, water, and mold resistance along with non-wicking lightweight polypropylene fillers. Water resistant with high dielectric insulation. Lightweight, long lasting, easy to carry and handle. All components are recyclable and non-hazardous for environmental landfill disposal. Federal and Military use under Federal Spec. JC-580B. UL Listed SE00W 600V and SJEOOW 300V to NEC Article 400, CSA approved ST00W or SJTOOW (TPE) -50°C to 105°C. MSHA approved for flame resistance in mining applications.



CAT NO	SIZE	TYPE	JACKET COLOR	WT/ 1000'
23225-xx-08	18/2	SJEOOW	Black	44
23325-xx-08	18/3	SJEOOW	Black	58
23425-xx-08	18/4	SJEOOW	Black	68
23226-xx-08	16/2	SJEOOW	Black	55
23326-xx-08	16/3	SJEOOW	Black	68
23426-xx-08	16/4	SJEOOW	Black	80
23227-xx-08	14/2	SJEOOW	Black	69
23327-xx-08	14/3	SJEOOW	Black	86
23427-xx-08	14/4	SJEOOW	Black	105
23228-xx-08	12/2	SJEOOW	Black	97
23328-xx-08	12/3	SJEOOW	Black	123
23428-xx-08	12/4	SJEOOW	Black	156
23229-xx-08	10/2	SJEOOW	Black	170
23329-xx-08	10/3	SJEOOW	Black	214
23429-xx-08	10/4	SJEOOW	Black	275
22225-xx-08	18/2	SE00W	Black	62
22325-xx-08	18/3	SE00W	Black	72
22226-xx-08	16/2	SE00W	Black	73
22326-xx-08	16/3	SE00W	Black	84
22227-xx-08	14/2	SE00W	Black	132
22327-xx-08	14/3	SE00W	Black	147
22427-xx-08	14/4	SE00W	Black	183
22228-xx-08	12/2	SE00W	Black	168
22328-xx-08	12/3	SE00W	Black	202
22428-xx-08	12/4	SE00W	Black	244
22229-xx-08	10/2	SE00W	Black	214
22329-xx-08	10/3	SE00W	Black	259
22429-xx-08	10/4	SE00W	Black	326
22320-xx-08*	8/3	SE00W	Black	329
22420-xx-08*	8/4	SE00W	Black	436
22321-xx-08*	6/3	SE00W	Black	485
22421-xx-08*	6/4	SE00W	Black	604
22322-xx-08*	4/3	SE00W	Black	700
22422-xx-08*	4/4	SE00W	Black	896
22323-xx-08*	2/3	SE00W	Black	1060
22423-xx-08*	2/4	SE00W	Black	1316

\* Not UL Listed or CSA Approved  
Put-up: xx= 250' (04); 500' (05); 1000' (06); 250' Pullout Box (64)





## Royal® Crown Series® Portable Cord



The Royal Crown Series portable cords are manufactured with advanced synthetic rubber compounds that provide exceptional flexibility, and excellent resistance to flame, deformation, ozone, oils, acids and chemicals. These are rated from -40C to 90C and meet MSHA flame test requirements. Unless otherwise noted, these are also UL listed and CSA approved.



CAT NO	SIZE	TYPE	JACKET COLOR	WT/ 1000'
823325-xx-08	18/3	SJ00W	Black	69
823226-xx-08	16/2	SJ00W	Black	69
823326-xx-08	16/3	SJ00W	Black	84
823227-xx-08	14/2	SJ00W	Black	84
823327-xx-08	14/3	SJ00W	Black	111
823427-xx-08	14/4	SJ00W	Black	131
823228-xx-08	12/2	SJ00W	Black	111
823328-xx-08	12/3	SJ00W	Black	146
823428-xx-08	12/4	SJ00W	Black	196
823329-xx-08	10/3	SJ00W	Black	254
822225-xx-08	18/2	S00W	Black	79
822325-xx-08	18/3	S00W	Black	89
822425-xx-08	18/4	S00W	Black	101
822226-xx-08	16/2	S00W	Black	89
822326-xx-08	16/3	S00W	Black	101
822426-xx-08	16/4	S00W	Black	121
830506-xx-08	16/5	S00W	Black	169
822227-xx-08	14/2	S00W	Black	152
822327-xx-08	14/3	S00W	Black	179
822427-xx-08	14/4	S00W	Black	222
822228-xx-08	12/2	S00W	Black	212
822328-xx-08	12/3	S00W	Black	242
822428-xx-08	12/4	S00W	Black	294
822229-xx-08	10/2	S00W	Black	272
822329-xx-08	10/3	S00W	Black	312
822429-xx-08	10/4	S00W	Black	377
830509-xx-08	10/5	S00W	Black	442
822320-xx-08*	8/3	S00W	Black	423
822420-xx-08*	8/4	S00W	Black	508
822321-xx-08*	6/3	S00W	Black	553
822421-xx-08*	6/4	S00W	Black	684
822322-xx-08*	4/3	S00W	Black	828
822422-xx-08*	4/4	S00W	Black	1050
822323-xx-08*	2/3	S00W	Black	967
822423-xx-08*	2/4	S00W	Black	1221

\* Not UL Listed or CSA Approved

Put-up: xx= 250' (04); 500' (05); 1000' (06); 250' Pullout Box (64)



# Seoprene® 105 Control Cable



Cable ranges from 18-10 AWG with 5 or more conductors. Provides lightweight flexibility and mechanical toughness in a multi-conductor construction that is easy to strip. Rated 600V with temperature ratings from -50C to 105C. Applications include power in processing facilities, push-button line controls, 600V control and instrumentation, temperature, motor and robotic control systems. UL Listed, CSA Certified, MSHA approved for flame resistant mining applications.



CAT NO	SIZE	TYPE	JACKET COLOR	WT/ 1000'
30505-xx-08	18/5	SE00W	Black	113
30605-xx-08	18/6	SE00W	Black	119
30805-xx-08	18/8	SE00W	Black	151
31005-xx-08	18/10	SE00W	Black	168
31205-xx-08	18/12	SE00W	Black	212
31405-xx-08	18/14	SE00W	Black	235
31605-xx-08	18/16	SE00W	Black	277
30506-xx-08	16/5	SE00W	Black	140
30606-xx-08	16/6	SE00W	Black	158
30706-xx-08	16/7	SE00W	Black	165
30806-xx-08	16/8	SE00W	Black	190
31006-xx-08	16/10	SE00W	Black	242
31206-xx-08	16/12	SE00W	Black	288
31406-xx-08	16/14	SE00W	Black	311
31606-xx-08	16/16	SE00W	Black	355
30507-xx-08	14/5	SE00W	Black	232
30607-xx-08	14/6	SE00W	Black	269
30707-xx-08	14/7	SE00W	Black	280
31007-xx-08	14/10	SE00W	Black	423
31207-xx-08	14/12	SE00W	Black	465
30508-xx-08	12/5	SE00W	Black	302
30608-xx-08	12/6	SE00W	Black	343
30808-xx-08	12/8	SE00W	Black	416
30509-xx-08	10/5	SE00W	Black	387

Put-up: xx= 250' (04); 500' (05); 1000' (06)

*The welding cable, portable cord and other industrial cables shown on these pages represent a very limited portion of our full offering. For additional items in these categories, please call our customer service group at 800-323-9355 and request our Industrial Cable catalog:*





## Lamp Cord

For use with lamps and other small appliances.



CAT NO	WIRE GAUGE	DESCRIPTION	JACKET COLOR	STRANDING	NOMINAL WALL	NOMINAL O.D.	LENGTH IN FT	MASTER WT
60000-66-xx	18/2	SPT-1	See code below	41/34	.033	.115 x .250	250	7
60126-66-xx	16/2	SPT-2		26/30	.048	.156 x .307	250	10

Color (xx): 01=White; 07=Brown; 08=Black; 18=Clear\*; 19=Gold\*; 21=Silver\*

\* Not CSA Listed

60000

## MTW



Features extra flexible 30 AWG stranding. Rated as ASTM Class Flexing Service by NFPA 79 electrical standard for industrial machinery. Insulations, oil, moisture, and acid resistant. Approvals: NFPA 79 Electrical Standard for Industrial Machinery, NFPA 70 National Electric Code, UL1063 Machine Tool Wires and Cables, UL Subject 758 Appliance Wire and Material, CSA C22.2 No. 127 Equipment Wires, CSA C22.2 No 210.1 Appliance Wiring Material Products, ASTM B174 Bunch Stranded Copper Conductors.

CAT NO	WIRE GAUGE	STRANDING	OVERALL O.D.	SPOOL LENGTH (FT)	MASTER PK QTY (FT)	MASTER WT
41101-05-xx	18	16/30	0.108	500	2000	22
41102-05-xx	16	26/30	0.120	500	2000	30
41103-05-xx	14	41/30	0.136	500	2000	40
41104-05-xx	12	65/30	0.155	500	2000	58
41105-05-xx	10	104/30	0.179	500	500	22
41109-05-xx	8	19/.0295	0.244	500	500	39
41110-05-xx	6	19/.0372	0.314	500	500	60

Color code: xx = White (01); Yellow (02); Orange (03); Red (04); Green (05); Blue (06); Brown (07); Black (08)  
Yellow, Orange, Blue, Brown not available on 6 & 8 gauge.



41103

## TFFN/TFN



PVC/Nylon insulated, 600V rated wire. AWM style 1316 and 1408. Rated gasoline and oil resistant.

CAT NO	DESCRIPTION	STRANDING	OVERALL O.D.	SPOOL LENGTH (FT)	MASTER PK QTY (FT)	MASTER WT
51011-05-xx	18 AWG TFFN	16/30	.088	500	2000	18
51012-05-xx	16 AWG TFFN	16/30	.100	500	2000	26
51791-05-xx	18 AWG TFN	Solid	.082	500	2000	18
51792-05-xx	16 AWG TFN	Solid	.093	500	2000	24

Color code: xx = White (01); Yellow (02); Orange (03); Red (04); Green (05); Blue (06); Brown (07); Black (08)



51791

## THHN



PVC/Nylon insulated, 600V rated wire. AWM style 1316 and 1408. Rated gasoline and oil resistant.

CAT NO	GAUGE	STRANDING	OVERALL O.D.	SPOOL LENGTH (FT)	MASTER PK QTY (FT)	MASTER WT
51041-05-xx	14	Solid	.106	500	2000	36
51042-05-xx	12	Solid	.123	500	2000	52

Color code: xx = White (01); Red (04); Green (05); Blue (06); Black (08)



51041





## Bare Copper Wire - Solid & Stranded, Unjacketed, Soft Drawn

Copperfield® solid and stranded, soft annealed bare copper conductors are available from 14 gauge to 500MCM. These conductors are made from Electrolytic Tough Pitch (ETP) copper feed stock and manufactured to ASTM standards B3 (Soft or Annealed) or B8 (Concentric-Lay). Bare Copper Wire is used in overhead transmission and distribution systems and for grounding grid systems.

CAT NO	SIZE	STRANDING	WT/M'
F54601	14	Solid BC	13
F54602	12	Solid BC	21
F54603	10	Solid BC	34
F54604	8	Solid BC	60
F54685	6	Solid BC	82
F54614	8	7/.0486 BC	53
F54605	6	7/.0612 BC	84
F54606	4	7/.0772 BC	143
F54607	2	7/.0974 BC	217
F54608	1/0	19/.0745 BC	345
F54609	2/0	19/.0837 BC	430
F54610	3/0	19/.0940 BC	558
F54611	4/0	19/.1055 BC	680
F54625	250 MCM	37/.0822 BC	792
F54635	350 MCM	37/.0973 BC	1102
F54650	500 MCM	37/.1162 BC	1563



Put-Up Codes: (05) 500' reel, (06) 1000' reel, (09) 2500' reel, (13) 3000' reel



## XHHW-2 Wire

Coleman Cable's Royal® brand of XHHW-2 is manufactured with fully annealed bare copper meeting American Society for Testing and Materials (ASTM) B 3 specifications. The flame retardant cross-linked polymer insulation provides excellent physical properties, is wet and dry rated for 90°C, and is Reduction of Hazardous Substances (RoHS) and Registration, Evaluation, Authorization and Restriction of Chemical (REACH) compliant.



CAT NO	SIZE	STRANDING	COPPER	INSULATION THICKNESS (IN)	NOMINAL OD (IN)	MASTER WT
18080	8	7/.0486	BARE	0.045	0.245	69
18060	6	7/.0612	BARE	0.045	0.275	100
18040	4	7/.0772	BARE	0.045	0.335	153
18020	2	7/.0974	BARE	0.045	0.395	235
18010	1	19/.0664	BARE	0.055	0.435	254
18100	1/0	19/.0740	BARE	0.055	0.470	325
18200	2/0	19/.0837	BARE	0.055	0.530	456
18300	3/0	19/.0940	BARE	0.055	0.580	565
18400	4/0	19/.1055	BARE	0.055	0.622	705
18250	250	37/.0822	BARE	0.065	0.690	891
18350	350	37/.0973	BARE	0.065	0.800	1225
18500	500	37/.1162	BARE	0.065	0.920	1710
18600	600	37/.1273	BARE	0.080	1.044	2045

Dimensions and weights are nominal unless otherwise specified and subject to industry tolerances. Colors available with minimum runs. VW-1 Flame rated constructions available upon request. Contact your Coleman Cable Representative for details.

\*Also available: XLP USE-2 & SIS/XHHW-2 Wire VW-1

**Thermostat Wire**



Baron's popular thermostat wire is both UL, CUL and ETL approved and is suitable for NEC article 725 applications. It is constructed with a PVC jacket and conductors insulated with polypropylene.



55302

CAT NO	AWG	NUMBER OF CONDUCTORS	LENGTH IN FT	JACKET COLOR	NOMINAL JACKET THICKNESS	NOMINAL O.D.	MASTER PACK	MASTER WT
55302-05-07	18	2	500	Brown	.014"	.132"	4	28
55303-05-07	18	3	500	Brown	.014"	.140"	4	40
55304-04-07	18	4	250	Brown	.014"	.154"	4	26
55305-04-07	18	5	250	Brown	.015"	.170"	4	32
55306-04-07	18	6	250	Brown	.015"	.186"	4	38
55307-04-07	18	7	250	Brown	.019"	.194"	4	43
55308-04-07	18	8	250	Brown	.019"	.210"	4	48
55309-04-07	18	9	250	Brown	.019"	.226"	4	54
55310-04-07	18	10	250	Brown	.019"	.246"	4	60
55312-04-07	18	12	250	Brown	.019"	.254"	1	19

Note: Spools and Bulk available packed 4 spools/box

**Single-Conductor Underground Feeder (UF)**



Underground feeder cable for direct burial applications. UL Type UF, CUL Type TWU FT1.



54501

CAT NO	GAUGE	COPPER STRANDING	LENGTH IN FT	JACKET COLOR	NOMINAL O.D.	MASTER PACK	MASTER WT
54501-05-xx	14	Solid	500	See code below*	.186"	4	56

\*Color code: xx = White (01); Red (04); Green (05); Black (08)

**Multi-Conductor Underground Feeder (UF) – B**



Underground feeder cable for direct burial applications. Black and white conductors with bare ground. UL Standard 493.



55562

CAT NO	CONDUCTOR AWG	NUMBER OF CONDUCTORS	COPPER STRANDING	GROUND AWG	NOMINAL INSULATION THICKNESS	JACKET COLOR	NOMINAL O.D.	LENGTH IN FT	MASTER WT
55560-06-09	14	2+Ground	Solid	14	.048"	Grey	.210" x .400"	1000	83
55562-06-09	12	2+Ground	Solid	12	.048"	Grey	.170" x .380"	1000	129
55564-06-09	10	2+Ground	Solid	10	.048"	Grey	.210" x .430"	1000	174

## Multi-Conductor Sprinkler Cable

Polypropylene Underground Sprinkler Cable (PUI) – UL Listed – Direct Burial SOL BC 30 Volt – PE Jacket with Ripcord.




54705

CAT NO	AWG	NUMBER OF CONDUCTORS	LENGTH IN FT	JACKET COLOR	NOMINAL JACKET THICKNESS	NOMINAL O.D.	MASTER WT
54702-04-08	18	2	250	Black	.026"	.196"	6
54703-04-08	18	3	250	Black	.026"	.208"	7
54704-04-08	18	4	250	Black	.026"	.226"	9
54705-04-08	18	5	250	Black	.026"	.246"	11
54706-04-08	18	6	250	Black	.026"	.268"	13
54707-04-08	18	7	250	Black	.026"	.268"	14
54708-04-08	18	8	250	Black	.026"	.290"	16
54709-04-08	18	9	250	Black	.026"	.312"	18
54710-04-08	18	10	250	Black	.026"	.340"	19
54712-04-08	18	12	250	Black	.026"	.352"	23
54713-04-08	18	13	250	Black	.026"	.370"	24

## Pump and Irrigation Cable


Coleman Cable's Pump and Irrigation Cables supply all those little extras you have wished for, like finer stranding, more flexible insulation, improved abrasion resistance and permanent colors that won't fade over time.



42338

CAT NO	DESCRIPTION	STRANDING	WT/1000 FT	LENGTH IN FT
<b>Superior Flat Parallel Pump Cable with Ground</b>				
<i>PVC insulation with extra fine stranding. Foot printed.</i>				
42338	12/3 with 12GA Ground	65/30	135	1000 and 500
42339	10/3 with 10GA Ground	104/30	192	1000 and 500
<b>Standard Twisted Pump Cable (PVC) with Ground</b>				
42359	10/3 with 10GA Ground	Solid	186	1000 and 500
<b>Standard Flat Jacketed Pump Cable (PVC/PVC) with Ground</b>				
<i>PVC jacket and insulation. Foot printed.</i>				
42368	12/3 with 12 g Ground	19/.0185	201	1000 and 500
42369	10/3 with 10 g Ground	19/.0234	268	1000 and 500

*The thermostat, pump and irrigation cables shown on these pages represent a very limited portion of our full offering. For additional items in these categories, please call our customer service group at 800-323-9355 and request one of the full-line Baron™ catalogs.*



# SIGNAL® Fire Alarm Cable

Power limited fire alarm and communication cable for riser or non-riser applications. Used in Fire Alarm Systems, Smoke Detectors and Signaling Fire Protective Circuits.  
 Approvals: UL Type FPLR, NEC Article 760, CUL Type CMG/FT4, California State Fire Marshal



98804

## Fire Alarm Multi-Conductor Cable – Unshielded Type FPLR



CAT NO	AWG	NUMBER OF CONDUCTORS	COPPER STRANDING	LENGTH IN FT	JACKET COLOR	NOMINAL O.D.	MASTER WT
98820-05-04	18	2	Solid	500	Red	.132"	16
98804-05-04	18	4	Solid	500	Red	.154"	27
98620-05-04	16	2	Solid	500	Red	.158"	22
98604-05-04	16	4	Solid	500	Red	.185"	40



98630

## Fire Alarm Multi-Conductor Cable – Overall Shielded Type FPLR



CAT NO	AWG	NUMBER OF CONDUCTORS	COPPER STRANDING	LENGTH IN FT	JACKET COLOR	NOMINAL O.D.	MASTER WT
98300-05-04	18	2	Solid	500	Red	.144"	10
98630-05-04	16	2	Solid	500	Red	.170"	13



85802

## Fire Alarm Multi-Conductor Cable – Unshielded Plenum Type FPLP



CAT NO	AWG	NUMBER OF CONDUCTORS	COPPER STRANDING	LENGTH IN FT	JACKET COLOR	NOMINAL O.D.	MASTER WT
85802-05-04	18	2	Solid	500	Red	.146"	10
85804-05-04	18	4	Solid	500	Red	.174"	17
85602-05-04	16	2	Solid	500	Red	.182"	24
85402-05-04	14	2	Solid	500	Red	.212"	24

## 2 & 4 Conductor Cable – Unshielded Type CM/CL2 - CMX Outdoor



Power limited circuit and communication cable for non-riser applications. Used in control, signaling, systems, and Intercom/PA Systems. Approvals: UL Type CM/CL2 - CMX Outdoor, Article 725 & 800.

CAT NO	GAUGE	NUMBER OF CONDUCTORS	COPPER STRANDING	LENGTH IN FT	NOMINAL JACKET THICKNESS	NOMINAL O.D.	PKG WT LBS
96238-05-09	22	4	Solid	500	.015"	.117"	7
51101-05-09	22	2	7 x 30	500	.014"	.112"	5
51112-05-09	22	4	7 x 30	500	.014"	.126"	7



**Multi-Conductor Cable – Unshielded Type CMR/CL3R**



51104

Power limited circuit and communication cable. Used in remote control, signaling, security systems, and Intercom/PA Systems, Sound/Audio, and Nurse Call. Approvals: UL Type CM/CL3R, NEC Article 725 & 800, CUL Type CMG/FT4, California State Marshal.

CAT NO	GAUGE	NUMBER OF CONDUCTORS	COPPER STRANDING	LENGTH IN FT	NOMINAL JACKET THICKNESS	NOMINAL O.D.	PKG WT LBS
51104-06-09	18	2	7 x .0152	1000	.014"	.142"	7
51114-06-09	18	4	7 x .0152	1000	.014"	.166"	28
51105-06-09	16	2	19 x .0117	1000	.014"	.168"	24

**Multi-Conductor Cable – Overall Shielded Type CMR/CL3R**



67003

Power limited circuit and communication cable. Used in remote control, signaling, security systems, and Intercom/PA Systems, Sound/Audio, and Nurse Call. Approvals: UL Type CMR/CL3R, NEC Article 725 & 800, CUL Type CMG/FT4, California State Marshal.

CAT NO	GAUGE	NUMBER OF CONDUCTORS	COPPER STRANDING	LENGTH IN FT	NOMINAL JACKET THICKNESS	NOMINAL O.D.	PKG WT LBS
95211-05-09	22	2	7 x 30	500	.015"	.122"	6
67001-05-09	22	4	7 x 30	500	.015"	.139"	9
95214-05-09	18	2	7 x .0152	500	.015"	.159"	11
67003-05-09	18	4	7 x .0152	500	.017"	.189"	19

**Area Network Cable**



96263

Power limited circuit and communication cable. Used in remote control, signaling, security systems, and Intercom/PA Systems, Sound/Audio, and Nurse Call. NEC Article 725 & 800, Canadian Type CMG/FT4, California State Marshal.

CAT NO	GAUGE	NUMBER OF CONDUCTORS	COPPER STRANDING	LENGTH IN FT	NOMINAL JACKET THICKNESS	NOMINAL O.D.	PKG WT LBS
<b>Category 3</b>							
<i>Approvals: UL or ETL Type CMR/MPR, NEC Article 800</i>							
96202-06-09	24	2	Solid	1000	.018"	.140"	10
96203-06-09	24	3	Solid	1000	.018"	.160"	13
96204-06-09	24	4	Solid	1000	.018"	.180"	17
96206-06-09	24	6	Solid	1000	.018"	.210"	24
<b>Category 5e</b>							
<i>Approvals: CMR/MPR, Canadian Type CMG FT4, EIA/TIA Cat 5e, (96263); CMP/MPP, Canadian Type CMP FT6 (966956)</i>							
96263-46-06	24	4	Solid	1000	.020"	.220"	20
966956-46-06	24	4	Solid	1000	.015"	.180"	20
96294-06-08*	24	4	Solid	1000	.020"	.250"	30
<b>Category 6</b>							
<i>Approvals: CMR/MPR, Canadian Type CMG FT4(97272); CMP/MPP, Canadian Type CMP FT6 (977964)</i>							
97272-16-06	23	4	Solid	1000	.020"	.230"	26
977964-16-06~	23	4	Solid	1000	-	.210"	26

\*Direct Burial

~Not made in U.S.A.



# SIGNAL® Coaxial Cable



75 OHM Coaxial Cables for use in CCTV or CATV applications. Not for use in riser or plenum applications. RG59/U and RG6/U. Black PVC jacket.



92003

CAT NO	DESCRIPTION RATING	CENTER CONDUCTOR AWG OR DIA (IN) NOM. D.C.R.	DIELECTRIC MATERIAL & O.D. (IN)	SHIELDS NUMBER TYPES NOM. D.C.R.		LENGTH IN FT	ATTENUATION		PKG WT LBS.
							MHZ	NOM DB PER 100'	
92001-05-08	RG6/U	18 AWG	Gas	1st	2nd	500	10	0.9	16
	Type	.0403" CCS	Injected	Bonded	40% Alum		50	1.6	
	CATV	27.5Ω/MFT	PE	APA Foil	Braid		100	2.3	
	CL2		.182		24.7Ω/MFT		200	3.2	
							400	4.8	
92003-05-08	RG/U	18 AWG	Gas	1st	2nd	500	10	0.9	16
	Type	.0403" CCS	Injected	Bonded	60% Alum		50	1.5	
	CATV	27.5Ω/MFT	PE	APA Foil	Braid		100	2.1	
	CL2		.182		11.0Ω/MFT		200	3.1	
							400	4.4	
92006-05-08	RG59/U	22 AWG	Gas	1st	2nd	500	50	2.0	11
	Type	.025"	Injected	Bonded	40% Alum		100	2.9	
	CATV	CCS	PE	APA Foil	Braid		200	4.8	
	CL2	69.0Ω/MFT	.146		14.9Ω/MFT		400	5.6	
							700	7.6	
92074-05-08	RG59/U	20 AWG	Foamed	1st		500	50	1.8	17
	Type	Solid Bare	PE	95% Bare			100	2.5	
	CL2	Copper	.146	Copper			200	3.4	
	CATV	10.1Ω/MFT		Braid			400	5.4	
							700	6.9	
92041-05-08	RG6/U	18 AWG	Gas	1st	3rd	500	10	0.8	33
	Type	.0403" CCS	Injected	Bonded	APA Foil		50	1.4	
	Quad-Shield	27.5Ω/MFT	FPE	APA Foil	4th		100	1.9	
	CATV		.146	2nd	40% Alum.		200	2.7	
	CL2			60% Alum.	Braid		400	4.0	
				Braid	700	6.1			
					1000	7.4			

*The fire alarm, coaxial and other electronic cables shown on these pages represent a very limited portion of our full offering. For additional items in these categories, please call our customer service group at 800-323-9355 and request our Electronic Cable catalog:*



# **CONSUMER CONTENTS**

Range & Dryer Cords .....	35
Replacement Power Supply Cords .....	35
Cube Tap Extensions Cords . .	36
Air Conditioner/Major Appliance Cords .....	36
Surge Protectors & Power Strips .....	37-38
Booster Cables & Clamps .....	39-40
Primary Wire .....	40
RV/Mobile Home .....	41



## Range & Dryer Cords



Thick vinyl insulation with right angle male plug. Strain relief clamp helps prevent cord damage. Hardware included.



CAT NO	WIRE GA/COND	WIRE TYPE	COLOR	LENGTH IN FT	PACKAGE TYPE	125V RATING	MASTER PACK	MASTER WT	MASTER PACK CUBE
<b>Range Cords - Three Conductor, Flat Cord - NEMA 10-50</b>									
09014	6/2 & 8/1	SRDT	Gray	4	Poly Bag	50A	12	20	.73
09015	6/2 & 8/1	SRDT	Gray	5	Poly Bag	50A	12	25	.82
09016	6/2 & 8/1	SRDT	Gray	6	Poly Bag	50A	12	30	.86
<b>Range Cords - Four Conductor, Round Cord - NEMA 14-60</b>									
09044	6/2 & 8/2	SRDT	Black	4	Poly Bag	50A	12	34	1.07
09045	6/2 & 8/2	SRDT	Black	5	Poly Bag	50A	12	42	1.10
09046	6/2 & 8/2	SRDT	Black	6	Poly Bag	50A	12	50	1.25
<b>Dryer Cords - Three Conductor, Flat Cord - NEMA 10-30</b>									
09124	10/3	SRDT	Gray	4	Poly Bag	30A	12	16	.74
09125	10/3	SRDT	Gray	5	Poly Bag	30A	12	17	.77
09126	10/3	SRDT	Gray	6	Poly Bag	30A	12	22	.82
<b>Dryer Cords - Four Conductor, Round Cord - NEMA 14-30</b>									
09154	10/4	SRDT	Black	4	Poly Bag	30A	12	26	1.01
09155	10/4	SRDT	Black	5	Poly Bag	30A	12	22	1.02
09156	10/4	SRDT	Black	6	Poly Bag	30A	12	24	1.17

## Replacement Power Supply Cords

CAT NO	WIRE GA/COND	WIRE TYPE	COLOR	LENGTH IN FT	PACKAGE TYPE	125V RATING	MASTER PACK	MASTER WT	MASTER PACK CUBE
<b>Two Conductor</b>									
<i>Water/oil resistant, superior abrasion resistance.</i>									
09853**~	16/2	SJEO	Black	6	Sleeve	13A	50	18	1.14
09854**~	16/2	SJEO	Black	9	Sleeve	13A	50	25	1.41
<b>Three Conductor</b>									
<i>Water/oil resistant, superior abrasion resistance.</i>									
09855**~	16/3	SJEO	Black	6	Sleeve	13A	50	23	1.14
09856**~	16/3	SJEO	Black	9	Sleeve	13A	50	32	1.41
09857**~	14/3	SJEO	Black	6	Sleeve	15A	25	15	1.14
09858**~	14/3	SJEO	Black	9	Sleeve	15A	25	21	1.41
09885**+~	16/3	SJEO	Black	50	Coil	13A	10	32	1.37
<b>Two and Three Conductor Vinyl</b>									
09702	16/2	SJTW	Black	6	Sleeve	13A	25	9	.50
09703	16/3	SJTW	Black	3	Sleeve	13A	25	10	.32
09706	16/3	SJTW	Black	6	Sleeve	13A	25	13	.54
09709	16/3	SJTW	Black	9	Sleeve	13A	25	22	.60
09716	14/3	SJTW	Black	6	Sleeve	15A	25	18	.56
09719	14/3	SJTW	Black	9	Sleeve	15A	25	23	.74
09733	16/3	SPT-3	Gray	3	Sleeve	13A	25	6	.31
09734	16/3	SPT-3	Gray	4	Sleeve	13A	25	9	.28
09736	16/3	SPT-3	Gray	6	Sleeve	13A	25	12	.30
09724**	16/3	SPT-3	Gray	4	Sleeve	13A	25	9	.32
09726**	16/3	SPT-3	Gray	6	Sleeve	15A	25	12	.31
09743	14/3	SPT-3	Beige	3	Sleeve	15A	25	10	.32
09746	14/3	SPT-3	Beige	6	Sleeve	15A	25	18	.54

\* UL Listed  
 \*\* Right Angle Plug  
 + L5-20 Male End  
 ~ Made in U.S.A.



## Cube Tap Extension Cords



Plug and three-outlet polarized connector for convenient use. Each connector has a safety cover or slide covers permanently attached.



09404



09412

CAT NO	WIRE GA/COND	WIRE TYPE	COLOR	LENGTH IN FT	PACKAGE TYPE	125V RATING	MASTER PACK	MASTER WT	MASTER PACK CUBE
<b>Cube Taps</b>									
09401	16/2	SPT-2	Brown	6	Sleeve	13A	48	15	.67
09402	16/2	SPT-2	Brown	9	Sleeve	13A	36	16	.69
09403	16/2	SPT-2	Brown	12	Sleeve	13A	36	20	.68
09404	16/2	SPT-2	Brown	15	Sleeve	13A	24	16	.50
09405	16/2	SPT-2	Brown	20	Sleeve	13A	24	19	.70
09411	16/2	SPT-2	White	6	Sleeve	13A	48	15	.67
09412	16/2	SPT-2	White	9	Sleeve	13A	36	16	.69
09413	16/2	SPT-2	White	12	Sleeve	13A	36	20	.68
09414	16/2	SPT-2	White	15	Sleeve	13A	24	16	.50
09415	16/2	SPT-2	White	20	Sleeve	13A	24	19	.70
03520-01	16/3	SPT-2	White	8	Sleeve	13A	24	15	.44
03520-07	16/3	SPT-2	Brown	8	Sleeve	13A	24	15	.44
<b>Remote Control Cord</b>									
09345	16/2	SPT-2	White	15	Sleeve	10A	24	26	.66

## Air Conditioner/Major Appliance Cords



Three conductor heavy duty flat vinyl. Right angle male plug. Sturdy cord for use with air conditioners, power tools and major appliances. Grounded, right-angle, male plugs guard against accidental disconnection.



03532

CAT NO	WIRE GA/COND	WIRE TYPE	COLOR	LENGTH IN FT	PACKAGE TYPE	125V RATING	MASTER PACK	MASTER WT	MASTER PACK CUBE
03531	14/3	SPT-3	Beige	3	Sleeve	15A	36	22	.84
03532	14/3	SPT-3	Beige	6	Sleeve	15A	24	20	.58
03533	14/3	SPT-3	Beige	9	Sleeve	15A	18	18	.85
03535	14/3	SPT-3	Beige	12	Sleeve	15A	12	16	.50
03536	14/3	SPT-3	Beige	15	Sleeve	15A	12	19	.62
03537*	14/3	SPT-3	Gray	9	Sleeve	20A/250	18	20	1.05

\* NEMA 6-20P Plug and 6-20R Receptacle





04653

## PowerStation® 8 Outlet Surge Protectors



These 8 outlet surge protectors feature a unique silver and black housing with 3 adapter-spaced outlets, sliding outlet covers, automatic shutdown protection with alarm and an exclusive cord management system.

CAT NO	JOULES	LENGTH IN FT	COLOR	WARRANTY	PACKAGE TYPE	MASTER PACK	MASTER WT	MASTER PACK CUBE
<b>8 Outlet Home Office Surge Protector with 2 Line Phone Protection</b>								
04652	2250	6	Blk/Silver	\$200,000	Box	3	7	0.39
<b>8 Outlet Home Theater Surge Protector with 2 Line Coaxial and Splitter Phone Line Protection</b>								
04649	2600	6	Blk/Silver	\$200,000	Box	3	7	0.39
<b>8 Outlet Network Surge Protector with RJ-45 Data, Coaxial and Splitter Phone Line Protection</b>								
04653	3000	6	Blk/Silver	\$300,000	Box	3	7	0.39



04665

## PowerStation® 7 Outlet Surge Protectors



These 7 outlet surge protectors feature a unique housing with 2 adapter-spaced outlets, sliding outlet covers, automatic shutdown protection and an exclusive cord management system.

CAT NO	JOULES	LENGTH IN FT	COLOR	WARRANTY	PACKAGE TYPE	MASTER PACK	MASTER WT	MASTER PACK CUBE
<b>7 Outlet Home Electronics Surge Protector</b>								
04662	1250	6	Blk/Gry	\$100,000	Box	6	12.12	0.7
<b>7 Outlet TV/DVD Surge Protector with Coaxial Line Protection</b>								
04663	1250	6	Blk/Gry	\$100,000	Box	6	12.12	0.7
<b>7 Outlet Personal Computer Surge Protector with Phone Line Protection</b>								
04664	1250	6	Blk/Gry	\$100,000	Box	6	12.12	0.7



04640

## PowerStation® 6 Outlet Surge Protectors



These 6 outlet surge protectors feature a unique housing, sliding outlet covers, automatic shutdown protection and an exclusive cord management system.

CAT NO	JOULES	LENGTH IN FT	COLOR	WARRANTY	PACKAGE TYPE	MASTER PACK	MASTER WT	MASTER PACK CUBE
<b>6 Outlet Home Electronics Surge Protector</b>								
04638	550	4	Gry/Ivry	\$50,000	Box	6	10.2	0.66
<b>6 Outlet Home Electronics Surge Protector w/ 15' Cord</b>								
04661	550	15	Gry/Ivry	\$50,000	Box	6	12	0.79



04948

## Smart Strip® Surge Protectors



SMART STRIP® Surge Protectors help eliminate “standby power” (also known as vampire power). “Standby power” is the electricity wasted when household or office electronic equipment are operating in “off, sleep, or standby” mode. The SMART STRIP® is easy to use and will quickly pay for itself in energy savings for years to come. It features automatic power control plus superior surge protection and include transformer spaced outlets. Some models feature phone, coax, or data connectivity.

CAT NO	DESCRIPTION	JOULES	CORD LENGTH	COLOR	CONNECTIVITY
04940	10 Outlet SMART STRIP®	2100	6 ft	Gray	N/A
04941	7 Outlet SMART STRIP®	1200	6 ft	Gray	N/A
04949	6 Outlet SMART STRIP®	2250	3 ft	Black	N/A
04950	6 Outlet SMART STRIP®	2250	3 ft	Black	Phone
04951	6 Outlet SMART STRIP®	2250	3 ft	Black	Coax
04946	10 Outlet SMART STRIP®	3600	4 ft	Black	N/A
04947	10 Outlet SMART STRIP®	3600	4 ft	Black	Phone
04948	10 Outlet SMART STRIP®	3600	4 ft	Black	Phone/2 Coax/Data
04952	10 Outlet SMART STRIP®	6000	6 ft	Black	Phone/3 Coax/Data





04617 04610



04625 04628

## PowerStation® Surge Protectors



Surges and spikes are increases in voltage in an electrical line. These fluctuations can gradually, or even instantaneously, destroy sensitive electronics. Protect your investment with a surge protector.

CAT NO	JOULES	LENGTH IN FT	COLOR	WARRANTY	PACKAGE TYPE	MASTER PACK	MASTER WT	MASTER PACK CUBE
<b>6 Outlet Surge Protector</b>								
04617*	150	4	Ivory	-	Sleeve	24	20.5	1.1
<b>6 Outlet Surge Protector</b>								
04610	450	4	White	\$5,000/1 Yr	Sleeve	12	10.4	5.4
<b>6 Outlet Metal Surge Protector</b>								
04625	450	4	Ivory	\$5,000/1 Yr	Box	6	9.5	0.6
<b>6 Outlet Metal Surge Protector with 12' Cord</b>								
04628	750	12	Ivory	\$5,000/1 Yr	Box	12	34.2	1.49

\* Not CUL US Listed. UL and CSA Listed.



04616/04658 04622



04618 04613



04659



09913



04660

## PowerStation® Power Strips and Adapters



Note: these products are not surge protectors and will not protect against power surges.

CAT NO	LENGTH IN FT	COLOR	PACKAGE TYPE	MASTER PACK	MASTER WT	MASTER PACK CUBE
<b>6 Outlet Strip</b>						
04616	4	Ivory	Sleeve	12	10.2	.61
<b>6 Outlet Strip with Safety Outlet Covers</b>						
04622	4	White	Sleeve	24	11	0.5
<b>6 Outlet Strip with Longer Cord</b>						
04658*	15	Ivory	Box	12	26	1.17
<b>6 Outlet Metal Strip</b>						
04618	4	Black	Box	20	39.2	1.92
<b>8 Outlet Power Center</b>						
04613	6	Ivory	Box	6	10.5	0.64
<b>3 Outlet Adapter</b>						
04659	-	White	Blister Card	24	4.5	0.64
<b>3 Outlet Adapter - Plastic Housing</b>						
09913	-	Beige	Blister	18	5	.24
<b>6 Outlet Adapter</b>						
04660	-	White	Blister Card	24	8.4	0.94

\* Not CUL US Listed. UL and CSA Listed.



# No-Tangle™ Booster Cables

## Light-Duty Booster Cables

Road Power® Light-Duty Booster Cables feature dual-extruded wire to provide the user with easy, tangle-free operation. Cables are manufactured with a PVC jacket and the 200 AMP clamps are made from copper-plated steel. Light-Duty Booster Cables comes standard in 10 gauge with 12 feet of length. Booster cables are packaged in retail-style sleeves which emphasize product features and benefits.



08435

CAT NO	WIRE GAUGE	JACKET COLOR	LENGTH IN FT	PACKAGE TYPE	PACK QTY	MASTER WT	MASTER PACK CUBE
08120	10	Black	12	Sleeve	6	18	.53

## Medium-Duty Booster Cables



Road Power® Medium-Duty Booster Cables feature dual-extruded wire to provide the user with easy, tangle-free operation. Cables are manufactured with either a PVC or T-Prene® jacket. While both jackets perform well in warm or cold climates, T-Prene provides additional oil, chemical, and water resistance.

Medium-Duty Booster Cables come standard with 200 AMP copper-plated steel clamps but can easily be upgraded to Polar-Glo™ Clamps. The Polar-Glo™ clamp's triple-polarity identification includes color-coding, indent stamping, and glow-in-the-dark labels. To ensure the highest levels of user-safety, all energized Polar-Glo™ Clamp surfaces are shielded to avoid short circuits and all conductive clamp surfaces are recessed to prevent accidental contact.

Medium-Duty Booster Cables are available in 8 gauge, either in 12 foot or 16 foot lengths, and packaged in a variety of retail-style formats. Some boosters are UL Listed depending on specific model options.



08467

CAT NO	WIRE GAUGE	JACKET COLOR	LENGTH IN FT	PACKAGE TYPE	PACK QTY	MASTER WT	MASTER PACK CUBE
08435* ~	8	Yellow	12	Sleeve	6	17	.50
08445* ~	8	Yellow	12	Box	4	11	.93
08471* ~	8	Yellow	12	Sleeve	6	18	.69
08465	8	Yellow	12	Box	6	24	1.65
08466	8	Yellow	16	Box	6	27	1.22
08467	8	Yellow	12	Bag	2	8	.93

\* Does not feature Polar-Glo™ clamps

~ Not UL Listed



08435

## Heavy-Duty Booster Cables



Road Power® Heavy-Duty Booster Cables feature Polar-Glo™ Clamps and T\*Prene® jacket insulation. This enhanced line of booster cables ensures the highest levels of user-safety and assures dependability in the most extreme climate conditions.

The Polar-Glo™ Clamp is ergonomically-designed so that it can be easily handled by everyone and it attaches itself firmly to both top and side post batteries. The clamps' triple-polarity identification includes color-coding, indent stamping, and glow-in-the-dark labels. In addition, all energized clamp surfaces are shielded to avoid short circuits and all conductive clamp surfaces are recessed to prevent accidental contact.

T\*Prene® insulation was chosen for the wire jacketing material because it remains flexible even under the severest temperatures and is oil, chemical, and water resistant. The 6 gauge wire performs best with small or large automobiles. This line of booster cables is UL Listed.



08565

CAT NO	WIRE GAUGE	JACKET COLOR	LENGTH IN FT	PACKAGE TYPE	PACK QTY	MASTER WT	MASTER PACK CUBE
08565	6	Orange	12	Box	6	25	1.67
08566	6	Orange	16	Box	6	30	1.67





## Extra Heavy-Duty Booster Cables



Road Power's® Extra Heavy-Duty Booster Cables feature Polar-Glo™ Clamps and T\*Prene® jacket insulation. This enhanced line of booster cables ensures the highest levels of user-safety and assures dependability in the most extreme climate conditions.

The Polar-Glo™ Clamp is ergonomically-designed so that it can be easily handled by everyone and it attaches itself firmly to both top and side post batteries. The clamps' triple-polarity identification includes color-coding, indent stamping, and glow-in-the-dark labels. In addition, all energized clamp surfaces are shielded to avoid short circuits and all conductive clamp surfaces are recessed to prevent accidental contact.

T\*Prene® insulation was chosen for the wire jacketing material because it remains flexible even under the severest temperatures and is oil, chemical, and water resistant. The 4 gauge wire performs best with any vehicle including cars, trucks, or SUVs. This line of booster cables is UL Listed.



CAT NO	WIRE GAUGE	JACKET COLOR	LENGTH IN FT	PACKAGE TYPE	PACK QTY	MASTER WT	MASTER PACK CUBE
08665	4	Red	12	Box	2	33	.76
08666	4	Red	16	Box	2	41	.76
08660	4	Red	20	Box	2	16	.76
08662	4	Red	25	Box	2	20	.76

## Commercial Grade Booster Cables



Road Power® Commercial Grade Booster Cables were engineered specifically for the needs of the professional mechanic and feature 500 AMP rated parrot-jaw clamps. Parrot Jaw clamps are manufactured from rugged zinc-plated steel with serrated copper-clad jaws and non-slip vinyl-coated grips. This family of booster cables is constructed with dual-extruded wire to provide the user with tangle-free operation.



CAT NO	WIRE GAUGE	JACKET COLOR	LENGTH IN FT	PACKAGE TYPE	PACK QTY	MASTER WT	MASTER PACK CUBE
08765	4	Black	12	Box	2	13	.93
08766	4	Black	16	Box	2	16	.93
08760	4	Black	20	Box	2	18	.93
08860	2	Black	20	Box	2	24	.93
08862	2	Black	25	Box	2	29	.93

## Booster Cable Clamps



CAT NO	CLAMP RATING	CLAMP COLOR	PACKAGE TYPE	PACK QTY	MASTER WT	MASTER PACK CUBE
<b>Vinyl Coated Steel</b>						
400C-2	500 Amp	1 Red and 1 Black	Blister	6	5	.45
<b>Parrot Jaw Clamp</b>						
08904	500 Amp	1 Red and 1 Black	Bag	12	13	.43

## Primary Wire Bulk Spools



CAT NO	WIRE GAUGE	LENGTH IN FT	STD PKG	PKG WT	MASTER CUBE
10-100-XX	10	100	6	26	.28
12-100-XX	12	100	6	16	.21
14-100-XX	14	100	6	12	.21
16-100-XX	16	100	6	9	.21
18-100-XX	18	100	6	7	.21

Color (XX): 11=Black; 12=Blue; 14=Yellow; 15=Green; 16=Red; 17=White





## RV/Mobile Home Cords

Includes power supply and extension cords that make any installation easy and safe. These are for use in campgrounds, motor parks and recreational areas. All cords and adapters are black.



09521



09524



09542



09572

CAT NO	CORD LENGTH	CORD TYPE & GAUGE	ATTACHMENT PLUG MALE	CORD CONNECTOR FEMALE	BULK PACK	RETAIL PACK
<b>RV Adapters &amp; Accessories</b>						
09521	–	Adapter	5-15P	30A RV	100	4
09522	–	Adapter	30A RV	5-15R	100	4
09524	–	Right Angle Adapter	5-15P	30A RV	100	12
09523*	–	Replacement Plug	30A RV Plug		–	4
09543*	–	Replacement Plug	50A RV Plug		–	3
<b>Adapter Extension Cord Sets</b>						
09542	18 in.	14/3 STW	5-15P	30A RV	12	6
09544	18 in.	14/3 STW	30A RV	5-15R	12	6
09552	18 in.	10/3 STW	30A RV	50A 14-50R	50	4
09554	18 in.	10/3 STW	50A 14-50P	30A RV	50	4
09553	12 in.	10/3 STW Twist-To-Lock Generator Adapter	30A L5-30P	30A RV	50	3
<b>30A &amp; 50A RV Power Supply Cords</b>						
09575	18 in.	10/3 STW	30A RV	–	50	–
09572	18 in.	10/3 STW	–	30A RV	50	–
09525*	25 ft.	10/3 STW	30A RV	–	10	–
09519*	30 ft.	10/3 STW	30A RV	–	8	–
09516*	36 ft.	10/3 STW	30A RV	–	8	–
09541*	40 ft.	10/3 STW	30A RV	–	6	–
09527*	25 ft.	6/3 & 8/1 STW	50A 14-50P	–	3	–
09530*	30 ft.	6/3 & 8/1 STW	50A 14-50P	–	3	–
09536*	36 ft.	6/3 & 8/1 STW	50A 14-50P	–	3	–
09560*	25 ft.	6/3 & 8/1 Flexible SEW 90C	50A 14-50P	–	3	–
09562*	30 ft.	6/3 & 8/1 Flexible SEW 90C	50A 14-50P	–	3	–
09561*	36 ft.	6/3 & 8/1 Flexible SEW 90C	50A 14-50P	–	3	–
09537*	40 ft.	6/3 & 8/1 Flexible SEW 90C	50A 14-50P	–	3	–
<b>15A, 30A &amp; 50A RV Extension Cord Sets</b>						
09510	10 ft.	10/3 STW	30A RV	30A RV	20	–
09550	25 ft.	10/3 STW	30A RV	30A RV	10	2
09555	50 ft.	10/3 STW	30A RV	30A RV	5	–
09570*	30 ft.	10/3 STW	30 RV	30 RV	–	2
09590	25 ft.	6/3 & 8/1 SEW	50A 14-50P	50A 14-50R	2	1

\* UL Listed



# INDEX

Part No.	UPC Code	Page No.	Part No.	UPC Code	Page No.	Part No.	UPC Code	Page No.
01220	0 29892 01220 5	5	02439	0 29892 02439 0	9	04108	0 29892 04108 3	7
01226	0 29892 01226 7	5	02457	0 29892 02457 4	6	04109	0 29892 04109 0	7
01287	0 29892 01287 8	4	02458	0 29892 02458 1	6	04112	0 29892 04112 0	7
01288	0 29892 01288 5	4	02459	0 29892 02459 8	6	04187	0 29892 33072 9	7
01289	0 29892 01289 2	4	02538	0 29892 02538 0	9	04188	0 29892 33073 6	7
01487	0 29892 01487 2	4	02539	0 29892 02539 7	9	04189	0 29892 33074 3	7
01488	0 29892 01488 9	4	02548		8	04207	0 29892 04207 3	7
01489	0 29892 01489 6	4	02549		8	04208	0 29892 04208 0	7
01567	0 29892 01567 1	4	02557	0 29892 02557 1	6	04209	0 29892 04209 7	7
01568	0 29892 01568 8	4	02558	0 29892 02558 8	6	04217	0 29892 04217 2	7
01569	0 29892 01569 5	4	02559	0 29892 02559 5	6	04218	0 29892 04218 9	7
01687	0 29892 01687 6	4	02577		8	04219	0 29892 04219 6	7
01688	0 29892 01688 3	4	02578		8	04388	0 29892 04388 9	7
01689	0 29892 01689 0	4	02579		8	04389	0 29892 04389 6	7
01767	0 29892 01767 5	4	02587	0 29892 82587 4	6	04422	0 29892 04422 0	5
01768	0 29892 01768 2	4	02588	0 29892 82588 1	6	04427	0 29892 04427 5	5
01769	0 29892 01769 9	4	02589	0 29892 82589 8	6	04428	0 29892 04428 2	5
01788	0 29892 01788 0	4	02618	0 29892 33514 4	14	04429	0 29892 04429 9	5
01789	0 29892 01789 7	4	02619	0 29892 33515 1	14	04522	0 29892 04522 7	5
01824	0 29892 01824 5	13	02648		8	04610	0 29892 04610 1	38
01834	0 29892 01834 4	13	02649		8	04613	0 29892 04613 2	38
01844	0 29892 05004 7	13	02687	0 29892 33755 1	6	04616	0 29892 04616 3	38
01854	0 29892 05009 2	13	02688	0 29892 02688 2	6	04617	0 29892 04617 0	38
01864	0 29892 05010 8	13	02689	0 29892 02689 9	6	04618	0 29892 04618 7	38
01910	0 29892 01910 5	13	02800	0 29892 12800 5	15	04622	0 29892 04622 4	38
01911	0 29892 01911 2	13	02816	0 29892 02816 9	15	04625	0 29892 04625 5	38
01912	0 29892 01912 9	13	02821	0 29892 02821 3	15	04628	0 29892 04628 6	38
01915	0 29892 33520 5	14	02822	0 29892 02822 0	15	04633	0 29892 04633 0	21
01917	0 29892 01917 4	23	02827	0 29892 02827 5	15	04638	0 29892 04638 5	37
01918	0 29892 01918 1	12	02828	0 29892 02828 2	15	04649	0 29892 04649 1	37
01919	0 29892 01919 8	12	02831	0 29892 02831 2	15	04652	0 29892 04652 1	37
01920	0 29892 21920 8	12	02832	0 29892 02832 9	15	04653	0 29892 04653 8	37
01922	0 29892 01922 8	23	02834	0 29892 02834 3	15	04658	0 29892 04658 3	38
01924	0 29892 33522 9	14	02837	0 29892 02837 4	15	04659	0 29892 04659 0	38
01934	0 29892 33524 3	14	02838	0 29892 02838 1	15	04660	0 29892 04660 6	38
01938	0 29892 01938 9	12	02839	0 29892 02839 8	15	04661	0 29892 04661 3	37
01939	0 29892 01939 6	12	02841	0 29892 02841 1	15	04662	0 29892 04662 0	37
01940	0 29892 58877 9	23	02851	0 29892 02851 0	15	04663	0 29892 04663 7	37
01941	0 29892 58875 5	23	03392	0 29892 03392 7	15	04664	0 29892 04664 4	37
01960	0 29892 02983 8	12	03482	0 29892 03482 5	4	04820	0 29892 04820 4	21
01962	0 29892 02986 9	12	03487	0 29892 03487 0	4	04940	0 29892 04940 9	37
01970	0 29892 02984 5	12	03488	0 29892 03488 7	4	04941	0 29892 04941 6	37
01972	0 29892 02987 6	12	03489	0 29892 03489 4	4	04946	0 29892 04946 1	37
01980	0 29892 01980 8	12	03520	0 29892 13520 1	36	04947	0 29892 04947 8	37
02211	0 29892 02211 2	6	03531	0 29892 03531 0	36	04948	0 29892 04948 5	37
02304	0 29892 02304 1	6	03532	0 29892 03532 7	36	04949	0 29892 04949 2	37
02305	0 29892 02305 8	6	03533	0 29892 03533 4	36	04950	0 29892 04950 8	37
02306	0 29892 02306 5	6	03535	0 29892 03535 8	36	04951	0 29892 04951 5	37
02307	0 29892 02307 2	6	03536	0 29892 03536 5	36	04952	0 29892 04952 2	37
02308	0 29892 02308 9	6	03537	0 29892 03537 2	36	05006	0 29892 05006 1	19
02309	0 29892 02309 6	6	03588	0 29892 03588 4	4	05007	0 29892 05007 8	19
02407	0 29892 32407 0	6	03589	0 29892 03589 1	4	05307	0 29892 05307 9	19
02408	0 29892 32408 7	6	04004	0 29892 04004 8	7	05327	0 29892 05327 7	19
02409	0 29892 32409 4	6	04102	0 29892 04102 1	7	05328	0 29892 05328 4	19
02438	0 29892 02438 3	9	04107	0 29892 04107 6	7	05337	0 29892 05337 6	19

Part No.	UPC Code	Page No.	Part No.	UPC Code	Page No.	Part No.	UPC Code	Page No.
05338	0 29892 05338 3	19	07598	0 29892 03148 0	18	09402	0 29892 09402 7	36
05360	0 29892 05360 4	21	07599	0 29892 03149 7	18	09403	0 29892 09403 4	36
05364	0 29892 05364 2	20	07605	0 29892 50953 8	17	09404	0 29892 09404 1	36
05407	0 29892 05407 6	19	07625	0 29892 50955 2	17	09405	0 29892 09405 8	36
05408	0 29892 05408 3	19	07765	0 29892 07765 5	17	09411	0 29892 09411 9	36
05427	0 29892 05427 4	19	07766	0 29892 07766 2	17	09412	0 29892 09412 6	36
05428	0 29892 05428 1	19	07775	0 29892 07775 4	17	09413	0 29892 09413 3	36
05570	0 29892 05570 7	21	07776	0 29892 07776 1	17	09414	0 29892 09414 0	36
05657	0 29892 05657 5	19	07777	0 29892 07777 8	17	09415	0 29892 09415 7	36
05658	0 29892 05658 2	19	07818	0 29892 07818 8	17	09510	0 29892 01826 9	41
05857	0 29892 05857 9	19	07880		17	09516	0 29892 01472 8	41
05858	0 29892 05858 6	19	08120	0 29892 08120 1	39	09519	0 29892 01470 4	41
05902	0 29892 05902 6	20	08435	0 29892 08435 6	39	09521	0 29892 09521 5	41
05903	0 29892 05903 3	20	08445	0 29892 08445 5	39	09522	0 29892 09522 2	41
05906	0 29892 05906 4	20	08465	0 29892 08465 3	39	09523	0 29892 09523 9	41
05922	0 29892 05922 4	21	08466	0 29892 08466 0	39	09524	0 29892 09524 6	41
05926	0 29892 05926 2	20	08467	0 29892 08467 7	39	09525	0 29892 01471 1	41
05929	0 29892 05929 3	20	08471	0 29892 08471 4	39	09527	0 29892 09527 7	41
05930	0 29892 05930 9	20	08565	0 29892 08565 0	39	09530	0 29892 02852 7	41
05931	0 29892 05931 6	20	08566	0 29892 08566 7	39	09536	0 29892 09536 9	41
05932	0 29892 05932 3	21	08660	0 29892 08660 2	40	09537	0 29892 03111 4	41
05933	0 29892 05933 0	20	08662	0 29892 08662 6	40	09541		41
05939	0 29892 05939 2	21	08665	0 29892 08665 7	40	09542	0 29892 71882 4	41
05946	0 29892 05946 0	21	08666	0 29892 08666 4	40	09543	0 29892 09543 7	41
05956	0 29892 05956 9	21	08760	0 29892 08760 9	40	09544	0 29892 09544 4	41
05958	7 83585 82799 5	11	08765	0 29892 08765 4	40	09550	0 29892 09550 5	41
05958	7 83585 82799 5	12	08766	0 29892 08766 1	40	09552	0 29892 71924 1	41
05959	7 83585 82797 1	11	08860	0 29892 08860 6	40	09553	0 29892 03157 2	41
05959	7 83585 82797 1	12	08862	0 29892 08862 0	40	09554	0 29892 71923 4	41
05961	0 29892 05961 3	21	08904	0 29892 08904 7	40	09555	0 29892 01827 6	41
05962	7 83585 17220 0	11	09001	0 29892 09001 2	7	09560	0 29892 01145 1	41
05963	7 83585 17221 7	11	09002	0 29892 09002 9	7	09561	0 29892 01182 6	41
05964	7 83585 17224 8	11	09003	0 29892 09003 6	7	09562	0 29892 02183 2	41
05965	7 83585 17225 5	11	09014	0 29892 09014 2	35	09570	0 29892 36788 6	41
05968	0 29892 05968 2	21	09015	0 29892 09015 9	35	09572	0 29892 01723 1	41
05974	0 29892 05974 3	11	09016	0 29892 09016 6	35	09575	0 29892 01724 8	41
05974	0 29892 05974 3	12	09018	0 29892 09018 0	13	09590	0 29892 02985 2	41
05975	0 29892 05975 0	11	09019	0 29892 09019 7	13	09702	0 29892 09702 8	35
05975	0 29892 05975 0	12	09020	0 29892 09020 3	14	09703	0 29892 09703 5	35
05984	0 32664 34090 1	11	09021	0 29892 09021 0	14	09706	0 29892 09706 6	35
05985	0 32664 34120 5	11	09022	0 29892 09022 7	14	09709	0 29892 09709 7	35
05986	7 83585 17218 7	11	09023	0 29892 09023 4	14	09716	0 29892 09716 5	35
05987	7 83585 17219 4	11	09028	0 29892 09028 9	13	09719	0 29892 09719 6	35
05990	7 83585 01301 5	11	09029	0 29892 09029 6	13	09724	0 29892 09724 0	35
05991	7 83585 01303 9	11	09044	0 29892 09044 9	35	09726	0 29892 09726 4	35
05992	7 83585 01300 8	11	09045	0 29892 09045 6	35	09733	0 29892 09733 2	35
05993	7 83585 01302 2	11	09046	0 29892 09046 3	35	09734	0 29892 09734 9	35
05998	0 29892 05998 9	20	09058	0 29892 33516 8	13	09736	0 29892 09736 3	35
05999	0 29892 05999 6	20	09059	0 29892 33517 5	13	09743	0 29892 09743 1	35
07145	0 29892 07145 5	18	09084	0 29892 33518 2	14	09746	0 29892 09746 2	35
07200	0 29892 07200 1	18	09124	0 29892 09124 8	35	09809	0 29892 09809 4	5
07300	0 29892 07300 8	18	09125	0 29892 09125 5	35	09810	0 29892 09810 0	5
07500	0 29892 03368 2	18	09126	0 29892 09126 2	35	09811	0 29892 09811 7	5
07538	0 29892 07538 5	18	09154	0 29892 09154 5	35	09812	0 29892 09812 4	5
07539	0 29892 07539 2	18	09155	0 29892 09155 2	35	09814	0 29892 09814 8	5
07548	0 29892 07548 4	18	09156	0 29892 09156 9	35	09815	0 29892 09815 5	5
07549	0 29892 07549 1	18	09208	0 29892 09208 5	13	09816	0 29892 09816 2	5
07558	0 29892 07558 3	18	09209	0 29892 09209 2	13	09853	0 29892 09853 7	35
07559	0 29892 07559 0	18	09345	0 29892 09345 7	36	09854	0 29892 09854 4	35
07569	0 29892 07569 9	18	09401	0 29892 09401 0	36	09855	0 29892 09855 1	35

Part No.	UPC Code	Page No.	Part No.	UPC Code	Page No.	Part No.	UPC Code	Page No.
09856	0 29892 09856 8	35	23228		24	41105		27
09857	0 29892 09857 5	35	23229		24	41109		27
09858	0 29892 09858 2	35	23325		24	41110		27
09885	0 29892 09885 8	35	23326		24	42338		30
09901	0 29892 09901 5	14	23327		24	42339		30
09902	0 29892 09902 2	14	23328		24	42359		30
09905	0 29892 09905 3	14	23329		24	42368		30
09906	0 29892 06909 4	14	23425		24	42369		30
09913	0 29892 09913 8	38	23426		24	51011		27
10-100		40	23427		24	51012		27
10411		23	23428		24	51041		27
10412		23	23429		24	51042		27
10413		23	2437	0 78693 02437 5	9	51101		31
10414		23	2438	0 78693 02438 2	9	51104		32
10415		23	2439	0 78693 02439 9	9	51105		32
10416		23	2627	0 78693 02627 0	9	51112		31
10416		23	2628	0 78693 02628 7	9	51114		32
10417		23	2629	0 78693 02629 4	9	51791		27
10418		23	2805	0 78693 02805 2	6	51792		27
12-100		40	2806	0 78693 02806 9	6	54501		29
14-100		40	2820	0 78693 02820 5	6	54702		30
1493	0 78693 01493 2	13	2827	0 78693 02827 4	6	54702		30
16-100		40	2882	0 78693 02882 3	6	54703		30
18010		28	2883	0 78693 02883 0	6	54704		30
18020		28	2884	0 78693 02884 7	6	54705		30
18040		28	2885	0 78693 02885 4	6	54706		30
18060		28	2886	0 78693 02886 1	6	54707		30
18080		28	2887	0 78693 02887 8	6	54709		30
18100		28	2888	0 78693 02888 5	6	54710		30
18-100		40	2893	0 78693 02893 9	19	54712		30
18200		28	2948	0 78693 02948 6	19	54713		30
18250		28	30505		26	55211		32
18300		28	30506		26	55302		29
18350		28	30507		26	55303		29
18400		28	30508		26	55304		29
18500		28	30509		26	55305		29
18600		28	30605		26	55306		29
22225		24	30606		26	55307		29
22226		24	30607		26	55308		29
22227		24	30608		26	55309		29
22228		24	30706		26	55310		29
22229		24	30707		26	55312		29
22320		24	30805		26	55560		29
22321		24	30806		26	55562		29
22322		24	30808		26	55564		29
22323		24	31005		26	67001		32
22325		24	31006		26	67003		32
22326		24	31007		26	822225		25
22327		24	31205		26	822226		25
22328		24	31206		26	822227		25
22329		24	31207		26	822228		25
22420		24	31405		26	822229		25
22421		24	31406		26	822320		25
22422		24	31605		26	822321		25
22427		24	31606		26	822322		25
22428		24	400C-2	0 85407 20400 8	40	822323		25
22429		24	41101		27	822325		25
23225		24	41102		27	822326		25
23226		24	41103		27	822327		25
23227		24	41104		27	822328		25

Part No.	UPC Code	Page No.	Part No.	UPC Code	Page No.	Part No.	UPC Code	Page No.
822329		25	85804		31	F35003		23
822420		25	92001		33	F50001		23
822421		25	92003		33	F54601		28
822422		25	92006		33	F54602		28
822423		25	92041		33	F54604		28
822425		25	92074		33	F54605		28
822426		25	95214		32	F54606		28
822427		25	96202		32	F54607		28
822428		25	96203		32	F54608		28
822429		25	96204		32	F54610		28
823226		25	96206		32	F54611		28
823227		25	96238		31	F54614		28
823228		25	96263		32	F54625		28
823325		25	96294		32	F54635		28
823326		25	966956		32	F54650		28
823327		25	97272		32	F54685		28
823328		25	977964		32	F56403		28
823329		25	98300		31			
823427		25	98620		31			
823428		25	98630		31			
830506		25	98640		31			
830509		25	98804		31			
85402		31	98820		31			
85602		31	997362		14			
85802		31	F25001		23			

## COMMON ABBREVIATIONS & WIRE TERMS

**AWG** – American Wire Gauge. A relative system for the designation of wire diameter.

**CSA** – Canadian Standards Association. This is a nonprofit, independent organization that operates a listing service for electrical and electronic materials and equipment the Canadian counterpart of the Underwriters Laboratories.

**ETL** – Intertek Testing Services. This is an independent organization that operates a listing service for electrical and electronic materials and equipment and tests to recognized standards distributed by UL, CSA, NEMA, etc.

**HPN** – Parallel Heater Cord, typically Neoprene-insulated two conductor.

**OSHA** – Occupational Safety and Health Act. Specifically the Williams-Steiger Law passed in 1970 covering all factors relating to safety in places of employment.

**PVC** – Polyvinyl Chloride. Compound used in thermoplastic (SJTW, STW) cords.

**SEOW** – Extra hard service cord. Thermoplastic elastomer, oil resistant (TPE) construction jacket. 600 volt, weather resistant for outdoor use.

**SJEOW** – Hard Service Cord. Thermoplastic elastomer, oil resistant (TPE) construction jacket. 300 volt, weather resistant for outdoor use.

**STW** – Extra Hard Service Cord. Thermoplastic constructed jacket. 600 volt, weather resistant for outdoor use.

**SJTW** – Hard Service Cord. Thermoplastic constructed jacket. 300 volt, weather resistant for outdoor use.

**SPT-1** – Thermoplastic constructed parallel jacketed (flat). 300 volt, 2 or 3 conductor, 18 gauge.

**SPT-2** – Same as SPT-1 but heavier construction. 18-16 gauge.

**SPT-3** – Same as SPT-2 but heavier construction. 18-10 gauge.

**SRDT** – Range and dryer cord, 3 conductor parallel or 4 conductors insulated thermoplastic construction.

**SVT** – Vacuum cleaner service cord. All plastic construction. 2 or 3 conductors.

**TPE** – Abbreviation for thermoplastic elastomer compound used in Polar/Solar cords (SEOW, SJEOW).

**UL** – Underwriters Laboratories. This is a nonprofit independent organization that operates a listing service for electrical and electronic materials and equipment.



## INDUSTRY-LEADING BRANDS

Coleman Cable has long realized the importance of producing top-quality products backed by strong brands. For over three decades CCI has offered some of the strongest and most respected brands in the industry.



### Polar Solar®

America's premier extension cord, Polar/Solar® is lightweight and stays flexible to -67°F. Its rugged T\*Prene® insulation provides superior resistance to abrasion, ozone, oil, grease, and chemicals. Plus, the outer jacket is flame retardant and water resistant. Polar/Solar® Extension Cords feature a power indicator light in the female receptacle to show that the power is on.



### Yellow Jacket®

Yellow Jacket® Contractor Cords & Work Lights provide the ultimate in flexibility and durability with enhanced abrasion resistance to hold up on any jobsite. They have superior flexibility in cold temperatures (down to -58°F) and will not deform in warm temperatures (up to 140°F). Yellow Jacket® contractor cords have lighted plugs to show that the cord has power.



### X-Treme Box™

Coleman Cable's X-Treme Box provides work site power distribution that's economical, rugged, and most of all safe! Now available in two versions to meet contractor demands. The new roll cage designs are constructed with a tubular steel frame for added durability and are vertically stackable for easy transportation. The X-Treme Box provides jobsites with a portable, reliable power distribution center that withstands the harshest jobsite conditions. When there's a job to do there's no time to fool around with power. Choose X-Treme Box from Coleman Cable and get the job done right.

### LUMA-SITE® Luma-Site®

Have light and power when and where you need it by using Luma-Site® Work Lights and Retractable Reels. With so many different models, there is one available for just about every job. Engineered to bring power and light to any application, Luma-Site Work Lights & Retractable Reels are constructed from tough materials to stand up to even the harshest work environments. Ergonomically designed heavy-duty handles fit naturally into the palm of your hand for ease of use. Whether being used on the jobsite or in the workshop, basement, or garage, Luma-Site Work Lights are the perfect solution for your lighting needs.

# Coleman Cable Wire and Cable Products

Marketed under leading brand names such as Seoprene®, Royal®, Baron™ and Signal®, Coleman Cable manufactures one of the most comprehensive lines of cable and related products available today. Our product offering provides cable solutions

## Why Coleman Cable?

- Industry leading brands
- Manufactured in ISO-9000 facilities
- Both cable and assembled products
- Inventory availability:
  - Full Line
  - Multiple Color
  - Reliable Delivery

for virtually any application. Coleman Cable's technical expertise and commitment to innovation ensure the most advanced and highest quality wire and cable on the market.



## Packaging Options\*

### Coleman Cable offers six types of packaging options

- Baro-Pak™
- Knock-Out Box
- Pull-Out Box (Rabbit Pull™)
- Reels
- Reel-in-Box
- Signa-Coil


All provide fast and easy cable access. Kinks and twists are eliminated. You get tangle-free cable delivery each and every time. These durable, compact designs save on installation time while reducing waste and material costs. They can be easily stacked to save room.

*\*Not all options are available for each product*



## Coleman Cable Part Legend

XXXXXX-XX-XX



Put-ups	Code
Reel, 250 ft	04
Reel, 500 ft	05
Reel, 1,000 ft	06
Reel-in-box, 1,000 ft	16
RabbitPull™ Pull-Box, 500 ft	45
RabbitPull™ Pull-Box, 1,000 ft	46
Baro-Pak™ 250 ft	54
Baro-Pak™ 500 ft	55
Baro-Pak™ 1,000 ft	56
Assembled Product	88, 89, 00

Colors	Code
White	01
Yellow	02
Orange	03
Red	04
Green	05
Blue	06
Brown	07
Black	08
Gray	09
Pink	11
Purple	13
Clear	18
Fluorescent	
Pink	21
Ivory	22
Natural	23
Beige	33
Red Striped	
CorraClad™	44



# Exceptional Performance

is reflected in everything we do.

**Coleman Cable Inc.** customers know they can rely on us to consistently deliver a broad range of wire and cable products and innovative solutions backed by recognized brands. These characteristics combined with a solid service platform and dedicated professional people, create a dynamic customer value that's exclusive to Coleman Cable.

## **Broad Range of Products -**

We provide one of the most extensive and diverse lines of electrical, electronic and assembled products in the industry. Through research, development and strategic acquisitions, such as Copperfield, we continue to enhance our product mix to meet customer needs.

## **Innovative Solutions -**

From custom cables for industrial, aerospace or military applications to the latest in electronic cables for security systems, you'll find Coleman Cable at the forefront of product and technology innovation.

## **Recognized Brands -**

Seoprene®, Royal®, Baron®, Signal®, Copperfield®, and Woods® all are leaders in their respective markets. Our distributors know that when they provide these leading brands to their customers, they receive instant acceptance and credibility in the marketplace.

## **Solid Service Platform -**

We utilize more than 2 million sq ft of strategically located, state-of-the-art, ISO-certified manufacturing and distribution facilities. This national footprint and extensive investment in service systems powers us to deliver more than 70,000 SKUs with a better than 97% first-fill rate.

## **Dedicated Professional People -**

We deliver strong performance because our people deliver strong performance every day. We've built a culture that puts customer needs first, making us easy to do business with and placing us at the top of our customers' list of suppliers.

## **Customer Value -**

A Broad Range of Products, Innovative Solutions, Recognized Brands, and a Solid Service Platform are the foundation that Coleman Cable's Dedicated, Professional People build upon to create Customer Value.

