

QUICKIE CUT™ CUT-OFF WHEELS

Quickie Cut™ 3/32 (.094 / 2.5mm) Thin Reinforced Cut-Off Wheels T1 & T27

Improved



Description and Applications

- WA: Aluminum Oxide – Metal & Stainless
 - 3/32" (.094) thickness for cutting/notching wheels.
- Externally reinforced with a unique bond for long wheel life and faster cutting action.

Type 1

Type 1

UPC#	SIZE	SPEC.	RPM	CARTON QTY
45028	4 1/2 x 3/32 x 7/8	WA36-S-BF	13,300	25
45030	5 x 3/32 x 7/8	WA36-S-BF	12,250	25
45046	6 x 3/32 x 7/8	WA36-S-BF	10,200	25
45032	7 x 3/32 x 7/8	WA36-S-BF	8,500	25

Type 27

Type 27

UPC#	SIZE	SPEC.	RPM	CARTON QTY
45019	4 x 3/32 x 5/8	WA36-S-BF	15,300	25
45020	4 1/2 x 3/32 x 7/8	WA36-S-BF	13,300	25
45021	4 1/2 x 3/32 x 5/8-11	WA36-S-BF	13,300	10
45022	5 x 3/32 x 7/8	WA36-S-BF	12,250	25
45023	5 x 3/32 x 5/8-11	WA36-S-BF	12,250	10
45024	6 x 3/32 x 7/8	WA36-S-BF	10,200	25
45025	6 x 3/32 x 5/8-11	WA36-S-BF	10,200	10
45026	7 x 3/32 x 7/8	WA36-S-BF	8,500	25
45027	7 x 3/32 x 5/8-11	WA36-S-BF	8,500	10
New 45113	9 x 3/32 x 7/8	WA36-S-BF	6,600	25
45114	9 x 3/32 x 5/8-11	WA36-S-BF	6,600	10

WHITE AO



1.9mm, 2.5mm, 3.2mm & 4mm Wheel Thickness Profile

