

SAFETY DATA SHEET

1. Identification

Product identifier Dykem® Opaque Stain - Dark Blue

Other means of identification

Part Number 81478, 81778

Recommended use Staining colors

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name ITW Pro Brands

Address 805 E. Old 56 Highway
Olathe, KS 66061

Country (U.S.A.)

Tel: +1 800-443-9536

In Case of Emergency 1-800-535-5053 (Infotrac)

2. Hazard(s) identification

Physical hazards Flammable liquids Category 2

Health hazards Skin corrosion/irritation Category 2

Serious eye damage/eye irritation Category 1

Specific target organ toxicity, single exposure Category 3 narcotic effects

Environmental hazards Not classified.

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Highly flammable liquid and vapor. Causes skin irritation. Causes serious eye damage. May cause drowsiness or dizziness.

Precautionary statement

Prevention Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/eye protection/face protection.

Response If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse. In case of fire: Use appropriate media to extinguish.

Storage Keep cool. Store in a well-ventilated place. Keep container tightly closed. Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC) None known.

Supplemental information Repeated exposure may cause skin dryness or cracking. Contains Orange Oil, Sweet. May produce an allergic reaction.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Butyl Acetate		123-86-4	20 - 30
Ethyl Alcohol		64-17-5	20 - 30
Ethyl Acetate		141-78-6	10 - 20
n-Butyl Alcohol		71-36-3	10 - 20
Isopropanol		67-63-0	1 - 5
Petrolatum		8009-03-8	1 - 5
Propyl Acetate		109-60-4	1 - 3

4. First-aid measures

Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
Skin contact	Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention immediately.
Ingestion	Rinse mouth. Get medical attention if symptoms occur.
Most important symptoms/effects, acute and delayed	May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. May cause respiratory irritation. Skin irritation. May cause redness and pain.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.
General information	Take off all contaminated clothing immediately. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media	Water fog. Alcohol resistant foam. Dry chemical powder. Carbon dioxide (CO ₂).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	Highly flammable liquid and vapor.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
--	--

Methods and materials for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid discharge into drains, water courses or onto the ground.

Environmental precautions**7. Handling and storage****Precautions for safe handling**

Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Do not get this material in contact with eyes. Avoid breathing mist or vapor. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection**Occupational exposure limits**

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value
Butyl Acetate (CAS 123-86-4)	PEL	710 mg/m ³
		150 ppm
Ethyl Acetate (CAS 141-78-6)	PEL	1400 mg/m ³
		400 ppm
Ethyl Alcohol (CAS 64-17-5)	PEL	1900 mg/m ³
		1000 ppm
Isopropanol (CAS 67-63-0)	PEL	980 mg/m ³
		400 ppm
n-Butyl Alcohol (CAS 71-36-3)	PEL	300 mg/m ³
		100 ppm
Propyl Acetate (CAS 109-60-4)	PEL	840 mg/m ³
		200 ppm

US. ACGIH Threshold Limit Values

Components	Type	Value
Butyl Acetate (CAS 123-86-4)	STEL	150 ppm
	TWA	50 ppm
Ethyl Acetate (CAS 141-78-6)	TWA	400 ppm
	STEL	1000 ppm

US. ACGIH Threshold Limit Values

Components	Type	Value
Isopropanol (CAS 67-63-0)	STEL	400 ppm
	TWA	200 ppm
n-Butyl Alcohol (CAS 71-36-3)	TWA	20 ppm
Propyl Acetate (CAS 109-60-4)	STEL	150 ppm
	TWA	100 ppm

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value
Butyl Acetate (CAS 123-86-4)	STEL	950 mg/m3
		200 ppm
	TWA	710 mg/m3
Ethyl Acetate (CAS 141-78-6)		150 ppm
	TWA	1400 mg/m3
Ethyl Alcohol (CAS 64-17-5)		400 ppm
	TWA	1900 mg/m3
		1000 ppm
Isopropanol (CAS 67-63-0)	STEL	1225 mg/m3
		500 ppm
	TWA	980 mg/m3
		400 ppm
n-Butyl Alcohol (CAS 71-36-3)	Ceiling	150 mg/m3
		50 ppm
Propyl Acetate (CAS 109-60-4)	STEL	1050 mg/m3
		250 ppm
	TWA	840 mg/m3
		200 ppm

Biological limit values**ACGIH Biological Exposure Indices**

Components	Value	Determinant	Specimen	Sampling Time
Isopropanol (CAS 67-63-0)	40 mg/l	Acetone	Urine	*

* - For sampling details, please see the source document.

Exposure guidelines**US - California OELs: Skin designation**

n-Butyl Alcohol (CAS 71-36-3)

Can be absorbed through the skin.

US - Minnesota Haz Subs: Skin designation applies

n-Butyl Alcohol (CAS 71-36-3)

Skin designation applies.

US - Tennessee OELs: Skin designation

n-Butyl Alcohol (CAS 71-36-3)

Can be absorbed through the skin.

US NIOSH Pocket Guide to Chemical Hazards: Skin designation

n-Butyl Alcohol (CAS 71-36-3)

Can be absorbed through the skin.

Appropriate engineering controls

Explosion-proof general and local exhaust ventilation. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station. Eye wash fountain and emergency showers are recommended.

Individual protection measures, such as personal protective equipment

Eye/face protection	Wear safety glasses with side shields (or goggles).
Skin protection	
Hand protection	Wear appropriate chemical resistant gloves.
Other	Wear appropriate chemical resistant clothing.
Respiratory protection	Use a positive-pressure air-supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air-purifying respirators may not provide adequate protection.
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.
General hygiene considerations	When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state	Liquid.
Form	Liquid.
Color	Dark blue.

Odor Sweet, Solvent.

Odor threshold Not available.

pH Not available.

Melting point/freezing point Not available.

Initial boiling point and boiling range 170 - 257 °F (76.67 - 125 °C)

Flash point 24.0 °F (-4.4 °C)

Evaporation rate < 1 (BuAc = 1)

Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits

Flammability limit - lower (%) Not available.

Flammability limit - upper (%) Not available.

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure Not available.

Vapor density > 1 (air = 1)

Relative density 0.9 @ 70°F

Solubility(ies)

Solubility (water) Negligible.

Partition coefficient (n-octanol/water) Not available.

Auto-ignition temperature Not available.

Decomposition temperature Not available.

Viscosity Not available.

Other information

Explosive properties Not explosive.

Oxidizing properties Not oxidizing.

VOC
8726D2 Pink: 80.2%, 798 g/L
8732D2 Purple: 84.36%, 773 g/L
8938 Yellow: 86.36%, 771 g/L
8718D1 Black: 87.44%, 772 g/L 8719D1 Dk Blue: 83.54%, 765 g/L
8727D2 Red: 87.95%, 780 g/L 8728D1 White: 80.24%, 754 g/L
8720D1 Lt Blue: 81.85%, 766 g/L 8939 Dk Green: 87.49%, 777 g/L

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents. Alkaline metals. Nitrates.
Hazardous decomposition products	Carbon oxides.

11. Toxicological information

Information on likely routes of exposure

Inhalation	May cause drowsiness and dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be harmful.
Skin contact	Causes skin irritation.
Eye contact	Causes serious eye damage.
Ingestion	Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. Skin irritation. May cause redness and pain.

Information on toxicological effects

Acute toxicity Not expected to be acutely toxic.

Components	Species	Test Results
Butyl Acetate (CAS 123-86-4)		
Acute		
Inhalation		
LC50	Rat	1.8 mg/l, 4 Hours
Oral		
LD50	Rat	14000 mg/kg
Ethyl Acetate (CAS 141-78-6)		
Acute		
Dermal		
LD50	Rabbit	> 20000 mg/kg, 24 Hours
Oral		
LD50	Rat	5.6 g/kg
Ethyl Alcohol (CAS 64-17-5)		
Acute		
Inhalation		
<i>Vapor</i>		
LC50	Rat	51 mg/l, 6 Hours
Isopropanol (CAS 67-63-0)		
Acute		
Oral		
LD50	Rat	4.7 g/kg
n-Butyl Alcohol (CAS 71-36-3)		
Acute		
Dermal		
LD50	Rabbit	3400 mg/kg
Oral		
LD50	Rat	790 mg/kg

Components	Species	Test Results
Petrolatum (CAS 8009-03-8)		
Acute		
Dermal		
LD50	Rabbit	> 2000 mg/kg, 24 Hours
Oral		
LD50	Rat	> 5000 mg/kg
Propyl Acetate (CAS 109-60-4)		
Acute		
Dermal		
LD50	Rabbit	> 18000 mg/kg, 24 Hours
Inhalation		
<i>Vapor</i>		
LC50	Rat	32 mg/l, 4 Hours
Oral		
LD50	Rat	8700 mg/kg
Skin corrosion/irritation	Causes skin irritation.	
Serious eye damage/eye irritation	Causes serious eye damage.	
Respiratory or skin sensitization		
Respiratory sensitization	Not a respiratory sensitizer.	
Skin sensitization	This product is not expected to cause skin sensitization.	
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.	
Carcinogenicity	This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.	
ACGIH Carcinogens		
Isopropanol (CAS 67-63-0)	A4 Not classifiable as a human carcinogen.	
IARC Monographs. Overall Evaluation of Carcinogenicity		
Not listed.		
OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)		
Not listed.		
US. National Toxicology Program (NTP) Report on Carcinogens		
Not listed.		
Reproductive toxicity	Possible reproductive hazard.	
Specific target organ toxicity - single exposure	May cause drowsiness and dizziness.	
Specific target organ toxicity - repeated exposure	Not classified.	
Aspiration hazard	Not an aspiration hazard.	
Chronic effects	Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.	
Further information	Symptoms may be delayed.	

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components	Species	Test Results
Butyl Acetate (CAS 123-86-4)		
Aquatic		
Fish	LC50	Fathead minnow (<i>Pimephales promelas</i>) 17 - 19 mg/l, 96 hours
Ethyl Acetate (CAS 141-78-6)		
Aquatic		
Fish	LC50	Indian catfish (<i>Heteropneustes fossilis</i>) 200.32 - 225.42 mg/l, 96 hours

Components	Species	Test Results
Ethyl Alcohol (CAS 64-17-5)		
Aquatic		
Crustacea	EC50	Water flea (Daphnia magna) 7.7 - 11.2 mg/l, 48 hours
Fish	LC50	Fathead minnow (Pimephales promelas) > 100 mg/l, 96 hours
Isopropanol (CAS 67-63-0)		
Aquatic		
Fish	LC50	Bluegill (Lepomis macrochirus) > 1400 mg/l, 96 hours
n-Butyl Alcohol (CAS 71-36-3)		
Aquatic		
Crustacea	EC50	Water flea (Daphnia magna) 1897 - 2072 mg/l, 48 hours
Fish	LC50	Bluegill (Lepomis macrochirus) 100 - 500 mg/l, 96 hours
Propyl Acetate (CAS 109-60-4)		
Aquatic		
Fish	LC50	Fathead minnow (Pimephales promelas) 56 - 64 mg/l, 96 hours

Persistence and degradability No data is available on the degradability of any ingredients in the mixture.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

Butyl Acetate	1.78
Ethyl Acetate	0.73
Ethyl Alcohol	-0.31
Isopropanol	0.05
n-Butyl Alcohol	0.88
Propyl Acetate	1.23

Mobility in soil Not established.

Other adverse effects None known.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

Waste from residues / unused products Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT

UN number	UN1263
UN proper shipping name	Paint related material including paint thinning, drying, removing, or reducing compound
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Label(s)	3
Packing group	II
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Special provisions	149, B52, IB2, T4, TP1, TP8, TP28
Packaging exceptions	150
Packaging non bulk	173
Packaging bulk	242

IATA

UN number	UN1263
UN proper shipping name	Paint related material (including paint thinning or reducing compounds)

Transport hazard class(es)

Class 3
Subsidiary risk -
Packing group II
Environmental hazards No.
ERG Code 3L

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo aircraft Allowed with restrictions.
Cargo aircraft only Allowed with restrictions.

IMDG

UN number UN1263
UN proper shipping name PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound)

Transport hazard class(es)

Class 3
Subsidiary risk -
Packing group II
Environmental hazards
Marine pollutant No.

EmS F-E, S-E

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

DOT**IATA; IMDG****15. Regulatory information**

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

Toxic Substances Control Act (TSCA)

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Butyl Acetate (CAS 123-86-4)	Listed.
Ethyl Acetate (CAS 141-78-6)	Listed.
n-Butyl Alcohol (CAS 71-36-3)	Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)**SARA 302 Extremely hazardous substance**

Not listed.

SARA 311/312 Hazardous chemical Yes

Classified hazard categories Flammable (gases, aerosols, liquids, or solids)
Skin corrosion or irritation
Serious eye damage or eye irritation
Specific target organ toxicity (single or repeated exposure)

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
N-BUTYL ALCOHOL	71-36-3	10 - 20

Other federal regulations**Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA) Contains component(s) regulated under the Safe Drinking Water Act.**FEMA Priority Substances Respiratory Health and Safety in the Flavor Manufacturing Workplace**

Butyl Acetate (CAS 123-86-4)	Low priority
Ethyl Acetate (CAS 141-78-6)	Low priority
Ethyl Alcohol (CAS 64-17-5)	Low priority
Isopropanol (CAS 67-63-0)	Low priority
n-Butyl Alcohol (CAS 71-36-3)	Low priority
Propyl Acetate (CAS 109-60-4)	Low priority

US state regulations**US. New Jersey Worker and Community Right-to-Know Act**

Butyl Acetate (CAS 123-86-4)
Ethyl Acetate (CAS 141-78-6)
Ethyl Alcohol (CAS 64-17-5)
Isopropanol (CAS 67-63-0)
n-Butyl Alcohol (CAS 71-36-3)
Propyl Acetate (CAS 109-60-4)

California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 2016 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Ethyl Acetate (CAS 141-78-6)
Isopropanol (CAS 67-63-0)
Petrolatum (CAS 8009-03-8)

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No

Country(s) or region	Inventory name	On inventory (yes/no)*
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)
A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 03-17-2020
Revision date 03-18-2020
Version # 02

Disclaimer ITW Pro Brands cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Revision information Hazard(s) identification: Supplemental information
Composition / Information on Ingredients: Disclosure Overrides