

Mini-Dynorbital® Back-Up Pads

For use with Mini-Dynorbital® Sanders



19 mm (3/4") Dia. Back-Up Pads

Part Number	Maximum RPM	Material	Density	Face	Thread
54017	5,000 RPM	Foam	Medium	Rubber	1/4"-20 Female
54087	5,000 RPM	Foam	Soft	Vinyl	1/4"-20 Female
54089	5,000 RPM	Nylon	Hard	Hook	1/4"-20 Female

NOTE: To mount pads that have 1/4"-20 female thread directly to tool for conventional rotary action, use 54021 Adapter.

32 mm (1-1/4") Dia. Back-Up Pads

Part Number	Maximum RPM	Material	Density	Face	Thread
54018	12,000 RPM	Foam	Medium	Rubber	1/4"-20 Female
54031	5,000 RPM	Nylon	Soft	Vinyl	Locking-Type
54033	5,000 RPM	Nylon	Medium	Rubber	Locking-Type
54037	12,000 RPM	Foam	Medium	Vinyl	Locking-Type
54084	15,000 RPM	Urethane	Soft	Vinyl	1/4"-20 Female
54086	12,000 RPM	Urethane	Soft	Vinyl	1/4"-20 Female
54088	15,000 RPM	Foam	Soft	Vinyl	1/4"-20 Female
54090	7,500 RPM	Nylon	Hard	Hook	1/4"-20 Female
54091	12,000 RPM	Foam	Medium	Vinyl	1/4"-20 Female

NOTE: To mount pads that have 1/4"-20 female thread directly to tool for conventional rotary action, use 54021 Adapter.



Hook-Face Random Orbital Back-Up Pads

For use with Random Orbital Sanders



Vacuum Pads

Part Number	Pad Diameter	Holes	Thickness	Nap	Density
56087	76 mm (3")	0	16 mm (5/8")	Short	Medium
56090	76 mm (3")	0	16 mm (5/8")	Long	Medium
22303	76 mm (3")	6	13 mm (1/2")	Short	Medium
56142	76 mm (3")	6	13 mm (1/2")	Short	Medium

NOTE: Our 76 mm (3") pads, without holes, can also be used for vacuum sanding. Vacuum pick-up is around periphery of pad.

