Dynapad® Disc Pads

Quick-Change Locking-Type Disc Pads

Type-R Series



DYNABRADE





- > For use on air and electric die grinders, disc sanders and drills.
- Type-R locking-type abrasive discs thread directly into the Dynapad® allowing for quick abrasive change.
- ➤ Unique one-piece injection-molded design provides low run-out and reduced vibration for smoother running performance.
- Long life, durable and non-marring.
- Available in 2" (51 mm), 3" (76 mm) and 4" (102 mm) diameters.



Continued Leadership in Portable Abrasive Power Tool Technology

Dynabrade Dynapad® Quick-Change Locking-Type Disc Pads

Type-R locking-type pads are available in different diameters for varying grinding applications. Pads have a hard density and are female threaded.

DISC DIAMETER	FEMALE THREAD	PART NUMBER	MAX. OPER. SPEED (RPM)
2" (51 mm)	1/4" - 20	50172	30,000
2" (51 mm)	3/8" - 24	50177	30,000
3" (76 mm)	1/4" - 20	50182	20,000
3" (76 mm)	3/8" - 24	50187	20,000
4" (102 mm)	3/8" - 24	50192	12,000



Threaded Shank Adapters

Model 50102

• 3/8"-24 male to 5/8"-11 female thread

Model 50103

- Has 1/4" diameter shank. 1/4" - 20 male thread
- Mounts to 1/4" and 6 mm collets
- Wrench Flats: 7/16"



50103

Model 50102

Pad Assemblies

Includes Type-R Locking-Type Pad with Shank

Model 50165 2" (51 mm) Hard Pad

(50172 - 1/4"-20)

with 50103 Shank

Model 50183 3" (76 mm) Hard Pad

(50182 - 1/4"-20)

with 50103 Shank

Model 50193 4" (102 mm) Hard Pad (50192 – 3/8"-24)

with 3/8"-24 male to 5/8"-11 female adapter

Model 50165





DISC	ABRASIVE GRIT			
DIAMETER	36	60	80	120
2" (51 mm)	_	92027	92028	92029
3" (76 mm)	_	92031	92032	92033
4" (102 mm)	92047	92049	92050	_

Non-Woven Nylon Type-R Locking-Type Discs



DISC DIAMETER	SUPER FINE	VERY FINE	MEDIUM	COARSE	SE COARSE
2" (51 mm)	90875	90874	90873	90872	_
3" (76 mm)	90879	90878	90877	90876	_
4" (102 mm)	_	_	90868	90867	90863

Abrasive/Pad Trial Packs

PAD Diameter	FEMALE THREAD	PACK PART NUMBER	
2" (51 mm)	1/4"-20	90800	
2" (51 mm)	3/8"-24	90801	
3" (76 mm)	1/4"-20	90802	
3" (76 mm)	3/8"-24	90803	
4" (102 mm)	3/8"-24	90804	
4" (102 mm)	3/8"-24 to 5/8"-11	90805	

DISTRIBUTED BY:

2" (51 mm) Pad Trial Pack







4" (102 mm) Pad Trial Pack



 Includes Type-R locking-type pads and an assortment of coated and non-woven nylon discs for grinding, cleaning, coatings removal, deburring, surface conditioning.



E-Mail: customer.service@dynabrade.com Visit Our Web Site: www.dynabrade.com

DYNABRADE, INC., 8989 Sheridan Drive Clarence, NY 14031-1490 • Phone: (716) 631-0100 Fax: 716-631-2073 • International Fax: 716-631-2524 DYNABRADE EUROPE S.àr.I., Zone Artisanale L-5485 Wormeldange—Haut, Luxembourg Telephone: 352 76 84 94 1 • Fax: 352 76 84 95 1 ©DYNABRADE, INC., 2002 PRINTED IN USA