

# Dynaswivel® Air Line Connectors

- Never Fight an Air Hose Again!
- The Dynaswivel® is a “universal-joint” that connects portable air tools to an air line.
- It improves tool maneuverability, minimizes operator fatigue and extends hose life.
- Patented; works great on air tools or paint guns.
- Choose from the most popular original Dynaswivel® style:
  - SWIVELS 360° AT TWO LOCATIONS which allows air hose to drop straight to the floor, no matter how the tool is held.
- OR, choose from the “single-pivot” style:
  - Right angle, “single-pivot” swivels 360° at one location. Permits 360° maneuverability of tool, while air hose extends horizontally.



## 1/8" NPT Model

**95852**

- 1/4" NPT and 1/8" NPT; fits small air tool.
- Air flow: up to 25 SCFM.
- Weight: 0.19 lb.
- Heavy duty aluminum.



## 1/4" NPT Model

**95460**

- Air flow: up to 25 SCFM.
- Heavy duty aluminum.



## 1/4" NPT, Composite Model

**94300**

- Air flow: up to 33 SCFM.
- Non-marring lightweight composite construction.
- Allows greater air flow than the “original” model (see P/N 95460).

**OUR BEST SELLER!**



## 1/4" NPT, Flow Control Model

**95734**

- Air flow: up to 25 SCFM.
- Built-in dial allows for air flow control.
- Heavy duty aluminum.



## 1/4" NPT, Flow Control, Composite Model

**94407**

- Air flow: up to 46 SCFM.
- Built-in dial allows for air flow control.



## 1/4", 3/8" & 1/2" NPT, Single-Pivot

- Heavy duty aluminum.

**95590**

*1/4" NPT*

- Air flow: up to 25 SCFM.

**95591**

*3/8" NPT*

- Air flow: 26 to 45 SCFM.

**95592**

*1/2" NPT*

- Air flow: 46 to 65 SCFM.



## 3/8", 1/2" & 3/4" NPT Models

- Heavy duty aluminum.

**95461**

*3/8" NPT*

- Air flow: 26 to 45 SCFM.

**95462**

*1/2" NPT*

- Air flow: 46 to 65 SCFM.



**95690**

*3/4" NPT*

- Air flow: above 65 SCFM.

## Dynaswivel® Store Counter Display Pack

**96177**

- Ten 94300 1/4" NPT Dynaswivel® Air Line Connectors in a refillable display box.
- Convenient way to buy!



**Important:** 150 PSI maximum on all models. Do not use on percussion tools or in areas of high mechanical abuse.

**Note:** Do not exceed recommended torque value of 20 ft. lbs.