GENERAL INFORMATION

LEGS®

Wallboard Anchor

PRODUCT DESCRIPTION

The Legs anchor is a one piece drive type anchor designed for use in hollow gypsum wallboard for light to medium duty loads. It is made from heat treated carbon steel which is zinc coated using a special plating process and can be used with No. 6 or No. 8 screws. The Legs anchor is a fast, easy to use expansion anchor designed for use in wallboard. As the screw enters the anchor, it engages the pre-formed tabs in each leg causing them to expand outwards into the base material. Removal of the anchor, if required, is easy. Once removed, the anchor leaves a small slit in the wallboard versus the gaping holes left with other types of hollow wall anchors.


FEATURES AND BENEFITS

- + Fast and easy to use
- + Leaves small "slit" in wallboard, versus larger holes left with other wall anchors
- + Removable


MATERIAL AND INSTALL SPECIFICATIONS

	JUNADLE DA	
Anchor Component	Component Material	 Wallboard
Anchor Body	Heat Treated Spring Steel	

INSTALLATION GUIDELINES



Place the tip of the anchor against the face of the wallboard and tap in with a hammer or back of a screwdriver until the flange is seated against the wallboard.



Locate the fixture and insert a No. 6 or No. 8 metal screw through the fixture hole into the installed anchor. Tighten the screw until the fixture is securely seated against the base material and the anchor is fully expanded.

PERFORMANCE DATA

Ultimate and Allowable Load Capacities for Legs in Wallboard^{1,2}

	3/8" Wallboard		1/2" Wallboard		5/8" Wallboard		3/4" Wallboard	
Loads	Tension	Shear	Tension	Shear	Tension	Shear	Tension	Shear
	Ibs.	Ibs.	Ibs.	Ibs.	Ibs.	Ibs.	Ibs.	Ibs.
	(kN)	(kN)	(kN)	(kN)	(kN)	(kN)	(kN)	(kN)
Ultimate Loads	60	85	70	115	95	165	100	170
	(0.3)	(0.4)	(0.3)	(0.5)	(0.4)	(0.7)	(0.5)	(0.8)
Allowable Loads	15	20	20	30	25	40	25	45
	(0.1)	(0.1)	(0.1)	(0.1)	(0.1)	(0.2)	(0.1)	(0.2)

1. Allowable load capacities listed are calculated using an applied safety factor of 4.0.

2. These fasteners are not recommended for use overhead or applications where holding values are critical.

ORDERING INFORMATION

Legs Drywall Anchor

Cat. No.	Description	Standard Box	Standard Carton
2336	Legs Wallboard Anchor	100	1,000
2335	Legs Anchor, No. 8 x 1" Screw	100	1,000



Bulk Legs

Cat. No.	Description	Standard Box	Standard Carton			
2338	Legs Wallboard Anchor	-	5,000			

SECTION CONTENTS

I

General Information1	
Installation Guidelines1	
Performance Data1	
Ordering Information1	



LEGS

ANCHOR MATERIALS

Zinc plated carbon steel

ANCHOR SIZE RANGE (TYP.)

- No. 6 screw or No. 8 screws
- **SUITABLE BASE MATERIALS**