



# SAFETY DATA SHEET

## 1. Identification

**Product identifier** White Lithium

**Other means of identification**

**Part Number** 03816

**Recommended use** A white lithium based grease formulated with PTFE additives to provide superior lubrication.

**Recommended restrictions** None known.

### Manufacturer/Importer/Supplier/Distributor information

#### Manufacturer

#### Manufacturer

**Company name** ITW Pro Brands

**Address** 4647 Hugh Howell Rd.  
Tucker, GA 30084

**Country** (U.S.A.)

**In Case of Emergency** Tel: +1 770-243-8800  
1-800-424-9300 (inside U.S.)  
+001 703-527-3887 (outside U.S.)

**Website** www.lpslabs.com

**E-mail** lpssds@itwprobrands.com

## 2. Hazard(s) identification

**Physical hazards** Flammable aerosols Category 1  
Gases under pressure Liquefied gas

**Health hazards** Skin corrosion/irritation Category 2  
Serious eye damage/eye irritation Category 2A  
Reproductive toxicity (fertility) Category 2  
Specific target organ toxicity, single exposure Category 3 narcotic effects  
Specific target organ toxicity, repeated exposure Category 2

**Environmental hazards** Not classified.

**OSHA defined hazards** Not classified.

### Label elements



#### Signal word

Danger

#### Hazard statement

Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes skin irritation. Causes serious eye irritation. Suspected of damaging fertility or the unborn child. May cause drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure by skin contact.

#### Precautionary statement

##### Prevention

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Wear eye/face protection. Avoid breathing dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves. Use personal protective equipment as required.

<b>Response</b>	IF exposed or concerned: Get medical advice/attention. IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Specific treatment (see this label). Take off contaminated clothing and wash before reuse. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
<b>Storage</b>	Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
<b>Disposal</b>	Dispose of contents/container in accordance with local/regional/national/international regulations.
<b>Hazard(s) not otherwise classified (HNOC)</b>	None known.
<b>Supplemental information</b>	37.23% of the mixture consists of component(s) of unknown acute oral toxicity.

### 3. Composition/information on ingredients

#### Mixtures

Chemical name	Common name and synonyms	CAS number	%
Petroleum Gases, Liquefied, Sweetened		68476-86-8	20 - 30
Petroleum Oil		64742-52-5	20 - 30
2-Methylpentane		107-83-5	10 - 20
Acetone		67-64-1	10 - 20
2,3-Dimethylbutane		79-29-8	1 - 10
3-Methylpentane		96-14-0	1 - 10
2,2-Dimethylbutane		75-83-2	1 - 5
N-hexane		110-54-3	1 - 3
Titanium Dioxide		13463-67-7	< 1

### 4. First-aid measures

<b>Inhalation</b>	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Get medical attention if symptoms persist.
<b>Skin contact</b>	Remove contaminated clothing immediately and wash skin with soap and water. Get medical attention if irritation develops and persists.
<b>Eye contact</b>	Immediately flush with plenty of water for at least 15 minutes. If easy to do, remove contact lenses. Get medical attention if irritation develops and persists.
<b>Ingestion</b>	Call a physician or poison control center immediately. Only induce vomiting at the instruction of medical personnel. Never give anything by mouth to an unconscious person. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Do not use mouth-to-mouth method if victim ingested the substance.
<b>Most important symptoms/effects, acute and delayed</b>	Irritation of eyes and mucous membranes. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. Defatting of the skin. Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea. Narcosis. Behavioral changes. Decrease in motor functions. Prolonged exposure may cause chronic effects.
<b>Indication of immediate medical attention and special treatment needed</b>	Provide general supportive measures and treat symptomatically. In case of shortness of breath, give oxygen. Keep victim under observation. Symptoms may be delayed.
<b>General information</b>	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. In the case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). Wash contaminated clothing before reuse.

### 5. Fire-fighting measures

<b>Suitable extinguishing media</b>	Powder. Alcohol resistant foam. Carbon dioxide (CO <sub>2</sub> ).
<b>Unsuitable extinguishing media</b>	Do not use a solid water stream as it may scatter and spread fire.
<b>Specific hazards arising from the chemical</b>	Contents under pressure. Pressurized container may explode when exposed to heat or flame.

<b>Special protective equipment and precautions for firefighters</b>	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
<b>Fire fighting equipment/instructions</b>	Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. Water runoff can cause environmental damage.
<b>Specific methods</b>	Use standard firefighting procedures and consider the hazards of other involved materials. Move container from fire area if it can be done without risk. In the event of fire and/or explosion do not breathe fumes.
<b>General fire hazards</b>	Extremely flammable aerosol.

## 6. Accidental release measures

<b>Personal precautions, protective equipment and emergency procedures</b>	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate personal protective equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. Use personal protection recommended in Section 8 of the SDS.
<b>Methods and materials for containment and cleaning up</b>	Refer to attached safety data sheets and/or instructions for use. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Stop leak if you can do so without risk. Isolate area until gas has dispersed. Collect spillage. Prevent product from entering drains. Following product recovery, flush area with water. For waste disposal, see section 13 of the SDS.
<b>Environmental precautions</b>	Avoid release to the environment. Contact local authorities in case of spillage to drain/aquatic environment. Prevent further leakage or spillage if safe to do so. Do not contaminate water. Avoid discharge into drains, water courses or onto the ground.

## 7. Handling and storage

<b>Precautions for safe handling</b>	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers.
<b>Conditions for safe storage, including any incompatibilities</b>	Avoid breathing gas. Avoid contact with skin. Avoid contact with eyes. Avoid contact during pregnancy/while nursing. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Observe good industrial hygiene practices. When using, do not eat, drink or smoke. Wash hands thoroughly after handling. Avoid release to the environment. Do not empty into drains. Level 3 Aerosol. Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source.

## 8. Exposure controls/personal protection

### Occupational exposure limits

U.S. - OSHA Components	Type	Value	Form
Petroleum Oil (CAS 64742-52-5)	PEL	5 mg/m <sup>3</sup>	Oil mist
US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)			
Components	Type	Value	Form
Acetone (CAS 67-64-1)	PEL	2400 mg/m <sup>3</sup> 1000 ppm	
N-hexane (CAS 110-54-3)	PEL	1800 mg/m <sup>3</sup> 500 ppm	
Titanium Dioxide (CAS 13463-67-7)	PEL	15 mg/m <sup>3</sup>	Total dust.
ACGIH Components	Type	Value	Form
Petroleum Oil (CAS 64742-52-5)	TWA	5 mg/m <sup>3</sup>	Oil mist

**US. ACGIH Threshold Limit Values**

Components	Type	Value
2,2-Dimethylbutane (CAS 75-83-2)	STEL	1000 ppm
	TWA	500 ppm
2,3-Dimethylbutane (CAS 79-29-8)	STEL	1000 ppm
	TWA	500 ppm
2-Methylpentane (CAS 107-83-5)	STEL	1000 ppm
	TWA	500 ppm
3-Methylpentane (CAS 96-14-0)	STEL	1000 ppm
	TWA	500 ppm
Acetone (CAS 67-64-1)	STEL	750 ppm
	TWA	500 ppm
N-hexane (CAS 110-54-3)	TWA	50 ppm
Titanium Dioxide (CAS 13463-67-7)	TWA	10 mg/m3

**US. NIOSH: Pocket Guide to Chemical Hazards**

Components	Type	Value
Acetone (CAS 67-64-1)	TWA	590 mg/m3
		250 ppm
N-hexane (CAS 110-54-3)	TWA	180 mg/m3
		50 ppm

**Biological limit values****ACGIH Biological Exposure Indices**

Components	Value	Determinant	Specimen	Sampling Time
Acetone (CAS 67-64-1)	50 mg/l	Acetone	Urine	*
N-hexane (CAS 110-54-3)	0.4 mg/l	2,5-Hexanedion, without hydrolysis	Urine	*

\* - For sampling details, please see the source document.

**Exposure guidelines****US - California OELs: Skin designation**

N-hexane (CAS 110-54-3) Can be absorbed through the skin.

**US ACGIH Threshold Limit Values: Skin designation**

N-hexane (CAS 110-54-3) Can be absorbed through the skin.

**Appropriate engineering controls**

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

**Individual protection measures, such as personal protective equipment**

**Eye/face protection** Wear safety glasses with side shields (or goggles). Eye wash fountain is recommended.

**Skin protection**

**Hand protection** For prolonged or repeated skin contact use suitable protective gloves. Chemical resistant gloves are recommended.

**Other** Avoid contact with clothing. Wear suitable protective clothing. Chemical resistant gloves.

**Respiratory protection**

No personal respiratory protective equipment normally required. Use a positive-pressure air-supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air-purifying respirators may not provide adequate protection.

**Thermal hazards**

Not applicable.

**General hygiene considerations**

When using, do not eat, drink or smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

## 9. Physical and chemical properties

<b>Appearance</b>	Liquid.
<b>Physical state</b>	Gas.
<b>Form</b>	Aerosol.
<b>Color</b>	White.
<b>Odor</b>	Slight petroleum odor
<b>Odor threshold</b>	Not available.
<b>pH</b>	Not available.
<b>Melting point/freezing point</b>	Not applicable
<b>Initial boiling point and boiling range</b>	158 °F (70 °C)
<b>Flash point</b>	< 1.4 °F (< -17.0 °C) Tag Closed Cup
<b>Evaporation rate</b>	< 1 (Ethyl Ether =1)
<b>Flammability (solid, gas)</b>	Not available.
<b>Upper/lower flammability or explosive limits</b>	
<b>Flammability limit - lower (%)</b>	1.8 % Estimated
<b>Flammability limit - upper (%)</b>	9.5 % Estimated
<b>Explosive limit - lower (%)</b>	Not available.
<b>Explosive limit - upper (%)</b>	Not available.
<b>Vapor pressure</b>	2200 - 2700 mm Hg @ 20 °C
<b>Vapor density</b>	3 (air =1)
<b>Relative density</b>	Not available.
<b>Solubility(ies)</b>	
<b>Solubility (water)</b>	Not soluble in water
<b>Partition coefficient (n-octanol/water)</b>	< 1
<b>Auto-ignition temperature</b>	Not available.
<b>Decomposition temperature</b>	Not available.
<b>Viscosity</b>	700 - 1600 cP
<b>Other information</b>	
<b>Percent volatile</b>	85 - 90 %
<b>Specific gravity</b>	0.74 - 0.78 @ 20 °C (water =1)
<b>VOC (Weight %)</b>	51.3 % per U.S. State and Federal Consumer Product Regulations

## 10. Stability and reactivity

<b>Reactivity</b>	The product is stable and non-reactive under normal conditions of use, storage and transport.
<b>Chemical stability</b>	Material is stable under normal conditions.
<b>Possibility of hazardous reactions</b>	Hazardous polymerization does not occur.
<b>Conditions to avoid</b>	Avoid temperatures exceeding the flash point. Heat, flames and sparks.
<b>Incompatible materials</b>	Acids. Strong oxidizing agents.
<b>Hazardous decomposition products</b>	Upon decomposition this product emits acrid dense smoke with carbon dioxide, carbon monoxide, water and other products of combustion.

## 11. Toxicological information

### Information on likely routes of exposure

<b>Inhalation</b>	Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea.
<b>Skin contact</b>	Causes skin irritation.
<b>Eye contact</b>	Causes serious eye irritation.

**Ingestion**

May be harmful if swallowed and enters airways. However, ingestion is not likely to be a primary route of occupational exposure.

**Symptoms related to the physical, chemical and toxicological characteristics**

Irritant effects. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Defatting of the skin. Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea. Behavioral changes. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

**Information on toxicological effects**

**Acute toxicity** Narcotic effects.

<b>Components</b>	<b>Species</b>	<b>Test Results</b>
Acetone (CAS 67-64-1)		
<b>Acute</b>		
<i>Dermal</i>		
LD50	Guinea pig	> 7426 mg/kg, 24 Hours > 9.4 ml/kg, 24 Hours
	Rabbit	> 7426 mg/kg, 24 Hours > 9.4 ml/kg, 24 Hours
<i>Inhalation</i>		
LC50	Rat	55700 ppm, 3 Hours 132 mg/l, 3 Hours 76 mg/l, 4 Hours 50.1 mg/l 50.1 mg/l, 8 Hours
<i>Oral</i>		
LD50	Mouse	5.2 g/kg
	Rat	5800 mg/kg 2.2 ml/kg
N-hexane (CAS 110-54-3)		
<b>Acute</b>		
<i>Dermal</i>		
LD50	Rabbit	> 2000 mg/kg, 4 Hours > 5 ml/kg, 4 Hours
<i>Inhalation</i>		
LC50	Mouse	48000 ppm, 4 Hours
	Rat	> 5000 ppm, 24 Hours > 31.86 mg/l 73860 ppm, 4 Hours
<i>Oral</i>		
LD50	Rat	24 ml/kg 24 mg/kg
	Wistar rat	49 mg/kg
Petroleum Gases, Liquefied, Sweetened (CAS 68476-86-8)		
<b>Acute</b>		
<i>Inhalation</i>		
LC50	Mouse	1237 mg/l, 120 Minutes 52 %, 120 Minutes
	Rat	1355 mg/l
Petroleum Oil (CAS 64742-52-5)		
<b>Acute</b>		
<i>Dermal</i>		
LD50	Rabbit	> 2000 mg/kg

Components	Species	Test Results
		> 2000 mg/kg, 24 Hours
<i>Inhalation</i>		
LC50	Rat	2.18 mg/l, 4 Hours
<i>Oral</i>		
LD50	Rat	> 2000 mg/kg
Titanium Dioxide (CAS 13463-67-7)		
<b>Acute</b>		
<i>Inhalation</i>		
LC50	Rat	> 2.28 mg/l, 4 Hours
<i>Oral</i>		
LD50	Rat	> 2000 mg/kg
<b>Skin corrosion/irritation</b>	Causes skin irritation.	
<b>Serious eye damage/eye irritation</b>	Causes serious eye irritation.	
<b>Respiratory or skin sensitization</b>		
<b>Respiratory sensitization</b>	Not a respiratory sensitizer.	
<b>Skin sensitization</b>	Irritating to skin. Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis. May be harmful in contact with skin.	
<b>Germ cell mutagenicity</b>	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.	
<b>Carcinogenicity</b>	This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.	
<b>ACGIH Carcinogens</b>		
Acetone (CAS 67-64-1)		A4 Not classifiable as a human carcinogen.
Titanium Dioxide (CAS 13463-67-7)		A4 Not classifiable as a human carcinogen.
<b>IARC Monographs. Overall Evaluation of Carcinogenicity</b>		
Titanium Dioxide (CAS 13463-67-7)		2B Possibly carcinogenic to humans.
<b>OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)</b>		
Not listed.		
<b>Reproductive toxicity</b>	Suspected of damaging fertility or the unborn child.	
<b>Specific target organ toxicity - single exposure</b>	Narcotic effects.	
<b>Specific target organ toxicity - repeated exposure</b>	May cause damage to organs through prolonged or repeated exposure by skin contact.	
<b>Aspiration hazard</b>	Not likely, due to the form of the product.	
<b>Chronic effects</b>	Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects. May be harmful if absorbed through skin.	
<b>Further information</b>	Symptoms may be delayed.	

## 12. Ecological information

**Ecotoxicity** Toxic to aquatic life with long lasting effects.

Components	Species	Test Results
Acetone (CAS 67-64-1)		
<b>Aquatic</b>		
Crustacea	EC50	Water flea (Daphnia magna) 10294 - 17704 mg/l, 48 hours
Fish	LC50	Rainbow trout, donaldson trout (Oncorhynchus mykiss) 4740 - 6330 mg/l, 96 hours
N-hexane (CAS 110-54-3)		
<b>Aquatic</b>		
Fish	LC50	Fathead minnow (Pimephales promelas) 2.101 - 2.981 mg/l, 96 hours
Titanium Dioxide (CAS 13463-67-7)		
<b>Aquatic</b>		
Crustacea	EC50	Water flea (Daphnia magna) > 1000 mg/l, 48 hours

Components	Species	Test Results
Fish	LC50	Mummichog ( <i>Fundulus heteroclitus</i> )
		> 1000 mg/l, 96 hours
<b>Persistence and degradability</b>	Not inherently biodegradable.	
<b>Bioaccumulative potential</b>	No data available for this product.	
<b>Partition coefficient n-octanol / water (log Kow)</b>		
White Lithium	< 1	
2,2-Dimethylbutane	3.82	
2,3-Dimethylbutane	3.42	
2-Methylpentane	3.74	
3-Methylpentane	3.6	
Acetone	-0.24	
N-hexane	3.9	
<b>Mobility in soil</b>	Not available.	
<b>Other adverse effects</b>	None known.	

### 13. Disposal considerations

<b>Disposal instructions</b>	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. This material and its container must be disposed of as hazardous waste. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.
<b>Hazardous waste code</b>	D001: Waste Flammable material with a flash point <140 F D003: Waste Reactive material

#### US RCRA Hazardous Waste U List: Reference

Acetone (CAS 67-64-1)

U002

<b>Waste from residues / unused products</b>	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
<b>Contaminated packaging</b>	Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied. Do not re-use empty containers.

### 14. Transport information

#### DOT

<b>UN number</b>	UN1950
<b>UN proper shipping name</b>	Aerosols, flammable
<b>Transport hazard class(es)</b>	
<b>Class</b>	2.1
<b>Subsidiary risk</b>	-
<b>Label(s)</b>	2.1
<b>Packing group</b>	Not applicable.
<b>Special precautions for user</b>	Read safety instructions, SDS and emergency procedures before handling.
<b>Special provisions</b>	N82
<b>Packaging exceptions</b>	306
<b>Packaging non bulk</b>	304
<b>Packaging bulk</b>	None

#### IATA

<b>UN number</b>	UN1950
<b>UN proper shipping name</b>	Aerosols, flammable
<b>Transport hazard class(es)</b>	
<b>Class</b>	2.1
<b>Subsidiary risk</b>	-
<b>Label(s)</b>	2.1
<b>Packing group</b>	Not applicable.
<b>Environmental hazards</b>	No.
<b>Special precautions for user</b>	Read safety instructions, SDS and emergency procedures before handling.
<b>Other information</b>	
<b>Passenger and cargo aircraft</b>	Allowed.
<b>Cargo aircraft only</b>	Allowed.



**IMDG**

**UN number** UN1950  
**UN proper shipping name** AEROSOLS, flammable  
**Transport hazard class(es)**  
**Class** 2.1  
**Subsidiary risk** -  
**Label(s)** 2.1  
**Packing group** Not applicable.  
**Environmental hazards**  
**Marine pollutant** No.  
**EmS** F-D, S-U  
**Special precautions for user** Read safety instructions, SDS and emergency procedures before handling.  
**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code** Not applicable.

**DOT****IATA; IMDG****15. Regulatory information**

**US federal regulations** This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

**TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)**

Not regulated.

**CERCLA Hazardous Substance List (40 CFR 302.4)**

Acetone (CAS 67-64-1) Listed.  
 N-hexane (CAS 110-54-3) Listed.

**SARA 304 Emergency release notification**

Not regulated.

**OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)**

Not listed.

**Superfund Amendments and Reauthorization Act of 1986 (SARA)**

**Hazard categories** Immediate Hazard - Yes  
 Delayed Hazard - Yes  
 Fire Hazard - Yes  
 Pressure Hazard - Yes  
 Reactivity Hazard - No

**SARA 302 Extremely hazardous substance**

Not listed.

SARA 311/312 Hazardous chemical Yes

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
N-HEXANE	110-54-3	1 - 3

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

N-hexane (CAS 110-54-3)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA) Not regulated.

Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number

Acetone (CAS 67-64-1) 6532

Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

Acetone (CAS 67-64-1) 35 %WV

DEA Exempt Chemical Mixtures Code Number

Acetone (CAS 67-64-1) 6532

US state regulations

US - California Candidate Chemicals: Listed

Acetone (CAS 67-64-1)  
Petroleum Gases, Liquefied, Sweetened (CAS 68476-86-8)  
Petroleum Oil (CAS 64742-52-5)  
Titanium Dioxide (CAS 13463-67-7)

US - California Candidate Chemicals: Listed on initial list

N-hexane (CAS 110-54-3)

US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

Not listed.

US. Massachusetts RTK - Substance List

2,2-Dimethylbutane (CAS 75-83-2)  
2,3-Dimethylbutane (CAS 79-29-8)  
2-Methylpentane (CAS 107-83-5)  
3-Methylpentane (CAS 96-14-0)  
Acetone (CAS 67-64-1)  
N-hexane (CAS 110-54-3)  
Titanium Dioxide (CAS 13463-67-7)

US. New Jersey Worker and Community Right-to-Know Act

2,2-Dimethylbutane (CAS 75-83-2)  
2,3-Dimethylbutane (CAS 79-29-8)  
2-Methylpentane (CAS 107-83-5)  
Acetone (CAS 67-64-1)  
N-hexane (CAS 110-54-3)  
Titanium Dioxide (CAS 13463-67-7)

US. Pennsylvania Worker and Community Right-to-Know Law

2,2-Dimethylbutane (CAS 75-83-2)  
2,3-Dimethylbutane (CAS 79-29-8)  
2-Methylpentane (CAS 107-83-5)  
3-Methylpentane (CAS 96-14-0)  
Acetone (CAS 67-64-1)  
N-hexane (CAS 110-54-3)  
Titanium Dioxide (CAS 13463-67-7)

US. Rhode Island RTK

Acetone (CAS 67-64-1)  
N-hexane (CAS 110-54-3)

US. California Proposition 65

Not Listed.

## International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

## 16. Other information, including date of preparation or last revision

**Issue date** 08-10-2015

**Version #** 01

**Disclaimer** The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**Revision Information** This document has undergone significant changes and should be reviewed in its entirety.