



T-91™

NON-SOLVENT DEGREASER

The non-solvent, non-flammable, and environmentally safe degreaser ideal for industrial cleaning applications.



PACKAGE SIZES

Net Contents	Part No.
28 fl.oz. (828 ml) trigger spray	06328
1 gal. (3.78 l)	06301
5 gal. (18.93 l)	06305
55 gal. (208 l)	06355

FEATURES

- Ideal for traditional solvent cleaning, plastic basin style part washers and dip tanks
- VOC compliant in all 50 states
- Zero VOCs: VOC's per CARB/OTC/LADCO: 0 g/L, VOC content per SCAQMD: 0 g/L
- Biodegradable
- Efficient: requires less product than traditional solvents to get the job done
- pH = 8 - 9
- Contains no solvents
- Moderate foam for effective mechanical cleaning
- Nonfood Compounds Program Listed Category Code: A1 Registration #141975
- Acceptable for use in Canadian Food Processing Establishments

APPLICATIONS

- Basin style parts washer
- Bilges
- Compressors
- Concrete
- Dip Tanks
- Drill presses
- Engines
- Floors
- Forklifts
- Grease traps
- Machinery
- Marine
- Tanks
- Tools



T-91™

NON-SOLVENT DEGREASER

APPLICATION DILUTION CHART

As a direct solvent degreaser replacement:

Use T-91 undiluted (straight) as a direct solvent replacement for all heavy duty degreasing applications.

Dilution Ratio Product (as a neutral pH cleaner) Water	Applications: (Suggested dilution ranges for cleaning surfaces not damaged by water alone)
1:10 - 1:75	Floors: Light to Heavy Duty Cleaning/Degreasing
Undiluted to 1 : 10	Metals: Heavy Duty Cleaning/Degreasing
1:20 - 1:80	Plastics, rubbers & painted surfaces
1:50 - 1:100	Glass
1:10 - 1:80	Pressure Washing: Light to Heavy-Duty Cleaning/Degreasing
1:10 - 1:25	Soak Tanks [Do Not Exceed 140°F (60°C)]

NOTE:

(1) A fresh water rinse is recommended after using stronger dilutions.

(2) Limit exposure time and temperature when cleaning sensitive, non ferrous metals such as aluminum and copper to avoid potential darkening of the metal surface.

PROPERTIES

Appearance / physical state	Liquid	Color	Colorless
Odor	Mild soapy	Vapor pressure	18 mm Hg
Evaporation rate	1 BuAc (water=1)	Flash point °F(°C)	None
Boiling/Condensation point °F(°C)	> 212°F (> 100°C)	Flash point method	None
Specific gravity	1.04	pH	8 - 9
VOC	0 % per State and Federal Consumer Product Regulations	Volatiles	70 - 90 %
Solubility (water)	Water soluble	Solubility in water	Water soluble

DIRECTIONS

Apply product to surface then agitate with a brush, cloth, or wipe. Remove soils by wiping. Rinse with water for a completely residue-free surface. NOTE: Test for compatibility on sensitive materials. Do not heat above 175°F (79°C). Do not allow parts to soak longer than 24 hours. The concentrated product may darken or damage sensitive surfaces and non-ferrous metals when used at elevated temperatures.

DISPOSAL INFORMATION

Waste must be disposed of in accordance with any and all applicable environmental control rules and/or regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner.

MATERIAL SAFETY DATA SHEETS AVAILABLE UPON REQUEST OR VISIT OUR WEB SITE : WWW.LPSLABS.COM



4647 Hugh Howell Road • Tucker, GA 30084 • TEL: (800) 241-8334 or (770) 243-8800 • FAX: (800) 543-1563 or (770) 243-8899
Internet Web Site: www.lpslabs.com

©2015 ITW Pro Brands • LPS® is a registered trademark of Illinois Tool Works • Printed in U.S.A. • All Rights Reserved • Form #TDS_06328 • Rev. 6/2015