

Product Data Sheet

Nitri-Guard Plus



Safety Products

Description: Unsupported Nitril Chemical resistant gloves with increased comfort due to a soft flock lining. Designed for handling inorganic acids and alkalis, oil, grease and other substances. Ideal for use e.g. in the chemical industry, painting, agriculture, printing and other applications, requiring flexibility and dexterity but also good protection against many chemicals, oil, grease,...

Articles:

LA102G	thickness 0, 28 mm (11mil) unflocked
LA132G	thickness 0, 38 mm (15mil) flocklined
LA142G	thickness 0, 38 mm (15mil) unflocked
LA172G	thickness 0, 43 mm (17mil) flocklined
LA225G	thickness 0, 56 mm (22mil) unflocked
LA258G	thickness 0, 63 mm (25 mil) unflocked

Sizes : 7 , 8 , 9 , 10, 11 (EN420)

Standards: EN420.2003, EN388.2003, EN374.2003.

CE Category: Complex design



4001 JKL
4002 for LA 225
4102 for LA258

Chemicals	B.T.T (Min)	Class
n-Heptane	>480	6
40% Sodium hydroxide	>480	6
96% Sulphuric Acid	> 30	2

B.T.T. (break through time) is defined as the time at which one micro-gram of a chemical permeates per square centimetre per minute through the glove palm sample (1 μ gm/cm²/min.).

Packaging: 12 pairs per pack, 144 pairs per case, LA225 and LA258 72 per case.