

Large diameter cut-off wheels

Portable gas saw – Performance line SG

Blended grain portable cut-off wheel designed to cut ductile iron, water main pipe and cast iron quickly and efficiently. For use on electric or gas-powered portable cut-off saws.

Abrasive: Aluminum oxide A and silicon carbide C

Workpiece materials

Ductile iron, cast iron, steel-reinforced concrete, composite materials

Application

Cutting of reinforced solid materials

PFERD specification number AC 24 Q SG



Diameter x thickness nominal [Inches]	Thickness metric [mm]	Bore	EDP number		Max. RPM
Flat (type 1)	_	•			
12 x 1/8	4.0	20 mm	64118	20	6,400
12 x 1/8	4.0	1"	64120	20	6,400
14 x 3/16	4.5	20 mm	64123	10	5,500
14 x 3/16	4.5	1"	64124	10	5,500
16 x 3/16	4.5	20 mm	64117	10	4,800
16 x 3/16	4.5	1"	64126	10	4,800



Designed for cutting masonry and natural materials on electric and gas-powered portable saws. Aggressive cutting action and long service life

Abrasive: Silicon carbide C

Workpiece materials

Masonry, natural stone, refractory brick

Application

Cutting of solid material

PFERD specification number

C 24 R SG



Diameter x thickness nominal [Inches]	Thickness metric [mm]	Bore	EDP number		Max. RPM
Flat (type 1)					
12 x 1/8	4.0	20 mm	64230	20	6,400
12 x 1/8	4.0	1"	64235	20	6,400
14 x 3/16	4.5	20 mm	64236	10	5,500
14 x 3/16	4.5	1"	64238	10	5,500
16 x 3/16	4.5	1"	64239	10	4,800