

General purpose cut-off wheels for use on die grinders. Ideal for working in hard-to-reach areas or close quarters.

**Abrasive: Aluminum oxide A**

**Workpiece material**

Steel

**Applications**

Cutting of sheet metal, sections and solid material

**Recommendations for use**

- Thin cut-off wheels (.035" and .1/16") provide fast and convenient cutting with minimized burr formation.
- Use 1/8" cut-off wheels for maximum service life and high lateral stability.
- Fully reinforced for use in hand-held cut-off work. Ideal for working in hard-to-reach areas or close quarters.


**Ordering note**

Mandrels for die grinder wheels listed on page 60.

**PFERD specification number**

A 24/36/60 P PSF



Diameter x thickness nominal [Inches]	Thickness metric [mm]	Grit	Bore [Inches]	EDP number		Max. RPM
<b>Flat (type 1)</b>						
2 x .035	0.9	60	1/4	69201	50	30,000
2 x .035	0.9	60	3/8	69203	50	30,000
2 x 1/16	1.6	36	1/4	69205	50	30,000
2 x 1/16	1.6	60	1/4	69207	50	30,000
2 x 1/16	1.6	36	3/8	69209	50	30,000
2 x 1/16	1.6	60	3/8	69211	50	30,000
2 x 1/8	3.2	36	3/8	69217	50	30,000
3 x .035	0.9	60	1/4	69301	50	25,000
3 x .035	0.9	60	3/8	69303	50	25,000
3 x 1/16	1.6	36	1/4	69305	50	25,000
3 x 1/16	1.6	60	1/4	69307	50	25,000
3 x 1/16	1.6	36	3/8	69309	50	25,000
3 x 1/16	1.6	60	3/8	69311	50	25,000
3 x 1/8	3.2	36	1/4	69313	50	25,000
3 x 1/8	3.2	60	1/4	69315	50	25,000
3 x 1/8	3.2	24	3/8	69316	50	25,000
3 x 1/8	3.2	36	3/8	69317	50	25,000
3 x 1/8	3.2	60	3/8	69319	50	25,000
4 x .035	0.9	60	1/4	69401	50	19,000
4 x .035	0.9	60	3/8	69403	50	19,000
4 x 1/16	1.6	36	1/4	69405	50	19,000
4 x 1/16	1.6	60	1/4	69407	50	19,000
4 x 1/16	1.6	36	3/8	69409	50	19,000
4 x 1/16	1.6	60	3/8	69411	50	19,000
4 x 1/16	1.6	36	5/8	69413	50	19,000
4 x 1/8	3.2	24	3/8	69420	50	19,000
4 x 1/8	3.2	60	3/8	69423	50	19,000
5 x .035	0.9	60	3/8	69501	50	12,200
5 x 1/16	1.6	36	3/8	69503	50	12,200
6 x .035	0.9	60	1/2	69601	25	10,200