


Power wire brushes

Stem mounted wheel brushes

Knot wire, standard twist



EDP 82915


More aggressive brushing action than crimped wire for faster removal. For deburring, cleaning, rust removal, and weld seam conditioning.

Recommendation for use

Suitable tool drives: straight grinders, flexible shafts, power drills.

Made in the USA.



Diameter d_1 [Inches]	Stem dia. d_3 [Inches]	No. of knots	Trim length l_2 [Inches]	Face width b [Inches]	Wire diameter and EDP number			Recom. speed [RPM]	MSFS max. [RPM]	
					.012	.014	.020			


Carbon steel wire

3	1/4	18	3/4	7/16	82915	82916	82917	12,500 - 18,700	25,000	10
3-1/4	1/4	20	3/4	1/2	-	82946	82947	12,500 - 18,700	25,000	10
4	1/4	22	3/4	5/8	-	82919	82920	12,500 - 18,700	25,000	10

Stainless steel wire (INOX)

3	1/4	18	3/4	7/16	-	82921	-	10,000 - 16,000	25,000	10
3-1/4	1/4	20	3/4	1/2	-	82948	-	10,000 - 16,000	25,000	10
4	1/4	22	3/4	5/8	-	82922	-	10,000 - 16,000	25,000	10

ECAP® encapsulated



EDP 83614


Encapsulated for maximum brushing action.

Ordering note

For additional information on ECAP® encapsulation, please see page 13.

Made in the USA.



Diameter d_1 [Inches]	Stem dia. d_3 [Inches]	Trim length l_2 [Inches]	Face width b [Inches]	ECAP® grade	Wire diameter and EDP number			Recom. speed [RPM]	MSFS max. [RPM]	
					.008	.010	.012			

Carbon steel wire

2	1/4	1/2	1/4	E3	-	83612	-	10,000 - 15,000	20,000	10
3	1/4	1	1/4	E3	83613	-	83614	10,000 - 15,000	20,000	10