

Nylon wheel and tube brushes




Type 6.6 nylon filament for scrubbing and brushing contaminants from surfaces and low-abrasion cleaning. Excellent for light cleaning action with solution-dependent applications. These brushes may be used individually or gangmounted to any desired width.

Highly abrasion resistant, highly chemical resistant, also heat stabilized.

Ordering note

For drive arbors and adapters, please refer to pages 66-67.

Made in the USA.



Diameter d,	Arbor hole d,	Trim length I	Face width b	Width on arbor	Keyway dimensions	Filament dia. and EDP number		Recom. speed [RPM]	MSFS max. [RPM]	Adapter style	
[Inches]	[Inches]	[Inches]	[Inches]	[Inches]	[Inches]	.014 Nylon	.016 Nylon				
Small diameter copper centre											
2	1/2	1/2	3/8	7/32	-	84340	-	5,200 - 9,000	20,000	-	10
3	1/2	1	3/8	5/16	-	-	84343	5,200 - 9,000	20,000	F	10
Narrow face											
6	1-1/4	1-1/2	3/4	7/16	1/4 x 1/8	-	84344	1,500 - 2,500	6,000	А	2
8	1-1/4	1-7/8	3/4	5/8	1/4 x 1/8	-	84345	1,200 - 2,000	4,800	А	2




Threaded nylon tube brushes are designed for working the inside surfaces of tubes, pipes and pipe bends.

Recommended for removing sand casting residue and other debris from inside surfaces, and light cleaning of stainless steel pipe ID for pharmaceutical and food industry.

For more information on flexible shafts and adapters, see our "Power tools" catalogue (section 209).

Made in the USA.



Brush diameter d₁		Brush Overall Thread size I_2 I_1 d_2			For pipe I.D.	Filament dia. and EDP number	Recom. speed	For use with flexible shaft EDP	Use with threaded adapter	
[Inches]	[mm]	[Inches]	[Inches]		[Inches]	.018 Nylon	[RPM]		EDP	
1	25	1/2	1-5/16	8-32	3/4	84430	750 - 2,000	94264, 94274	95810, 95811	10
1-1/4	32	1/2	1-5/16	8-32	1	84432	750 - 2,000	94264, 94274	95810, 95811	10
1-3/4	44	1/2	1-5/16	8-32	1-1/2	84434	750 - 2,000	94264, 94274	95810, 95811	10
2-1/4	57	1/2	1-5/16	8-32	2	84436	750 - 2,000	94264, 94274	95810, 95811	10
2-3/4	69	1/2	1-5/16	8-32	2-1/2	84438	750 - 2,000	94264, 94274	95810, 95811	10
3-1/4	82	1/2	1-5/16	8-32	3	84440	750 - 2,000	94264, 94274	95810, 95811	10

