



# SPECIFICATION SHEET

## 85-7512J

### “B/C” GRADE SHOULDER SPLIT COWHIDE LEATHER DOUBLE PALM GLOVE WITH FABRIC BACK AND JOINTED INNER PALM - RUBBERIZED SAFETY CUFF

- Constructed from the most economical split cowhide available on the market today
- Double palm offers comfort, insulation and heat protection
- Jointed inner palm for increased glove life and durability
- Cotton lined palm for extra comfort
- Gunn cut pattern delivers excellent durability, wear and comfort, especially for heavier gloves
- Wing thumb increases comfort in open-handed work
- Fabric back provides breathability and flexibility
- Leather knuckle strap and finger tips for extra protection
- Elastic closure sewn inside glove for safety and comfort
- Rubberized fabric safety cuff helps protect wrist, allows for fast removal, and water resistance
- Cotton color binding denotes sizing

#### APPLICATIONS

- Construction
- Material handling
- General maintenance

#### TECHNICAL DATA

MATERIAL	Cowhide leather		
COLOR	Shell: <span style="color: gray;">■</span> Gray w/ Red Stripe / Palm: <span style="color: green;">■</span> Green		
CUFF STYLE	Rubberized safety cuff		
SIZES	S - XL		
PACKAGING	12 per dozen, 6 dozen per case		
CASE SIZE (in/cm)	S - M	L	XL
	17.5 x 10.4 x 16.3 44.5 x 26.5 x 41.5	17.5 x 10.8 x 16.3 44.5 x 27.5 x 41.5	17.5 x 11.6 x 16.3 44.5 x 29.5 x 41.5
CASE WEIGHT	S	M	L
	37.45 lbs / 17 kg	39.7 lbs / 18 kg	41.9 lbs / 19 kg
COO	China		

#### BARCODES

ITEM	BAG	DOZEN	CASE
■ 85-7512J/S	---	01616314122650	02616314122659
■ 85-7512J/M	---	01616314122643	02616314122642
■ 85-7512J/L	---	01616314015809	02616314015809
■ 85-7512J/XL	---	01616314122636	02616314122635



#### DIMENSIONS (in/cm)

	S	M	L	XL
<b>A</b>	9.4 / 24	10 / 25.5	10.4 / 26.5	10.8 / 27.5
<b>B</b>	4.7 / 12	5.1 / 13	5.3 / 13.5	5.5 / 14
<b>H</b>	<span style="color: red;">■</span> Red	<span style="color: green;">■</span> Green	<span style="color: brown;">■</span> Brown	<span style="color: blue;">■</span> Blue

Tolerance: +/- 0.6cm for length & 0.3cm for width  
Thickness: 1.1 (+/- 0.1) mm

