

**"A" Taper** Carbide Drill Bits

**PRODUCT DESCRIPTION**

"A" Taper drill bits are designed for use in a rotary hammer equipped with an "A" Taper type chuck. The bits meet ANSI standards and can be used to drill in concrete, block, brick and soft stone. "A" Taper drill bits are manufactured from high grade tool steel. The bit is formed with a Turbo flute which quickly removes dust to provide faster drilling into a variety of masonry materials. The carbide insert is copper brazed to provide longer bit life. "A" Taper drill bits can be used in most models of rotary hammer drills with an "A" Taper shank adapter.

**FOR USE WITH**

Rotary Hammer with "A" Taper Chuck or Adapter

**SIZE RANGE**

1/4" x 6" to 3/4" x 12"



**DRILL BIT SPECIFICATIONS AND ORDERING INFORMATION**

**"A" Taper Drill Bits**

Catalog Number	Size	Usable Length	Standard Tube	Wt./ Dozen
0712	1/4" x 6"	4"	1	1 1/2
0752	5/8" x 9"	7"	1	6
0754	5/8" x 12"	10"	1	7

Catalog Number	Size	Usable Length	Standard Tube	Wt./ Dozen
0760	3/4" x 9"	7"	1	12
0762	3/4" x 12"	10"	1	16

**"A" Taper Drill Bit Adapters**

Catalog Number	Size	Standard Pouch	Wt./ Adapter
0791	SDS-Plus to "A" Tapper	1	13
0790	SDS-Max to "A" Tapper	1	13

Catalog Number	Size	Standard Pouch	Wt./ Adapter
0798	Ejector Pin "A" Tapper	1	1 1/4

**Rotary** Carbide Drill Bits

**PRODUCT DESCRIPTION**

Rotary carbide bits are designed for use in a rotation only drill equipped with a 3 jaw Jacobs type chuck. The bits meet ANSI standards and can be used to drill in soft or brittle masonry materials using rotation only. Fast spiral flutes are for fast drilling in soft to medium masonry materials such as block or brick. Deep fluted drills perform best in concrete where the wide fluting helps clean concrete chips and dust from the hole.

**FOR USE WITH**

Rotary Only Drill

**SIZE RANGE**

1/8" x 2-1/2" to 3/4" x 6"



**DRILL BIT SPECIFICATIONS AND ORDERING INFORMATION**

**Fast Spiral Rotary Bits**

Catalog Number	Drill Size	Shank Size	Usable Length	Overall Length	Std. Tube	Wt./ Dozen
8500	1/8"	1/8"	1 3/4"	2 1/2"	1	1/4
8506	3/16"	3/16"	1 3/4"	3"	1	1/2
8508	1/4"	1/4"	1 3/4"	4"	1	3/4
8512	5/16"	1/4"	2 1/2"	4"	1	3/4
8514	3/8"	1/4"	2 1/2"	4"	1	1
8560	3/8"	1/4"	4 1/2"	6"	1	1 1/2
8520	1/2"	3/8"	4"	6"	1	3
8566	1/2"	3/8"	10"	12"	1	3
8526	5/8"	1/2"	4"	6"	1	5
8570	5/8"	1/2"	10 1/2"	12"	1	8
8530	3/4"	1/2"	4"	6"	1	6

**Deep Flute Rotary Bits**

Catalog Number	Drill Size	Shank Size	Usable Length	Overall Length	Std. Tube	Wt./ Dozen
8606	3/16"	3/16"	1 3/4"	3"	1	1/2
8608	1/4"	1/4"	1 3/4"	4"	1	3/4
8610	9/32"	1/4"	2 1/2"	4"	1	3/4