

Feed Rate Chart

Alpha Code	Feed in Inches per Revolution (IPR) ± 25%															Ø Diameter				
	1mm/ 1/32"	2mm/ 3/32"	3mm/ 1/8"	4mm/ 5/32"	5mm/ 3/16"	6mm/ 1/4"	8mm/ 5/16"	10mm/ 3/8"	12mm/ 1/2"	15mm/ 9/16"	16mm/ 5/8"	20mm/ 3/4"	25mm/ 1"	30mm/ 1.1/8"	40mm/ 1.5/8"	50mm/ 2"				
A	0.0004	0.0009	0.0011	0.0013	0.0014	0.0017	0.0021	0.0024	0.0027	0.0032	0.0034	0.0043	0.0049	0.0053	0.0061	0.0069				
B	0.0006	0.0011	0.0015	0.0016	0.0018	0.0021	0.0026	0.0031	0.0035	0.0041	0.0043	0.0053	0.0060	0.0065	0.0074	0.0082				
C	0.0006	0.0013	0.0017	0.0020	0.0022	0.0025	0.0031	0.0039	0.0043	0.0049	0.0051	0.0063	0.0071	0.0077	0.0087	0.0094				
D	0.0006	0.0015	0.0021	0.0024	0.0027	0.0031	0.0039	0.0047	0.0051	0.0059	0.0061	0.0074	0.0083	0.0090	0.0100	0.0108				
E	0.0007	0.0017	0.0024	0.0028	0.0031	0.0037	0.0045	0.0055	0.0059	0.0068	0.0071	0.0085	0.0094	0.0102	0.0112	0.0122				
F	0.0007	0.0020	0.0029	0.0033	0.0037	0.0043	0.0054	0.0065	0.0070	0.0080	0.0083	0.0098	0.0108	0.0116	0.0126	0.0135				
G	0.0007	0.0022	0.0033	0.0038	0.0043	0.0050	0.0063	0.0075	0.0081	0.0091	0.0094	0.0110	0.0122	0.0130	0.0140	0.0148				
H	0.0008	0.0026	0.0040	0.0046	0.0051	0.0059	0.0075	0.0090	0.0096	0.0107	0.0110	0.0126	0.0140	0.0148	0.0157	0.0165				
I	0.0008	0.0030	0.0047	0.0053	0.0059	0.0068	0.0087	0.0104	0.0110	0.0122	0.0126	0.0142	0.0157	0.0165	0.0173	0.0181				
J	0.0009	0.0033	0.0053	0.0060	0.0067	0.0078	0.0098	0.0117	0.0124	0.0137	0.0142	0.0159	0.0175	0.0183	0.0191	0.0198				
K	0.0010	0.0036	0.0059	0.0067	0.0075	0.0087	0.0110	0.0130	0.0138	0.0153	0.0157	0.0177	0.0193	0.0201	0.0209	0.0215				
L	0.0011	0.0040	0.0065	0.0073	0.0082	0.0094	0.0120	0.0142	0.0152	0.0165	0.0169	0.0191	0.0207	0.0215	0.0224	0.0231				
M	0.0012	0.0043	0.0071	0.0080	0.0089	0.0102	0.0130	0.0154	0.0165	0.0177	0.0181	0.0205	0.0220	0.0228	0.0238	0.0248				
N	0.0013	0.0047	0.0077	0.0086	0.0095	0.0110	0.0140	0.0165	0.0179	0.0189	0.0193	0.0219	0.0234	0.0242	0.0253	0.0265				
S	0.0003	0.0006	0.0008	0.0010	0.0012	0.0015	0.0020	0.0031	0.0039	0.0048	0.0051	0.0059	0.0070	0.0070	0.0090					
T	0.0006	0.0011	0.0016	0.0020	0.0024	0.0028	0.0035	0.0043	0.0051	0.0063	0.0067	0.0075	0.0080	0.0090	0.0100					
U	0.0010	0.0019	0.0028	0.0031	0.0035	0.0042	0.0055	0.0067	0.0079	0.0088	0.0091	0.0094	0.0110	0.0120	0.0140					
V	0.0015	0.0027	0.0039	0.0045	0.0051	0.0060	0.0079	0.0098	0.0110	0.0122	0.0126	0.0134	0.0160	0.0170	0.0200					
W	0.0019	0.0035	0.0051	0.0059	0.0067	0.0079	0.0102	0.0130	0.0150	0.0165	0.0169	0.0177	0.0190	0.0190	0.0200					
X	0.0022	0.0041	0.0059	0.0071	0.0083	0.0098	0.0130	0.0165	0.0189	0.0210	0.0217	0.0228								
Y	0.0027	0.0049	0.0071	0.0087	0.0102	0.0125	0.0169	0.0217	0.0276	0.0276	0.0276	0.0291								
Z	0.0037	0.0068	0.0098	0.0128	0.0157	0.0210	0.0315	0.0394	0.0433	0.0463	0.0472	0.0472								

How To Use This Chart to Find Cutting Feed Rate (IPR):

1. Find your Alpha Code on the AMG Chart (example: 279 U : U is the Alpha Code)
2. Find the closest diameter for your cutting application on the chart to find your IPR

Application Material Groups (AMG)		Hardness HRC	ISO
1. Steel	1.1 Magnetic soft steel	12L14, 12L15	<120 HB P 1
	1.2 Structural Steel/ case carburising steel	1005-1025, 1214, 1215, A36	<200 HB P 1
	1.3 Plain Carbon steel	1030-1060, 1050-1060, 1144-1146	<24 P 2
	1.4 Alloy steel	4140,4340,52100,8620 H11-H41,A2,D2,01,P20,420	<24 P 3
	1.5 Alloy steel/ Hardened and tempered steel	4140,4340,52100,8620 H11-H41,A2,D2,01,P20,420	>24<38 P 4
	1.6 Alloy steel/ Hardened and tempered steel	4140,4340,52100,8620 H11-H41,A2,D2,01,P20,420	>38 H 1
	1.7 Alloy steel Hardened	A2-D2, H10-H41, L1-L6, M1-M42, T1	49-55 H 3
	1.8 Alloy steel Hardened	A2-D2, H10-H41, L1-L6, M1-M42, T1	55-63 H 4
2. Stainless Steel	2.1 Free machining Stainless Steel	200, 303, 416, 420F, 430F, 440	<24 M 1
	2.2 Austenitic	301, 302, 304, 316, 321, 330, CUSTOM 455, AM-350	<24 M 3
	2.3 Ferritic + Austenitic, Martensitic	318-329, 400-446, DUPLEX	<32 M 2
	2.4 Precipitation Hardened	15-5PH, Custom 450 17-4PH	<32 S 2
3. Cast Iron	3.1 Lamellar graphite	Grey, G10, Gg40, J431C, A48 CLASS 20	<150 HB K 1
	3.2 Lamellar graphite	Grey, GG25-Gg40, J158, A48 CLASS 40-60	>150 HB<32 K 2
	3.3 Nodular graphite/ Malleable Cast Iron	A220, A436, A439, A602, Black, GGG40-GGG70	<200 HB K 3
	3.4 Nodular graphite/ Malleable Cast Iron	Black Gts/Gtw, J434C	>200 HB<32 K 4
4. Titanium	4.1 Titanium, unalloyed	Commercially Pure	<200 HB S 1
	4.2 Titanium, alloyed	6Al4V, 6A14V-2Sn, Monel, Monel K	<28 S 2
	4.3 Titanium, alloyed	6Al4V-4Mo, 7A14V-4Mo, 4911-4967	>28<38 S 3
5. Nickel	5.1 Nickel, unalloyed	Commercially Pure, 17644, 200, 5553	<150 HB S 1
	5.2 Nickel, alloyed	Monel 400, Hastelloy C, Inconel 625, Waspaloy	<28 S 2
	5.3 Nickel, alloyed	Inconel 718, Nimonic 75-95, Rene 41, Inconel 825, A286	>28<38 S 3
6. Copper	6.1 Copper	Commercially Pure	<100 HB N 3
	6.2 β-Brass, Bronze	314-340, 350-370	<200 HB N 4
	6.3 α-Brass	Alloyed Cu + Al + Fe, Long Chipping	<200 HB N 3
	6.4 High Strength Bronze	Ampco 18-25	<49 N 4
7. Aluminium Magnesium	7.1 Al, Mg, unalloyed	Commercially Pure	<100 HB N 1
	7.2 Al alloyed, Si<0.5%	6061 T6, 7075, 314-340	<150 HB N 1
	7.3 Al alloyed, Si>0.5%<10%	6061 T6, 380-390	<120 HB N 1
	7.4 Al alloyed, Si>10% Mg alloys	Magnesium Whisker Reinforced	<120 HB N 2
8. Synthetic Materials	8.1 Thermoplastics	Ultradim, Polystrol	---
	8.2 Thermosetting plastics	Bakelit, Pertinax	---
	8.3 Reinforced plastic materials	CFK, GFKAFK	---
9. Hard Mat.	9.1 Cermets (Metal-ceramics)	Ferrotic	<54 H
10. Graphite	10.1 Standard graphite		---



COBALT SCREW MACHINE DRILL



Heavy Duty Screw Machine Length

M40CO - Fractional Sizes

M41CO - Wire Gauge Sizes

M42CO - Letter Sizes

Low thrust design self centering Split Point for easier penetration. Cobalt base material with Bronze Oxide for wear resistance and lubricity.



d_1 Ø Inch	d_1 Ø Nr.	d_1 Ø letter	d_1 decimal Inch	l_2 Inch	l_1 Inch	Pack Qty	M40CO	M41CO	M42CO
	60		0.0400	1/2	1.3/8	12	—	041360 ¹⁾	—
	59		0.0410	1/2	1.3/8	12	—	041359 ¹⁾	—
	58		0.0420	1/2	1.3/8	12	—	041358 ¹⁾	—
	57		0.0430	1/2	1.3/8	12	—	041357 ¹⁾	—
	56		0.0465	1/2	1.3/8	12	—	041356 ¹⁾	—
	55		0.0520	5/8	1.5/8	12	—	041355 ¹⁾	—
	54		0.0550	5/8	1.5/8	12	—	041354 ¹⁾	—
	53		0.0595	5/8	1.5/8	12	—	041353 ¹⁾	—
1/16			0.0625	5/8	1.5/8	12	040304	—	—
	52		0.0635	11/16	1.11/16	12	—	041352	—
	51		0.0670	11/16	1.11/16	12	—	041351	—
	50		0.0700	11/16	1.11/16	12	—	041350	—
	49		0.0730	11/16	1.11/16	12	—	041349	—
	48		0.0760	11/16	1.11/16	12	—	041348	—
5/64			0.0781	11/16	1.11/16	12	040305	—	—
	47		0.0785	11/16	1.11/16	12	—	041347	—
	46		0.0810	3/4	1.3/4	12	—	041346	—
	45		0.0820	3/4	1.3/4	12	—	041345	—
	44		0.0860	3/4	1.3/4	12	—	041344	—
	43		0.0890	3/4	1.3/4	12	—	041343	—
	42		0.0935	3/4	1.3/4	12	—	041342	—
3/32			0.0938	3/4	1.3/4	12	040306	—	—
	41		0.0960	13/16	1.13/16	12	—	041341	—
	40		0.0980	13/16	1.13/16	12	—	041340	—
	39		0.0995	13/16	1.13/16	12	—	041339	—
	38		0.1015	13/16	1.13/16	12	—	041338	—
	37		0.1040	13/16	1.13/16	12	—	041337	—
	36		0.1065	13/16	1.13/16	12	—	041336	—
7/64			0.1094	13/16	1.13/16	12	040307	—	—
	35		0.1100	7/8	1.7/8	12	—	041335	—
	34		0.1110	7/8	1.7/8	12	—	041334	—
	33		0.1130	7/8	1.7/8	12	—	041333	—

¹⁾ Not Split Point

COBALT SCREW MACHINE DRILL



d ₁ Ø Inch	d ₁ Ø Nr.	d ₁ Ø letter	d ₁ decimal Inch	l ₂ Inch	l ₁ Inch	Pack Qty	M40CO	M41CO	M42CO
	32		0.1160	7/8	1.7/8	12	—	041332	—
	31		0.1200	7/8	1.7/8	12	—	041331	—
1/8			0.1250	7/8	1.7/8	12	040308	—	—
	30		0.1285	15/16	1.15/16	12	—	041330	—
	29		0.1360	15/16	1.15/16	12	—	041329	—
	28		0.1405	15/16	1.15/16	12	—	041328	—
9/64			0.1406	15/16	1.15/16	12	040309	—	—
	27		0.1440	1"	2.1/16	12	—	041327	—
	26		0.1470	1"	2.1/16	12	—	041326	—
	25		0.1495	1"	2.1/16	12	—	041325	—
	24		0.1520	1"	2.1/16	12	—	041324	—
	23		0.1540	1"	2.1/16	12	—	041323	—
5/32			0.1563	1"	2.1/16	12	040310	—	—
	22		0.1570	1.1/16	2.1/8	12	—	041322	—
	21		0.1590	1.1/16	2.1/8	12	—	041321	—
	20		0.1610	1.1/16	2.1/8	12	—	041320	—
	19		0.1660	1.1/16	2.1/8	12	—	041319	—
	18		0.1695	1.1/16	2.1/8	12	—	041318	—
11/64			0.1719	1.1/16	2.1/8	12	040311	—	—
	17		0.1730	1.1/8	2.3/16	12	—	041317	—
	16		0.1770	1.1/8	2.3/16	12	—	041316	—
	15		0.1800	1.1/8	2.3/16	12	—	041315	—
	14		0.1820	1.1/8	2.3/16	12	—	041314	—
	13		0.1850	1.1/8	2.3/16	12	—	041313	—
3/16			0.1875	1.1/8	2.3/16	12	040312	—	—
	12		0.1890	1.3/16	2.1/4	12	—	041312	—
	11		0.1910	1.3/16	2.1/4	12	—	041311	—
	10		0.1935	1.3/16	2.1/4	12	—	041310	—
	9		0.1960	1.3/16	2.1/4	12	—	041309	—
	8		0.1990	1.3/16	2.1/4	12	—	041308	—
	7		0.2010	1.3/16	2.1/4	12	—	041307	—
13/64			0.2031	1.3/16	2.1/4	12	040313	—	—
	6		0.2040	1.1/4	2.3/8	12	—	041306	—
	5		0.2055	1.1/4	2.3/8	12	—	041305	—
	4		0.2090	1.1/4	2.3/8	12	—	041304	—
	3		0.2130	1.1/4	2.3/8	12	—	041303	—
7/32			0.2188	1.1/4	2.3/8	12	040314	—	—
	2		0.2210	1.5/16	2.7/16	12	—	041302	—
	1		0.2280	1.5/16	2.7/16	12	—	041301	—
		A	0.2340	1.5/16	2.7/16	12	—	—	042301
15/64			0.2344	1.5/16	2.7/16	12	040315	—	—
		B	0.2380	1.3/8	2.1/2	12	—	—	042302
		C	0.2420	1.3/8	2.1/2	12	—	—	042303
		D	0.2460	1.3/8	2.1/2	12	—	—	042304
		E	0.2500	1.3/8	2.1/2	12	—	—	042305
1/4			0.2500	1.3/8	2.1/2	12	040316	—	—
		F	0.2570	1.7/16	2.5/8	12	—	—	042306
		G	0.2610	1.7/16	2.5/8	12	—	—	042307
17/64			0.2656	1.7/16	2.5/8	12	040317	—	—
		H	0.2660	1.1/2	2.11/16	12	—	—	042308
		I	0.2720	1.1/2	2.11/16	12	—	—	042309
		J	0.2770	1.1/2	2.11/16	12	—	—	042310
		K	0.2810	1.1/2	2.11/16	12	—	—	042311
9/32			0.2813	1.1/2	2.11/16	12	040318	—	—
		L	0.2900	1.9/16	2.3/4	12	—	—	042312
		M	0.2950	1.9/16	2.3/4	12	—	—	042313
19/64			0.2969	1.9/16	2.3/4	12	040319	—	—
		N	0.3020	1.5/8	2.13/16	12	—	—	042314
5/16			0.3125	1.5/8	2.13/16	6	040320	—	—
		O	0.3160	1.11/16	2.15/16	6	—	—	042315
		P	0.3230	1.11/16	2.15/16	6	—	—	042316
21/64			0.3281	1.11/16	2.15/16	6	040321	—	—
		Q	0.3320	1.11/16	3"	6	—	—	042317
		R	0.3390	1.11/16	3"	6	—	—	042318
11/32			0.3437	1.11/16	3"	6	040322	—	—
		S	0.3480	1.3/4	3.1/16	6	—	—	042319



COBALT SCREW MACHINE DRILL

d ₁ Ø Inch	d ₁ Ø Nr.	d ₁ Ø letter	d ₁ decimal Inch	l ₂ Inch	l ₁ Inch	Pack Qty	M40CO	M41CO	M42CO
		T	0.3580	1.3/4	3.1/16	6	—	—	042320
23/64			0.3594	1.3/4	3.1/16	6	040323	—	—
		U	0.3680	1.13/16	3.1/8	6	—	—	042321
3/8			0.3750	1.13/16	3.1/8	6	040324	—	—
		V	0.3770	1.7/8	3.1/4	6	—	—	042322
		W	0.3860	1.7/8	3.1/4	6	—	—	042323
25/64			0.3906	1.7/8	3.1/4	6	040325	—	—
		X	0.3970	1.15/16	3.5/16	6	—	—	042324
		Y	0.4040	1.15/16	3.5/16	6	—	—	042325
13/32			0.4063	1.15/16	3.5/16	6	040326	—	—
		Z	0.4130	2"	3.3/8	6	—	—	042326
27/64			0.4219	2"	3.3/8	6	040327	—	—
7/16			0.4375	2.1/16	3.7/16	6	040328	—	—
29/64			0.4531	2.1/8	3.9/16	6	040329	—	—
15/32			0.4687	2.1/8	3.5/8	6	040330	—	—
31/64			0.4844	2.3/16	3.11/16	6	040331	—	—
1/2			0.5000	2.1/4	3.3/4	6	040332	—	—
33/64			0.5156	2.3/8	3.7/8	1	046033	—	—
17/32			0.5313	2.3/8	3.7/8	1	046034	—	—
35/64			0.5469	2.1/2	4"	1	046035	—	—
9/16			0.5625	2.1/2	4"	1	046036	—	—
37/64			0.5781	2.5/8	4.1/8	1	046037	—	—
19/32			0.5937	2.5/8	4.1/8	1	046038	—	—
39/64			0.6094	2.3/4	4.1/4	1	046039	—	—
5/8			0.6250	2.3/4	4.1/4	1	046040	—	—
41/64			0.6406	2.7/8	4.1/2	1	046041	—	—
21/32			0.6563	2.7/8	4.1/2	1	046042	—	—
43/64			0.6719	2.7/8	4.5/8	1	046043	—	—
11/16			0.6875	2.7/8	4.5/8	1	046044	—	—
45/64			0.7031	3"	4.3/4	1	046045	—	—
23/32			0.7188	3"	4.3/4	1	046046	—	—
47/64			0.7344	3.1/8	5"	1	046047	—	—
3/4			0.7500	3.1/8	5"	1	046048	—	—