

# General Purpose Reduced Shank Drill - 1/2" Shank

## Style R56

**How To Use This Chart:**

1. Determine your Workpiece Material from the Application Material Groups (AMG) below.
2. Use the Icons to find Product Features.
3. Find the Surface Feet Per Minute (SFM) and Alpha Code  
 example: 361W  
 361 = SFM  
 W = Alpha Code used to find your Feed Rate

	HSS
	ANSI
	4XD
	118°
	ST
	<b>R56</b>
	33/64 - 1.1/2
	<b>174</b>
1.1	115H
1.2	98H
1.3	82F
1.4	66E
1.5	43D
1.6	30C
1.7	
1.8	
2.1	49D
2.2	23F
2.3	23B
2.4	
3.1	89H
3.2	72E
3.3	62D
3.4	39D
4.1	56E
4.2	30C
4.3	16A
5.1	26F
5.2	13D
5.3	10A
6.1	115F
6.2	108H
6.3	89G
6.4	52F
7.1	108I
7.2	98H
7.3	89G
7.4	72G
8.1	98I
8.2	92G
8.3	46E
9.1	10A
10.1	

## Feed Rate Chart

Alpha Code	Feed in Inches per Revolution (IPR) ± 25%															Ø Diameter				
	1mm/ 1/32"	2mm/ 3/32"	3mm/ 1/8"	4mm/ 5/32"	5mm/ 3/16"	6mm/ 1/4"	8mm/ 5/16"	10mm/ 3/8"	12mm/ 1/2"	15mm/ 9/16"	16mm/ 5/8"	20mm/ 3/4"	25mm/ 1"	30mm/ 1.1/8"	40mm/ 1.5/8"	50mm/ 2"				
A	0.0004	0.0009	0.0011	0.0013	0.0014	0.0017	0.0021	0.0024	0.0027	0.0032	0.0034	0.0043	0.0049	0.0053	0.0061	0.0069				
B	0.0006	0.0011	0.0015	0.0016	0.0018	0.0021	0.0026	0.0031	0.0035	0.0041	0.0043	0.0053	0.0060	0.0065	0.0074	0.0082				
C	0.0006	0.0013	0.0017	0.0020	0.0022	0.0025	0.0031	0.0039	0.0043	0.0049	0.0051	0.0063	0.0071	0.0077	0.0087	0.0094				
D	0.0006	0.0015	0.0021	0.0024	0.0027	0.0031	0.0039	0.0047	0.0051	0.0059	0.0061	0.0074	0.0083	0.0090	0.0100	0.0108				
E	0.0007	0.0017	0.0024	0.0028	0.0031	0.0037	0.0045	0.0055	0.0059	0.0068	0.0071	0.0085	0.0094	0.0102	0.0112	0.0122				
F	0.0007	0.0020	0.0029	0.0033	0.0037	0.0043	0.0054	0.0065	0.0070	0.0080	0.0083	0.0098	0.0108	0.0116	0.0126	0.0135				
G	0.0007	0.0022	0.0033	0.0038	0.0043	0.0050	0.0063	0.0075	0.0081	0.0091	0.0094	0.0110	0.0122	0.0130	0.0140	0.0148				
H	0.0008	0.0026	0.0040	0.0046	0.0051	0.0059	0.0075	0.0090	0.0096	0.0107	0.0110	0.0126	0.0140	0.0148	0.0157	0.0165				
I	0.0008	0.0030	0.0047	0.0053	0.0059	0.0068	0.0087	0.0104	0.0110	0.0122	0.0126	0.0142	0.0157	0.0165	0.0173	0.0181				
J	0.0009	0.0033	0.0053	0.0060	0.0067	0.0078	0.0098	0.0117	0.0124	0.0137	0.0142	0.0159	0.0175	0.0183	0.0191	0.0198				
K	0.0010	0.0036	0.0059	0.0067	0.0075	0.0087	0.0110	0.0130	0.0138	0.0153	0.0157	0.0177	0.0193	0.0201	0.0209	0.0215				
L	0.0011	0.0040	0.0065	0.0073	0.0082	0.0094	0.0120	0.0142	0.0152	0.0165	0.0169	0.0191	0.0207	0.0215	0.0224	0.0231				
M	0.0012	0.0043	0.0071	0.0080	0.0089	0.0102	0.0130	0.0154	0.0165	0.0177	0.0181	0.0205	0.0220	0.0228	0.0238	0.0248				
N	0.0013	0.0047	0.0077	0.0086	0.0095	0.0110	0.0140	0.0165	0.0179	0.0189	0.0193	0.0219	0.0234	0.0242	0.0253	0.0265				
S	0.0003	0.0006	0.0008	0.0010	0.0012	0.0015	0.0020	0.0031	0.0039	0.0048	0.0051	0.0059	0.0070	0.0070	0.0090					
T	0.0006	0.0011	0.0016	0.0020	0.0024	0.0028	0.0035	0.0043	0.0051	0.0063	0.0067	0.0075	0.0080	0.0090	0.0100					
U	0.0010	0.0019	0.0028	0.0031	0.0035	0.0042	0.0055	0.0067	0.0079	0.0088	0.0091	0.0094	0.0110	0.0120	0.0140					
V	0.0015	0.0027	0.0039	0.0045	0.0051	0.0060	0.0079	0.0098	0.0110	0.0122	0.0126	0.0134	0.0160	0.0170	0.0200					
W	0.0019	0.0035	0.0051	0.0059	0.0067	0.0079	0.0102	0.0130	0.0150	0.0165	0.0169	0.0177	0.0190	0.0190	0.0200					
X	0.0022	0.0041	0.0059	0.0071	0.0083	0.0098	0.0130	0.0165	0.0189	0.0210	0.0217	0.0228								
Y	0.0027	0.0049	0.0071	0.0087	0.0102	0.0125	0.0169	0.0217	0.0276	0.0276	0.0276	0.0291								
Z	0.0037	0.0068	0.0098	0.0128	0.0157	0.0210	0.0315	0.0394	0.0433	0.0463	0.0472	0.0472								

### How To Use This Chart to Find Cutting Feed Rate (IPR):

1. Find your Alpha Code on the AMG Chart (example: 279 U : U is the Alpha Code)
2. Find the closest diameter for your cutting application on the chart to find your IPR

Application Material Groups (AMG)		Hardness HRC	ISO
1. Steel	1.1 Magnetic soft steel	12L14, 12L15	<120 HB P 1
	1.2 Structural Steel/ case carburising steel	1005-1025, 1214, 1215, A36	<200 HB P 1
	1.3 Plain Carbon steel	1030-1060, 1050-1060, 1144-1146	<24 P 2
	1.4 Alloy steel	4140,4340,52100,8620 H11-H41,A2,D2,01,P20,420	<24 P 3
	1.5 Alloy steel/ Hardened and tempered steel	4140,4340,52100,8620 H11-H41,A2,D2,01,P20,420	>24<38 P 4
	1.6 Alloy steel/ Hardened and tempered steel	4140,4340,52100,8620 H11-H41,A2,D2,01,P20,420	>38 H 1
	1.7 Alloy steel Hardened	A2-D2, H10-H41, L1-L6, M1-M42, T1	49-55 H 3
	1.8 Alloy steel Hardened	A2-D2, H10-H41, L1-L6, M1-M42, T1	55-63 H 4
2. Stainless Steel	2.1 Free machining Stainless Steel	200, 303, 416, 420F, 430F, 440	<24 M 1
	2.2 Austenitic	301, 302, 304, 316, 321, 330, CUSTOM 455, AM-350	<24 M 3
	2.3 Ferritic + Austenitic, Martensitic	318-329, 400-446, DUPLEX	<32 M 2
	2.4 Precipitation Hardened	15-5PH, Custom 450 17-4PH	<32 S 2
3. Cast Iron	3.1 Lamellar graphite	Grey, G10, Gg40, J431C, A48 CLASS 20	<150 HB K 1
	3.2 Lamellar graphite	Grey, GG25-Gg40, J158, A48 CLASS 40-60	>150 HB<32 K 2
	3.3 Nodular graphite/ Malleable Cast Iron	A220, A436, A439, A602, Black, GGG40-GGG70	<200 HB K 3
	3.4 Nodular graphite/ Malleable Cast Iron	Black Gts/Gtw, J434C	>200 HB<32 K 4
4. Titanium	4.1 Titanium, unalloyed	Commercially Pure	<200 HB S 1
	4.2 Titanium, alloyed	6Al4V, 6A14V-2Sn, Monel, Monel K	<28 S 2
	4.3 Titanium, alloyed	6Al4V-4Mo, 7A14V-4Mo, 4911-4967	>28<38 S 3
5. Nickel	5.1 Nickel, unalloyed	Commercially Pure, 17644, 200, 5553	<150 HB S 1
	5.2 Nickel, alloyed	Monel 400, Hastelloy C, Inconel 625, Waspaloy	<28 S 2
	5.3 Nickel, alloyed	Inconel 718, Nimonic 75-95, Rene 41, Inconel 825, A286	>28<38 S 3
6. Copper	6.1 Copper	Commercially Pure	<100 HB N 3
	6.2 β-Brass, Bronze	314-340, 350-370	<200 HB N 4
	6.3 α-Brass	Alloyed Cu + Al + Fe, Long Chipping	<200 HB N 3
	6.4 High Strength Bronze	Ampco 18-25	<49 N 4
7. Aluminium Magnesium	7.1 Al, Mg, unalloyed	Commercially Pure	<100 HB N 1
	7.2 Al alloyed, Si<0.5%	6061 T6, 7075, 314-340	<150 HB N 1
	7.3 Al alloyed, Si>0.5%<10%	6061 T6, 380-390	<120 HB N 1
	7.4 Al alloyed, Si>10% Mg alloys	Magnesium Whisker Reinforced	<120 HB N 2
8. Synthetic Materials	8.1 Thermoplastics	Ultradim, Polystrol	---
	8.2 Thermosetting plastics	Bakelit, Pertinax	---
	8.3 Reinforced plastic materials	CFK, GFKAFK	---
9. Hard Mat.	9.1 Cermets (Metal-ceramics)	Ferrotic	<54 H
10. Graphite	10.1 Standard graphite		---

# REDUCED SHANK DRILL



## General Purpose Reduced Shank - 1/2" Shank

**R56** Silver & Deming Drills. Steam Oxide for increased wear resistance & lubricity.

R56

ANSI

4XD

HSS

118°



33/64 - 1.1/2



d <sub>1</sub> Ø Inch	d <sub>1</sub> decimal Inch	l <sub>2</sub> Inch	l <sub>1</sub> Inch	d <sub>2</sub> Ø Inch	Pack Qty	R56
33/64	0.5156	3"	6"	1/2	1	091433
17/32	0.5313	3"	6"	1/2	1	091434
35/64	0.5469	3"	6"	1/2	1	091435
9/16	0.5625	3"	6"	1/2	1	091436
37/64	0.5781	3"	6"	1/2	1	091437
19/32	0.5937	3"	6"	1/2	1	091438
39/64	0.6094	3"	6"	1/2	1	091439
5/8	0.6250	3"	6"	1/2	1	091440
41/64	0.6406	3"	6"	1/2	1	091441
21/32	0.6563	3"	6"	1/2	1	091442
43/64	0.6719	3"	6"	1/2	1	091443
11/16	0.6875	3"	6"	1/2	1	091444
45/64	0.7031	3"	6"	1/2	1	091445
23/32	0.7188	3"	6"	1/2	1	091446
47/64	0.7344	3"	6"	1/2	1	091447
3/4	0.7500	3"	6"	1/2	1	091448
49/64	0.7656	3"	6"	1/2	1	091449
25/32	0.7813	3"	6"	1/2	1	091450
51/64	0.7969	3"	6"	1/2	1	091451
13/16	0.8125	3"	6"	1/2	1	091452
53/64	0.8281	3"	6"	1/2	1	091453
27/32	0.8438	3"	6"	1/2	1	091454
55/64	0.8594	3"	6"	1/2	1	091455
7/8	0.8750	3"	6"	1/2	1	091456
57/64	0.8906	3"	6"	1/2	1	091457
29/32	0.9063	3"	6"	1/2	1	091458
59/64	0.9219	3"	6"	1/2	1	091459
15/16	0.9375	3"	6"	1/2	1	091460
61/64	0.9531	3"	6"	1/2	1	091461
31/32	0.9688	3"	6"	1/2	1	091462
63/64	0.9844	3"	6"	1/2	1	091463
1"	1.0000	3"	6"	1/2	1	091464
1.1/64	1.0156	3"	6"	1/2	1	091465



# REDUCED SHANK DRILL

$d_1$ Ø Inch	$d_1$ decimal Inch	$l_2$ Inch	$l_1$ Inch	$d_2$ Ø Inch	Pack Qty	R56
1.1/32	1.0312	3"	6"	1/2	1	091486
1.3/64	1.0469	3"	6"	1/2	1	091467
1.1/16	1.0625	3"	6"	1/2	1	091468
1.5/64	1.0781	3"	6"	1/2	1	091469
1.3/32	1.0937	3"	6"	1/2	1	091470
1.7/64	1.1094	3"	6"	1/2	1	091471
1.1/8	1.1250	3"	6"	1/2	1	091472
1.9/64	1.1406	3"	6"	1/2	1	091473
1.5/32	1.1563	3"	6"	1/2	1	091487
1.11/64	1.1719	3"	6"	1/2	1	091474
1.3/16	1.1875	3"	6"	1/2	1	091476
1.13/64	1.2031	3"	6"	1/2	1	091475
1.7/32	1.2187	3"	6"	1/2	1	091488
1.15/64	1.2344	3"	6"	1/2	1	091477
1.1/4	1.2500	3"	6"	1/2	1	091480
1.9/32	1.2813	3"	6"	1/2	1	091479
1.5/16	1.3125	3"	6"	1/2	1	091482
1.11/32	1.3437	3"	6"	1/2	1	091497
1.3/8	1.3750	3"	6"	1/2	1	091483
1.13/32	1.4063	3"	6"	1/2	1	091492
1.7/16	1.4375	3"	6"	1/2	1	091484
1.15/32	1.4687	3"	6"	1/2	1	091495
1.1/2	1.5000	3"	6"	1/2	1	091485