

Pliers, Snips, Clamps & Eye Bolts



C-CLAMPS - HEAVY SERVICE STANDARD SCREW

- Designed for heavy service applications where the strength of the extra heavy service C-clamp is not required.
- Clamps have a high strength steel frame with a hardened forcing screw.
- Forcing screws are fitted with impact resistant pads.

Product ID No.	C	T	D	Min. Test Load Pounds	Weight lbs.
J102GS	0" - 2"	1-3/8"	1/2"	7,500	1.3
J103GS	0"-3"	1-3/4"	5/8"	8,750	2.6
J104GS	0"-4-1/8"	2"	3/4"	10,000	4.1
J106GS	2"-6"	2-1/4"	3/4"	11,250	5.9
J108GS	4"-8"	2-1/4"	3/4"	12,500	6.9
J110GS	6"-10-1/4"	2-3/8"	3/4"	13,750	8.0
J112GS	8"-12"	2-5/8"	7/8"	15,000	11.6
J115GS	10"-15"	2-1/2"	7/8"	16,250	15.0
J118GS	12"-18"	2-7/8"	7/8"	17,500	18.2



C-CLAMPS - STANDARD SERVICE DEEP THROAT FULL LENGTH SCREW

- Standard service, deep throat style is the most versatile and popular.
- Hot forged for strength and hard use.
- Forcing screw has heavy rolled Acme thread allowing the screw to turn easily under pressure and is less susceptible to damage.
- Forcing screw has a sliding T handle and an impact resistant pad.

Product ID No.	C	T	D	Min. Test Load Pounds	Weight lbs.
J402	0"-2"	2"	1/2"	3,500	1.3
J403	1/2"	2-3/8"	1/2"	3,500	2.0
J404	3/4"	2-3/4"	3/4"	6,500	3.5
J406	3/4"	3-5/8"	3/4"	6,600	5.0
J408	3/4"	4-1/2"	3/4"	6,900	7.0
J410	3/4"	5-3/8"	3/4"	8,000	10.5
J412	7/8"	5-3/4"	7/8"	9,500	15.5

