



PYRAMEX
Perform At Your Peak

Venture II® ANSI CE CSA BALLISTIC



RUBBER NOSEPIECE



ADJUSTABLE TEMPLES

Temples adjust to four different lengths

Nosepiece secures the glass and prevents slipping

Passes MIL-PRF 32432 High Velocity Impact Standards



Part No.	Black Frame
SB1810S ●●●●	Clear
SB1810ST ●●●●	AF Clear H2X
SB1820S ●●●●	Gray
SB1820ST ●●●●	AF Gray H2X
SB1830S ●●●●	Amber
SB1835S ●●●●	Sun Block Bronze
SB1840S ●●●●	Orange
SB1850SF ●●●●	5.0 IR Filter
SB1860S ●●●●	Infinity Blue
SB1860SF ●●●●	3.0 IR Filter
SB1870S ●●●●	Silver Mirror
SB1875S ●●●●	Blue Mirror
SB1880S ●●●●	I/O Mirror
SB1880ST ●●●●	AF I/O Mirror
SB1890S ●●●●	Gold Mirror

Part No.	Realtree Hardwoods HD® Frame
SH1810S ●●	Clear
SH1820S ●●	Gray
SH1830S ●●	Amber

Part No.	Metallic Blue Frame
SMB1810S ●●●●	Clear
SMB1820S ●●●●	Gray
SMB1880S ●●●●	I/O Mirror



Part No.	Maroon Frame
SMM1810S ●●●●	Clear



Part No.	Slate Gray Frame
SSG1810S ●●	Clear

Venture II Readers ANSI CE CSA



RUBBER NOSEPIECE



ADJUSTABLE TEMPLES



Part No.	Black Frame
SB1810R10 ●●●●	Clear +1.0 Mag
SB1810R15 ●●●●	Clear +1.5 Mag
SB1810R15T ●●●●	AF Clear H2X +1.5 Mag
SB1810R20 ●●●●	Clear +2.0 Mag
SB1810R20T ●●●●	AF Clear H2X +2.0 Mag
SB1810R25 ●●●●	Clear +2.5 Mag
SB1810R25T ●●●●	AF Clear H2X +2.5 Mag
SB1810R30 ●●●●	Clear +3.0 Mag

Part No.	Black Frame
SB1820R15 ●●	Gray +1.5 Mag
SB1820R20 ●●	Gray +2.0 Mag
SB1820R25 ●●	Gray +2.5 Mag
SB1820R30 ●●	Gray +3.0 Mag
SB1830R15 ●●	Amber +1.5 Mag
SB1830R20 ●●	Amber +2.0 Mag
SB1830R25 ●●	Amber +2.5 Mag
SB1880R15 ●●	I/O Mirror +1.5 Mag
SB1880R20 ●●	I/O Mirror +2.0 Mag
SB1880R25 ●●	I/O Mirror +2.5 Mag

There's more to see at
PYRAMEXSAFETY.COM

(P) 800.736.8673 | (F) 901.861.4967

All safety eyewear meets ANSI Z87.1+ standards (●) and provide 99% protection from harmful UV rays. All lenses are hard coated polycarbonate scratch-resistant unless otherwise noted. Some options meet European (EN166) (●), Canadian (CSA Z94.3) (●) or Ballistic (MIL-PRF-32432) (●) standards.



Venture II®

General Specifications

Weight: 27 gm
 PD: 68 mm
 Bridge: 10.5 mm
 Lens base: 9.75 curve
 Lens size diagonal: 56 mm
 Lens size vertical: 45 mm
 Lens thickness: 2.2 mm
 Overall length (lens - tip): 150 - 163 mm
 Overall width (hinge - hinge): 142 mm

Materials

Lens: polycarbonate (PC)
 Frame: polyhexamethylene adipitimide (nylon 6/6)
 Hinge: polycarbonate (PC) & nylon
 Screw: stainless steel
 Side shields: polycarbonate (PC)
 Nosepiece: polycarbonate (PC) & thermoplastic rubbers (TPR)

Part No.	Lens Markings	Frame Markings
SB1810S	P + U6	P Z87 + / P c SEI CAN/CSA Z94.3-15
SB1810ST	P + U6	P Z87 + / P c SEI CAN/CSA Z94.3-15
SB1820S	P + U6 L2.5	P Z87 + / P c SEI CAN/CSA Z94.3-15
SB1820ST	P + U6 L2.5	P Z87 + / P c SEI CAN/CSA Z94.3-15
SB1830S	P + U6	P Z87 + / P c SEI CAN/CSA Z94.3-15
SB1835S	P + S	P Z87 + / P c SEI CAN/CSA Z94.3-15
SB1840S	P + S	P Z87 + / P c SEI CAN/CSA Z94.3-15
SB1850SF	P + W 5	P Z87 +
SB1860S	P + S	P Z87 + / P c SEI CAN/CSA Z94.3-15
SB1860SF	P + W 3	P Z87 +
SB1870S	P + S	P Z87 + / P c SEI CAN/CSA Z94.3-15
SB1875S	P + S	P Z87 + / P c SEI CAN/CSA Z94.3-15
SB1880S	P + U6 L1.7	P Z87 + / P c SEI CAN/CSA Z94.3-15
SB1880ST	P + U6 L1.7	P Z87 + / P c SEI CAN/CSA Z94.3-15
SB1890S	P + S	P Z87 + / P c SEI CAN/CSA Z94.3-15
SH1810S	P + U6	P Z87 +
SH1820S	P + U6 L2.5	P Z87 +
SH1830S	P + U6	P Z87 +
SMB1810S	P + U6	P Z87 +
SMB1820S	P + U6 L2.5	P Z87 +
SMB1880S	P + U6	P Z87 +
SMM1810S	P + U6	P Z87 +
SSG1810S	P + U6	P Z87 +

Lens Marking Symbols

P: Manufacturer's mark
 +: High impact
 W: Welding filter
 S: Special purpose
 UV Filter Transmittance
 U6: .01% max effective far UV • .1% max near UV
 Visible Light Filters
 L1.7: 55% max visible light
 L2.5: 29% max visible light

Frame Marking Symbols

P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 +: High impact
 c SEI CAN/CSA Z94.3-15: CAN/CSA standard for eye and face protection devices

Venture II Readers

General Specifications

Weight: 27 gm
 PD: 68 mm
 Bridge: 10.5 mm
 Lens base: 9.75 curve
 Lens size diagonal: 56 mm
 Lens size vertical: 45 mm
 Lens thickness: 2.2 mm
 Overall length (lens - tip): 150 - 163 mm
 Overall width (hinge - hinge): 142 mm

Materials

Lens: polycarbonate (PC)
 Frame: polyhexamethylene adipitimide (nylon 6/6)
 Hinge: polycarbonate (PC) & nylon
 Screw: stainless steel
 Side shields: polycarbonate (PC)
 Nosepiece: polycarbonate (PC) & thermoplastic rubbers (TPR)

Part No.	Lens Markings	Frame Markings
SB1810R10	P + U6	+1.00 P Z87 - 2+ / P c SEI CAN/CSA Z94.3-15
SB1810R15	P + U6	+1.50 P Z87 - 2+ / P c SEI CAN/CSA Z94.3-15
SB1810R15T	P + U6	+1.50 P Z87 - 2+ / P c SEI CAN/CSA Z94.3-15
SB1810R20	P + U6	+2.00 P Z87 - 2+ / P c SEI CAN/CSA Z94.3-15
SB1810R20T	P + U6	+2.00 P Z87 - 2+ / P c SEI CAN/CSA Z94.3-15
SB1810R25	P + U6	+2.50 P Z87 - 2+ / P c SEI CAN/CSA Z94.3-15
SB1810R25T	P + U6	+2.50 P Z87 - 2+ / P c SEI CAN/CSA Z94.3-15
SB1810R30	P + U6	+3.00 P Z87 - 2+ / P c SEI CAN/CSA Z94.3-15
SB1820R15	P + U6 L2.5	+1.50 P Z87 - 2+ / P c SEI CAN/CSA Z94.3-15
SB1820R20	P + U6 L2.5	+2.00 P Z87 - 2+ / P c SEI CAN/CSA Z94.3-15
SB1820R25	P + U6 L2.5	+2.50 P Z87 - 2+ / P c SEI CAN/CSA Z94.3-15
SB1820R30	P + U6 L2.5	+3.00 P Z87 - 2+ / P c SEI CAN/CSA Z94.3-15
SB1830R15	P + U6	+1.50 P Z87 - 2+
SB1830R20	P + U6	+2.00 P Z87 - 2+
SB1830R25	P + U6	+2.50 P Z87 - 2+
SB1880R15	P + U6 L1.7	+1.50 P Z87 - 2+ / P c SEI CAN/CSA Z94.3-15
SB1880R20	P + U6 L1.7	+2.00 P Z87 - 2+ / P c SEI CAN/CSA Z94.3-15
SB1880R25	P + U6 L1.7	+2.50 P Z87 - 2+ / P c SEI CAN/CSA Z94.3-15

Lens Marking Symbols

P: Manufacturer's mark
 +: High impact
 W: Welding filter
 S: Special purpose
 UV Filter Transmittance
 U6: .01% max effective far UV • .1% max near UV
 Visible Light Filters
 L1.7: 55% max visible light
 L2.5: 29% max visible light

Frame Marking Symbols

+1.00: magnification of +1.0
 +1.50: magnification of +1.5
 +2.00: magnification of +2.0
 +2.50: magnification of +2.5
 +3.00: magnification of +3.0
 P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 - 2: Rx
 +: High impact
 c SEI CAN/CSA Z94.3-15: CAN/CSA standard for eye and face protection devices