



# Red Devil

## TECHNICAL DATA SHEET

### SPEED DEMON®

#### ACRYLIC LATEX CAULK

#### DESCRIPTION

An economical general-purpose acrylic latex caulk designed for limited joint movement applications.

#### SURFACE PREPARATION

Surface must be clean, dry & free from dirt, dust, grease, oil, mildew, wax, loose paint, frost & old caulking. Prime bare surfaces before caulking for best results.

PART #	PACKAGE	COLOR	UPC
0736	10.1 oz (300 ml) Cartridge	White	075339007365

#### DIRECTIONS

1. Remove old caulking.
2. Clean and dry surface.
3. Clip off tip of nozzle/spout @ 45° angle to desired size.
4. Load cartridge into caulking gun and apply.
5. Smooth caulk using Red Devil Caulk Smoother, Putty Knife, or Damp Cloth before surface skins over.
6. Wait 2 hours before painting with latex paint or 24 hours with and oil-based paint.
7. Protect from water until cured (72 hours).

#### KEY FEATURES

- Water clean-up
- Easy application & tooling
- Odorless
- Paintable
- Interior/Exterior
- VOC compliant

#### FOR BEST RESULTS

- Joint size should not exceed 3/8". If joint depth exceeds 3/8", use a backer rod.
- Prime bare surfaces before caulking.
- Store at temperatures above freezing and below 90F.
- Do not overtool.

#### USES

Formulated for use around interior windows, doors, trim, baseboards, and molding.

#### CLEAN UP

Mild Soap and Water.

#### LIMITATIONS

- Not recommended for underwater applications
- Not Recommended for use on fish tanks/aquariums
- Not recommended for use on mirrors
- Protect from rain/water exposure for 72 hours
- Apply only to clean, dry substrates

CRITERIA	STATUS
CARB Compliance	Yes
Prop 65 Ingredients	Yes (See MSDS)
DOT Proper Shipping Name	Not Regulated by DOT
DOT Hazard	None
DOT UN/NA Number	None
Packing Group	None
VOC Content	< 1.5% by weight, < 25 g/L

#### LIMITED WARRANTY

Recommendations for use of this product are based on tests we believe to be reliable. Manufacturer and seller are not responsible for results where this product is used under conditions beyond our control. If when applied as directed, this material peels, cracks or separates, it will be replaced without charge upon presentation of proof of purchase and used cartridge. This limited warranty only applies to residential use and damages including consequential damage and other remedies are excluded. No other warranties apply, including fitness for a particular purpose.



# Red Devil

## TECHNICAL DATA SHEET

### SPEED DEMON® ACRYLIC LATEX CAULK

PHYSICAL/PERFORMANCE PROPERTY	TEST METHOD	TYPICAL RESULT
Weight Per Gallon	Gardner Cup	13.5 +/- 1.50
Specific Gravity	Calculated	Approx. 1.40 to 1.80
Total Non Volatile % Solids (Weight)	Computrac Analyzer	> 78% +/- 2%
Extrudability/Application	Brookfield Viscometer	300,000 to 400,000 cPs
Consistency/Appearance	Visual Observation	Smooth, Creamy Paste
pH (initial)	pH Meter	7 to 10
Odor	Subjective	Mild
Base Polymer	Known	Aqueous Emulsion
Filler/Pigment	Known	Calcium Carbonate
Flash Point	Closed Cup	Non-Flammable; >200F
Freeze/Thaw Stability	Test Lab 0F/77F @ 24 hrs or ASTM C731	Pass 3 Cycles
Shelf Life	Lab 50 C Oven – Accelerated	Expect 1 Yr @ 72F
Tack Free Time	Test Lab	< 1 hr @ 72F
Full Cure	Test Lab	72 Hours
Storage Conditions	Test Lab	40F to 90F (5C to 32C)
Application Temperature	Test Lab	40F to 90F (5C to 32C)
Tooling	Test Lab/Field Evaluation	Excellent
% Elongation	Test Lab	200%
Service Temperature	Test Lab	0F to 160F (-18C to 71C)
Coverage	Test Lab	50 – 55 Linear Feet (3/16” Bead)

**CAUTION: NOT FOR INTERNAL CONSUMPTION. KEEP OUT OF REACH OF CHILDREN & PETS. KEEP FROM FREEZING (See SDS for additional safety information)**

**⚠ WARNING: Cancer Risk From Formaldehyde Exposure -[www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)**

### **LIMITED WARRANTY**

Recommendations for use of this product are based on tests we believe to be reliable. Manufacturer and seller are not responsible for results where this product is used under conditions beyond our control. If when applied as directed, this material peels, cracks or separates, it will be replaced without charge upon presentation of proof of purchase and used cartridge. This limited warranty only applies to residential use and damages including consequential damage and other remedies are excluded. No other warranties apply, including fitness for a particular purpose.