SIOUX TOOLS FORCE PRODUCT CATALOG | SPECIALTY





Specialty Index

| Reciprocating Air Saw. | | | | | | | | . 33 |
|------------------------|--|--|--|--|--|--|--|------|
| Air Engraving Pen | | | | | | | | . 33 |
| Cut-off Tool | | | | | | | | . 33 |

Special Applications Require Special Tools

Sioux Tools has a history of designing specialty tools for very specific applications, and as always, we manufacture the finest tools in the industry. These tools will live up to your expectations in both power and ergonomics.

Reciprocating Saw

Operating at 10,000 strokes per minute, this powerful saw features an adjustable blade guard, lock-off lever throttle and a built-in speed regulator.

Cut-off Tool

We designed our cut-off tool to operate with a free speed of 21,000 and a lock-off lever throttle. The lightweight aluminum housing and rear exhaust make it very comfortable to operate.

Selection

If your application requires routers, tappers or metalworking tools like nibblers, check out the extensive line of Sioux Industrial Tools for a complete listing.

RECIPROCATING AIR SAW AIR ENGRAVING PEN CUT-OFF TOOL



Reciprocating Air Saw

Model No. 5300A

- Comfort Grip Handle
- 10,000 strokes per minute
- Adjustable Blade Guard
- Lockoff lever throttle
- Built-in speed regulator
- Weight 1.8 lbs. (0.8 kg)
- Length: 9.2" (235 mm)
- Air inlet size: 1/4" NPT
- Recommended hose size: 5/16" (8 mm)



Cut-off Tool

Model No. 5564A

- Rear exhaust
- Comfort Grip
- · Lockoff lever throttle
- Aluminum housing
- Free speed: 21,000 rpm
- Blade Diameter: 3" (76 mm)
- Weight: 1.8 lb (0.08 kg)
- Length: 8" (203 mm) • Air inlet size: 1/4" NPT
- Recommended hose size: 3/8" (10 mm)
- 3/8" Arbor



Bi-Metal Saw Blade (5 Pack)

| Part Number | Description | Length |
|-------------|-------------------------|------------|
| 1823 | Bi-Metal Blade - 18 TPI | 4" (100mm) |
| 1824B | Bi-Metal Blade - 24 TPI | 4" (100mm) |
| 1825 | Bi-Metal Blade - 32 TPI | 4" (100mm) |



Air Engraving Pen

Model No. 5980

- 13,000 cycles per minute
- · Replaceable carbide tipped points
- Twist throttle
- 59" (1500 mm) hose
 1/4" NPT air fitting
- High quality stainless steel housing
- Replaceable engraving points
 - 506246 45° (STD) 506245 30°

 - 506244 15°

