



# FLEX HEAD MICROMETER ROUND HEAD TORQUE WRENCHES



- › Flex head to 17+ degrees each direction.
- › Certificate of calibration.
- › Adjustable settings with both ft. lb. and N.m scales.
- › Automated calibration with +-4% clockwise and +-6% counter clockwise accuracy.
- › Reversible 72 teeth ratcheting mechanism.
- › Sleek industrial design of both torque wrench and blow molded case.



J6012FC



J6014FC



| PRODUCT # | DRIVE SIZE | RANGE         | HEAD WIDTH | HEAD DEPTH | OVERALL LENGTH | WEIGHT      |
|-----------|------------|---------------|------------|------------|----------------|-------------|
| J6012FC   | 3/8"       | 10-100 ft.lbs | 1-37/64"   | 1-23/64"   | 16-11/16"      | 2-1/2 lbs   |
| J6014FC   | 1/2"       | 30-250 ft.lbs | 1-21/32"   | 1-5/8"     | 25-13/32"      | 3-25/32 lbs |

Proto® Torque Wrench Repair • 6115-C Jimmy Carter Blvd • Norcross, GA 30071

MKT-2598  
ICJ601214FCSS



WARNING: WORK SAFELY WITH TOOLS. WEAR SAFETY GOGGLES.

©2016 Proto Industrial Tools · 1.800.800.TOOL · Fax: 1.800.828.7809 · protoindustrial.com