



**DuraScrim™ Jacket**

**Stock Number - J56107**



**Compliance Standards:** Flame resistant. Self extinguishing with flameout and afterglow less than or equal to 2 seconds after removal of ignition source and char length of less than 6 inches. Test Method ASTM D6413.

**Garment Detail:**

The jacket has batwing sleeve construction with a 90 degree sleeve-to-body angle, a storm fly front with snap closure, and an attached hood.

**Garment Type:** Designed to meet the protection and safety needs of customers who require durable self-extinguishing rainwear.

**Sizes:** S, M, L, XL, 2X, 3X, 4X, 5X

**Color:** Yellow

**Material:** Yellow material is 8 oz./yd<sup>2</sup> PVC on Polyester Scrim.

**Seam Construction:** All seams are RF/heat sealed and 100% waterproof.

**Labels/Tags:**

Label sealed to inside collar displays Tingley logo, size, Flame Resistance and country of origin. Care instructions, fabric composition, lot and date codes are located on the reverse.

**Closure Type:** Snap closure with 4 snaps and storm fly with 1 additional snap.

**Packaging:** Printed polyethylene bag.

**Pockets:**

**Other:** Mildew Resistant.

Dimensions	S	M	L	XL	2X	3X	4X	5X
<b>Chest</b>	45"	49"	53"	57"	61"	65"	69"	73"
<b>Length</b>	29"	30"	31"	31"	32"	32"	32"	33"
<b>Sleeve Length</b>	33.5"	34"	35"	35.5"	36"	36.5"	37"	37.5"

**Case Pack:** 12 each

**Case Dimensions/Weight**

S = 15"(L) X 13"(W) X 9"(H) / 22 lbs.	2X = 15"(L) X 13"(W) X 9"(H) / 28 lbs.
M = 15"(L) X 13"(W) X 9"(H) / 24 lbs.	3X = 15"(L) X 13"(W) X 9"(H) / 29 lbs.
L = 15"(L) X 13"(W) X 9"(H) / 26 lbs.	4X = 15"(L) X 13"(W) X 9"(H) / 31 lbs.
XL = 15"(L) X 13"(W) X 9"(H) / 27 lbs.	5X = 15"(L) X 13"(W) X 9"(H) / 32 lbs.

DuraScrim™ is a trademark of Tingley Rubber Corp.