



TOOLS @ HEIGHT
DROP PREVENTION SYSTEM

Side hole in socket permits use with Snap-on Industrial Brands Tools@Height drive tools such as ratchets, extensions and u-joints



6M-1250



6M-1219

3/4" DRIVE SHALLOW IMPACT SOCKETS, 12 POINT, METRIC

Black Industrial Finish

Product Code	Size (MM)	A		B		C		D		E		F		Uses RET RING® Number	Use O-Ring / Pin
		OAL (Inches)	Drive End Diameter (Inches)	Working End Diameter (Inches)	Broach Depth (Inches)	Bolt Clearance Diameter (Inches)	Bolt Clearance Depth (Inches)	Bolt Clearance Diameter (Inches)	Nose Length (Inches)						
6M-1219	19	2	1 5/8	1 1/4	1/2	1	3/8	1	6-1XS	6-1A/6-2B					
6M-1220	20	2	1 5/8	1 3/8	1/2	1	3/8	1	6-1XS	6-1A/6-2B					
6M-1221	21	2	1 5/8	1 3/8	1/2	1	3/8	1	6-1XS	6-1A/6-2B					
6M-1222	22	2	1 5/8	1 1/2	1/2	1	3/8	1	6-1XS	6-1A/6-2B					
6M-1223	23	2	1 5/8	1 1/2	5/8	1	3/8	1	6-1XS	6-1A/6-2B					
6M-1224	24	2	1 5/8	1 1/2	3/8	1	3/4	1	6-1XS	6-1A/6-2B					
6M-1225	25	2	1 5/8	1 1/2	11/16	1	3/4	1	6-1XS	6-1A/6-2B					
6M-1226	26	2	1 5/8	1 1/2	11/16	1	3/4	1	6-1XS	6-1A/6-2B					
6M-1227	27	2	1 5/8	1 5/8	11/16	1	1	-	6-1XS	6-1A/6-2B					
6M-1228	28	2 1/4	1 5/8	1 3/4	11/16	1 3/8	1	-	6-1XS	6-1A/6-2B					
6M-1229	29	2 1/4	1 5/8	1 3/4	11/16	1 3/8	1	-	6-1XS	6-1A/6-2B					
6M-1230	30	2 1/4	1 5/8	1 3/4	3/4	1 3/8	1	-	6-1XS	6-1A/6-2B					
6M-1231	31	2 1/4	1 5/8	2	3/4	1 1/4	1 1/4	-	6-1XS	6-1A/6-2B					
6M-1232	32	2 1/4	1 3/4	2	13/16	1 1/4	1 1/4	-	6-1XS	6-1A/6-2C					
6M-1233	33	2 1/4	1 3/4	2	13/16	1 1/4	1 1/4	-	6-1XS	6-1A/6-2C					
6M-1234	34	2 1/4	1 3/4	2	7/8	1 1/4	1 1/4	-	6-1XS	6-1A/6-2C					
6M-1235	35	2 1/4	1 3/4	2 1/8	7/8	1 1/4	1 1/4	-	6-1XS	6-1A/6-2C					
6M-1236	36	2 1/4	1 3/4	2 1/8	7/8	1 1/4	1 1/2	-	6-1XS	6-1A/6-2C					
6M-1238	38	2 1/4	1 3/4	2 3/16	1	1 1/4	1 1/2	-	6-1XS	6-1A/6-2C					
6M-1240	40	2 1/2	1 3/4	2 3/8	1 1/8	1 7/16	1 1/2	-	6-1XS	6-1A/6-2C					
6M-1241	41	2 1/2	1 3/4	2 3/8	1 1/8	1 7/16	1 1/2	-	6-1XS	6-1A/6-2C					
6M-1242	42	2 1/2	1 3/4	2 3/8	1 1/8	1 3/8	1 1/2	-	6-1XS	6-1A/6-2C					
6M-1243	43	2 1/2	1 3/4	2 1/2	1 1/8	1 3/8	1 3/4	-	6-1XS	6-1A/6-2C					
6M-1244	44	2 1/2	1 3/4	2 1/2	1 1/8	1 3/8	1 3/4	-	6-1XS	6-1A/6-2C					
6M-1246	46	2 3/4	1 3/4	2 5/8	1 1/8	1 1/2	1 3/4	-	6-1XS	6-1A/6-2C					
6M-1250	50	2 3/4	1 3/4	2 5/8	1 1/8	1 1/2	2	-	6-1XS	6-1A/6-2C					

Features

- SUPERTORQUE® lobular openings for greater turning power without deforming the fastener.
- Designed for maximum engagement on 6 and 12 point fasteners.
- Suitable for use with pneumatic and electric impact wrenches.
- Specially heat treated for impact use to provide long life, safety, and durability.
- Drive end features pin retention hole and groove.