



**JHWSPR-K-14-4/JHWSPR-K-72-6
SuperTorque™ Slotted Flat Tipped
Screwdrivers with Rubber Grip 4 -5
29/32 in x 0,039 - 1/4 in**



PRODUCT DETAILS

- Screwdriver developed in accordance with the Scientific ERGO™ 11 Step Process
- Phosphate finished tip for precise accuracy
- Three-component handle for maximum user comfort, soft material with ridged undermolded material provides superior grip and greater force transmission
- Maximum comfort with minimum effort thanks to our ergonomic design
- Color-coded handle with symbol on the domed end is an easy-to-choose feature for selecting the right tip
- Flat surface on the screwdriver handle limits rolling
- Integrated handle hole allows for hanging on a peg board, securing a lanyard or inserting another screwdriver blade for added leverage
- High-performance hardened alloy steel blade with chrome plating, entirely hardened for protection against corrosion and long tool life
- Standards: ISO 2380 and DIN 5264

PRODUCT ATTRIBUTES

Product								
JHWSPR-K-72-4	.039 in	7/32 in	3 15/16 in	0.2 in	1 1/8 in	4 13/16 in	8 3/4 in	0.15 lb
JHWSPR-K-72-6	.039 in	.21 in	5 29/32 in	0.2 in	1 1/8 in	4 13/16 in	10 45/64 in	0.16 lb
JHWSPR-K-14-5	3/64 in	1/4 in	4 59/64 in	0.24 in	1 3/8 in	4 13/16 in	9 23/32 in	0.25 lb
JHWSPR-K-14-6	3/64 in	1/4 in	5 29/32 in	0.24 in	1 3/8 in	4 13/16 in	10 45/64 in	0.26 lb
JHWSPR-K-56-6	3/64 in	1/4 in	5 29/32 in	0.28 in	1 3/8 in	4 13/16 in	10 45/64 in	0.3 lb
JHWSPR-K-56-7	3/64 in	1/4 in	6 57/64 in	0.28 in	1 3/8 in	4 13/16 in	11 11/16 in	0.31 lb
JHWSPR-K-38-8	1/16 in	25/64 in	7 7/8 in	0.31 in	1 3/8 in	6 11/32 in	14 7/32 in	0.43 lb