



ST-812



WSS-814RC

Features

- SUPERTORQUE® lobular openings for greater turning power without deforming the fastener.
- 8 point sockets are designed for quick engagement on 4 point fasteners.



1/2" DRIVE SHALLOW SOCKETS, 8 POINT, SAE

High-Polished Chrome Finish

Product Code	Size (Inches)	A		B		C		D		E		F	
		OAL (Inches)	Drive End Diameter (Inches)	Working End Diameter (Inches)	Broach Depth (Inches)	Bolt Clearance Depth (Inches)	Bolt Clearance Diameter (Inches)	Nose Length (Inches)					
ST-812	3/8	1 1/2	7/8	29/32	5/16	27/32	5/16	7/8					
ST-814	7/16	1 1/2	7/8	19/16	3/8	27/32	5/16	7/8					
ST-816	1/2	1 1/2	29/32	29/32	13/32	27/32	11/32	-					
ST-818	9/16	1 1/2	31/32	31/32	7/16	27/32	7/16	-					
ST-820	5/8	1 1/2	1 1/16	1 1/16	1/2	27/32	7/16	-					
ST-822	11/16	1 1/2	1 3/16	1 3/16	1/2	27/32	17/32	-					
ST-824	3/4	1 1/2	1 9/32	1 9/32	9/16	13/16	23/32	-					
ST-826	13/16	1 5/8	1 7/16	1 7/16	9/16	31/32	27/32	-					
ST-828	7/8	1 3/4	1 1/2	1 1/2	5/8	1 1/16	15/16	-					
ST-830	15/16	1 13/16	1 5/8	1 5/8	11/16	1 1/8	1 1/32	-					
ST-832	1	1 15/16	1 11/16	1 11/16	11/16	1 1/4	1 1/32	-					
ST-834	1 1/16	1 15/16	1 3/4	1 3/4	23/32	1 1/8	1 1/16	-					
ST-836	1 1/8	2	1 13/16	1 13/16	3/4	1 3/16	13/16	-					
ST-840	1 1/4	2	2	2	25/32	1 3/16	1	-					

Fed. Spec: ANSI B107.1

WSS-814RC 14 Piece 8 Point Socket Set on Clip Rail

Contents Include:

Product Code	Size (Inches)	Product Code	Size (Inches)	Product Code	Size (Inches)	Product Code	Size (Inches)
ST-812	3/8	ST-820	5/8	ST-828	7/8	ST-834	1 1/16
ST-814	7/16	ST-822	11/16	ST-830	15/16	ST-836	1 1/8
ST-816	1/2	ST-824	3/4	ST-832	1	ST-840	1 1/4
ST-818	9/16	ST-826	13/16				



Made in U.S.A.



SD-1224 SD-1216



WSSD-11RC

Features

- SUPERTORQUE® lobular openings for greater turning power without deforming the fastener.
- Designed for quick engagement on both 6 and 12 point fasteners.



1/2" DRIVE DEEP SOCKETS, 12 POINT, SAE

High-Polished Chrome Finish

Product Code	Size (Inches)	A		B		C		D		E		F	
		OAL (Inches)	Drive End Diameter (Inches)	Working End Diameter (Inches)	Broach Depth (Inches)	Bolt Clearance Depth (Inches)	Bolt Clearance Diameter (Inches)	Nose Length (Inches)					
SD-1216	1/2	3 1/4	29/32	3/4	13/32	2 19/32	15/32	2 15/32					
SD-1218	9/16	3 1/4	29/32	13/16	7/16	2 19/32	15/32	2 15/32					
SD-1220	5/8	3 1/4	29/32	29/32	19/32	2 7/16	19/32	-					
SD-1222	11/16	3 1/4	31/32	31/32	17/32	2 11/32	21/32	-					
SD-1224	3/4	3 1/4	1 1/16	1 1/16	19/32	2 9/16	23/32	-					
SD-1225	29/32	3 1/4	1 1/16	1 1/16	21/32	2 9/32	25/32	-					
SD-1226	13/16	3 1/4	1 1/8	1 1/8	21/32	2 9/32	25/32	-					
SD-1228	7/8	3 1/4	1 3/16	1 3/16	23/32	2 9/32	27/32	-					
SD-1230	15/16	3 1/4	1 9/32	1 9/32	3/4	2 9/32	29/32	-					
SD-1232	1	3 1/4	1 11/32	1 11/32	3/4	2 1/4	1	-					
SD-1234	1 1/16	3 1/4	1 7/16	1 7/16	3/4	2 1/4	1 1/16	-					
SD-1236	1 1/8	3 1/4	1 1/2	1 1/2	25/32	2 1/4	1 3/32	-					

Fed. Spec: ANSI B107.1

WSSD-11RC 11 Piece 1/2" Drive Deep 12 Point Socket Set on Clip Rail

Contents Include:

Product Code	Size (Inches)	Product Code	Size (Inches)	Product Code	Size (Inches)
SD-1216	1/2	SD-1224	3/4	SD-1232	1
SD-1218	9/16	SD-1226	13/16	SD-1234	1 1/16
SD-1220	5/8	SD-1228	7/8	SD-1236	1 1/8
SD-1222	11/16	SD-1230	15/16		



Made in U.S.A.